

448141

BOB WILSON  
Geologist



**OGDEN** ENVIRONMENTAL AND ENERGY SERVICES  
■■■■■

4582 So. Ulster Street Pkwy, Suite 415  
Denver, CO 80237  
303 843 6210 Fax 303 843 6215

---

**COTTONWOOD WEST INDUSTRIAL PARK  
PHASE I ENVIRONMENTAL SITE ASSESSMENT  
AND PRELIMINARY PHASE II ANALYSIS**

---



**Submitted by**

**Ogden Environmental and Energy Services Company, Inc.**  
Denver, Colorado 80237

to

**LeisureTime Management Resources, Inc.**  
Lakewood, Colorado 80228

**CONTRACT NO. LT-1-91-092**

**January 17, 1991**

**COTTONWOOD WEST INDUSTRIAL PARK**  
**PHASE I ENVIRONMENTAL SITE ASSESSMENT AND**  
**PRELIMINARY PHASE II ANALYSIS**  
**ARVADA, COLORADO**

Prepared for  
LeisureTime Management Resources, Inc.  
and Resolution Trust Corporation  
555 Zang, Suite 300  
Lakewood, Colorado 80228

by  
Ogden Environmental and Energy Services, Inc.  
Denver Operations  
Standford Place 3, Suite 415  
4582 South Ulster Street Parkway  
Denver, Colorado 80237

*LTMR Contract LT-1-91-092*

JANUARY 17, 1992

## CONTENTS

|  |           |
|--|-----------|
| <b>1.0 INTRODUCTION</b>                              | <b>2</b>  |
| 1.1 PURPOSE  | 2         |
| 1.2 GENERAL SITE INFORMATION                         | 2         |
| 1.2.1 Chain of Title                                 | 4         |
| 1.2.2 Topographical Map Reference                    | 5         |
| <b>2.0 SITE INFORMATION HISTORICAL</b>               | <b>6</b>  |
| 2.1 AERIAL PHOTOGRAPHS                               | 6         |
| 2.2 ENVIRONMENTAL EXTRACTS FROM PRIOR SOIL ANALYSIS  | 6         |
| <b>3.0 SPECIFIC SITE INFORMATION</b>                 | <b>7</b>  |
| <b>4.0 PERSONAL INTERVIEWS</b>                       | <b>8</b>  |
| <b>5.0 CURRENT SITE USE</b>                          | <b>11</b> |
| <b>6.0 ENVIRONMENTAL REGULATION RESEARCH</b>         | <b>12</b> |
| 6.1 FEDERAL AND STATE LISTINGS                       | 12        |
| 6.2 AGENCY INTERVIEWS                                | 14        |
| <b>7.0 SITE RECONNAISSANCE</b>                       | <b>15</b> |
| 7.1 GENERAL DESCRIPTION                              | 15        |
| 7.2 MAGNETIC SURVEY                                  | 16        |
| 7.3 RADIOLOGICAL SURVEY                              | 16        |
| 7.4 pH SURVEY  | 17        |
| 7.5 VISUAL OBSERVATIONS OF ENVIRONMENTAL IMPACTS     | 18        |
| 7.5.1 Upstream                                       | 18        |
| 7.5.2 Adjacent                                       | 18        |
| 7.5.3 Downstream                                     | 18        |
| 7.6 DRIVE TUBE WELL INSTALLATIONS                    | 19        |
| 7.7 SAMPLING AND ANALYSIS                            | 19        |
| 7.7.1 Field GC                                       | 20        |
| 7.7.2 Fixed Base Laboratory (ATI Laboratories, Inc.) | 21        |
| 7.8 SAMPLING AND ANALYTICAL CAVEATS                  | 21        |
| <b>8.0 CONCLUSIONS</b>                               | <b>23</b> |
| <b>9.0 SUMMARY</b>                                   | <b>24</b> |
| <b>10.0 RECOMMENDATIONS</b>                          | <b>25</b> |
| <b>11.0 REPORTING TO GOVERNMENT AGENCIES</b>         | <b>26</b> |

## APPENDICES

## **1.0 INTRODUCTION**

Ogden Environmental Energy Services Company (Ogden) has completed a Phase I Environmental Site Assessment (ESA) at the Cottonwood West Industrial Park (referred to herein as the "property" or "LTMR site." This ESA has been prepared for the exclusive use of LeisureTime Management Resources, Inc. (LTMR) and the Resolution Trust Corporation (RTC).

### **1.1 PURPOSE**

The purpose of the Phase I ESA is to:

- identify the presence of a release or threat of a release of any hazardous substance affecting the property;
- determine the level of compliance with current selective environmental standards, laws, and regulations with respect to the property;
- provide support background for valuation of the property;
- establish baseline information for environmental liability for historical and comparative purposes;
- identify any hazardous substance that may have been utilized, stored, released, or disposed on the property; and
- identify the need for additional testing/monitoring to evaluate the scope, location, source, and nature of any releases, or threat of releases, of hazardous and toxic substances affecting the property or adjacent properties—both public and private.

### **1.2 GENERAL SITE INFORMATION**

The site is located within the east one-half of Section 1, Township 3 South, Range 70 West of the 6th Prime Meridian, Jefferson County, State of Colorado. Specifically, the site is located near W. 68th Place and Joyce Street, Arvada, Colorado. The site consists of six parcels of land with five parcels being within the subdivision Cottonwood West Industrial Park Filing Number 1,

and the sixth parcel being directly south of the subdivision. Please refer to the 1986 Aerial Photograph Site Vicinity Map (1"=200') (Appendix B). The full property legal descriptions are included in Appendix C.

The property is bordered on the north by agricultural land with sparsely scattered single family homes, zoned A-1, City of Arvada. To the east of the property and directly adjacent to the site is Systems Engineering Associates, Inc., a vacant subdivided lot, and B-TEN SYSTEMS INC. Following the eastern boundary to the southern most point is The City of Arvada's Municipal Service Center/Public Works Department.

The Arvada Municipal Service Center houses the Police Department's impoundment yard, the Fleet Services Division, the Traffic and Water Departments, and the Engineering Department's Soil Lab. Adjacent to these facilities are open-air, temporary asphalt stockpiles. Directly east of the stockpiles is the Jefferson County School District's (JCSD's) Arvada Bus Terminal and maintenance yard. All of the land use to the east is zoned Planned Unit Development-Industrial (PUD-I), City of Arvada. Directly to the south of the property is the Croke Canal; south of the canal is a single-family home with a barn and silo surrounded by agricultural land. This land is zoned A-2 Jefferson County Zoning. Directly west of the site is the Croke Canal, and west of the canal is agricultural land with scattered single-family homes. This land is zoned A-2 and is within Jefferson County jurisdiction. The closest major intersection is to the southeast at 64th Avenue and Indiana Street.

The historical use of the site was researched in order to ascertain the probability of past waste disposal. Information researched included the following:

- Chain of Title
- Topographic Maps
- Historical Aerial Photographs (Appendices A and B)
- Geotechnical Site Evaluation; a 1982 Chen and Associates Soil and Foundation Investigation report, which was provided by LTMR is included in Appendix H.
- Soil Conservation Service Maps (Appendix E)
- Personal Interviews

In November 1985, Jefferson County recorded the Cottonwood West Industrial Park Filing 1, located in the City of Arvada. This 25.4-acre subdivision is the northern part of the site located north of Ralston Creek. There are also 13 acres (more or less) located south of the creek, which is also part of the LTMR site (see Figure 1, Appendix D). The subject property was annexed from Jefferson County by the City of Arvada in 1981 and 1982.

### 1.2.1 Chain of Title

The Chain of Title and deed research was conducted at the Jefferson County Court House in the Tax Assessors office and the County Clerk and Records office. Property ownership dating back to 1932 is listed below.

| Date(s)   | Ownership                            |
|---|--------------------------------------|
| Cottonwood West Industrial Park Filing 1<br>(Block 1, Block 2, Block 3, Block 4 Lot 1, Block 4 Lot 2) |                                      |
| Present - March 18, 1988  | Cottonwood West LTD.                 |
| March 18, 1988 - November 21, 1985  | Cottonwood West Industrial Park Inc. |
| November 21, 1985 - July 20, 1981   | Pulse Holding LTD.                   |
| July 20, 1981 - January 22, 1954  | Earl N. & Ruth M. Murray             |
| January 22, 1954 - November 29, 1945  | Arthur H. Meisner                    |
| November 29, 1945 - September 19, 1932  | Joseph H. Parish                     |
| Property South of Cottonwood West Industrial Park Filing 1  |                                      |
| Present - March 18, 1988  | Cottonwood West LTD.                 |
| March 18, 1988 - November 2, 1981   | Cottonwood West Industrial Park      |
| November 2, 1981 - July 20, 1981  | Pulse Holdings LTD.                  |
| July 20, 1981 - January 22, 1954  | Earl N. & Ruth M. Murray             |
| January 22, 1954 - November 29, 1945  | Arthur H. Meisner                    |
| November 29, 1945 - May 28, 1932  | Joseph H. Perish                     |

No industrial or manufacturing interests have occupied the property in the specified time period. Prior to use as a landfill, the land was utilized for agricultural purposes. Although part of the site was planned for commercial development, no such activity was established. Other than the landfill site, the land remains in an agricultural state.

Presently, the subject site is vacant. The City of Arvada has zoned this property PUD-I. This zoning district allows for the construction of planned office/industrial parks.

The northern 25-acre portion of the site was subdivided in 1985 into five parcels: Block 1, Block 2, Block 3, Block 4-Lot 1, and Block 4-Lot 2. Streets and easements have been dedicated to the City of Arvada; but since no development has occurred, the streets have not been constructed.

The southern 13-acre portion of the site has not been subdivided. It is separated from the northern portion of the site by Ralston Creek.

### **1.2.2 Topographical Map Reference**

United States Geological Survey (USGS) 7.5 minute (Golden Quadrangle) topographical maps were reviewed. The most recent quad edition is from a 1965 base with photo-revisions in 1980. The map shows the property to be relatively flat with a slight eastward tilt and lying geographically within the Ralston Creek drainage basin.

## **2.0 SITE INFORMATION HISTORICAL**

### **2.1 AERIAL PHOTOGRAPHS**

Historical aerial photographs were obtained from the City of Arvada Planning Department and the Jefferson County Mapping Department. The photographs examined were dated 1970 and 1986. In 1970, aerial photography revealed undeveloped land with possible agricultural uses north of Ralston Creek. The parcel south of Ralston Creek there is evidence of a landfill excavation with placement of a soil cap over the excavation. Aerial photography dated 1986 shows surface scrapes north of Ralston Creek where proposed roads in the Cottonwood Industrial Park were excavated. Today this parcel is covered by native grasses. The parcel south of Ralston Creek shows natural vegetation with a noticeably raised surface area. Commercial and industrial development is established along the eastern property line.

### **2.2 ENVIRONMENTAL EXTRACTS FROM PRIOR SOIL ANALYSIS**

In 1982, a construction/development firm conducted a preliminary discovery process to determine the bearing capacity and structural suitability for bridge emplacement across Ralston Creek. A soil and foundation investigation report prepared by Chen and Associates Consulting Geotechnical Engineers confirmed the presence of a landfill south of Ralston Creek on a 13-acre tract. The Chen report revealed the presence of explosive levels of methane gas in three wells. This report is in reference to job no. 23,548 dated January 27, 1982, and is presented in Appendix H.

### **3.0 SPECIFIC SITE INFORMATION**

The 25-acre tract north of Ralston Creek consists of hummocky surface conditions probably formed from the removal of topsoil where the proposed roadways were scrapped within the subdivision. Within this area, there is no indication of any environmental problems. South of Ralston Creek, the 13-acre subject site is a flat lying surface condition that has been artificially elevated approximately 5 to 10 ft above the surrounding landscape. This difference in relief is one indication of the presence of landfill material. This surface of fill area is partially unconsolidated and demonstrates signs of subsidence throughout.

According to soil surveys conducted by the USDA Soil Conservation Service, the predominant native soil type at and around the site consists of well-drained clayey soils that formed in material derived from mudstone and shale. The soil service map—located in Appendix E— is composed of an overlay of an aerial photograph that was taken from either 1978 or 1979 orthophotographs.

## **4.0 PERSONAL INTERVIEWS**

On December 23, 1991, Ogden personnel interviewed people living and working in an area within a half-mile radius of the site.

The Arvada Municipal Service Center/Public Works Department borders the property on the southern quarter of the east side. Built in 1975, the Service Center houses several departments. In the past, spoils from Street and Water Department projects were stored on the western side of the property bordering the LTMR site. Presently, asphalt from old streets and roads is temporarily stored there and is later hauled away to be recycled. East of this location is the Police Department's impoundment yard. Southeast of the impoundment yard is the gas shed and two underground unleaded fuel tanks. Kevin Muenchow, fleet services coordinator for the Department, said that an additional two tanks were located there in the past. He directed Ogden to contact Callie Videtich, environmental analyst for the Water Quality and Environmental Services Department for the City of Arvada. Ms. Videtich confirmed that two underground storage tanks were pulled from the Municipal Service Center site on April 4, 1991, and were sent out as scrap iron. The tanks had been leaking. Ms. Videtich stated that the contamination plume from the tanks remains on their property extending 200 ft east toward the Indiana St. and 150 feet north towards JCSD. James McCarthy, Manager of the Arvada Water Quality and Environmental Services Department, concurred with the above information. Maps and documentation of the contamination will be available when the final report is released by the end of January 1992.

JCSD's Arvada Bus Terminal is located 675 ft east of the site and is bordered on the north by 68th Avenue. The terminal, built in 1976, is used for repair and maintenance of school busses. Two underground fuel tanks are located on the property. Patricia Cawfield, legal assistant to Bill Johnson, JCSD's Environmental Compliance Manager, stated that there is soil contamination heading in a north, northeast direction away from the LTMR site. As of November 11, 1991, eight monitoring wells were on the JCSD property, and the County was in the process of developing and implementing a corrective action plan for this contamination.

Bob Monzingo, a 19-year veteran of the Arvada Volunteer Fire Department, said he knew of no "Haz-Mat" responses, major fires, or floods on the LTMR site. His station is located one-half mile southeast of the site.

Jack Mathes, a two-year employee of B-TEN Systems, Inc., 6803 Joyce St., confirmed that dumping has occurred directly south of his building. He did not know the nature or extent of

this activity. This activity would probably occur at the Arvada Municipal Service Center stockpile area, since Ogden personnel did not observe recently dumped material directly on the LTMR site.

Kenneth P. Dixon is an employee of Systems Engineering Associates, Inc., which borders the site on the east and is north of the Arvada Municipal Service Center. During the 11 years that he has been at this location, he has noticed small-scale, farming-type operations in the field north of Ralston Creek. He has seen surveyors on the subject property many times. Mr. Dixon also said that he has noticed fire trucks at Glass Tech Solar, Inc. (GTSI), which is located directly east of his building, across Joyce Street. A few months ago, he saw a Haz-Mat Team removing something from the building. Several people working in the area have expressed concern with GTSI at 6800 Joyce Street. A sticker on the entrance door states that the facility is monitored by an MDA Scientific toxic gas detection system. Scott Brown, President of the now defunct GTSI, is the new owner of the building. He said the gas cylinders that were once stored in the building are gone. The contents of an underground acid tank north of the building had been neutralized, and the tank was removed January 13, 1992. In his opinion, the tank did not leak. Ogden was not able to determine the type of acid stored underground.

Ogden interviewed H.D. Adams on December 27, 1991. Mr. Adams has owned the property immediately south of the Croke Canal since 1972. He remembers the land south of Ralston Creek and north of the canal being farmed for hay and/or oats through the years 1972-1975. He estimates that the landfill, operated by Jefferson County, was closed in the late 1960s or early 1970s but before 1972. Since 1972, he can remember several junk items appearing along Ralston Creek. He recalls no major floods, industrial incidents, or unusual odors on the LTMR subject site.

On December 23, 1991, Ogden personnel interviewed Don Forbes, the owner of Lawn A Mat, a lawn service company. Mr. Forbes' property is across the Croke Canal west of the LTMR site. He has resided on this property since 1958. Tests performed on his well water at that time showed no problems. He knew of no unusual occurrences on the LTMR site. He responded to Ogden's questions about chemicals used in his lawn service company by saying that he had a tank with Trimeck Pesticide. This tank always remains on a truck for transportation to job sites. Ogden was not able to determine the depth of the producing aquifer or geologic formation from which Mr. Forbes gets his water.

Ruth Murray, owner of the LTMR site from 1954 to 1981, presently still owns some acreage across the Croke Canal south-southwest of the LTMR site. When she moved there 38 years ago, Jefferson County was operating the landfill with a guard on duty. She recalls that the landfill was

capped around 1971. Ms. Murray was told by the County that the property could be built upon in 10 years.

Sundstrand Fluid Handling is located southeast, diagonally from the LTMR site. John Randolph has been employed as Plant Engineer since the plant was constructed in 1976. The plant fabricates water pumps and recycles paint thinners and stoddard solvents that comprise its listed waste codes. The only tank on the facility is inside, containing water soluble coolant. The contents of the tank are periodically removed for appropriate disposal. According to Randolph, there is 17 ft of landfill buried in the northern 10 acres of Sundstrand's property. Not wanting to become involved in the waste-stream liability, Sundstrand has not done any testing of the area. Jefferson County has declared that Sundstrand was not involved with the landfill and any fill associated contamination in the area. Randolph has lived near the LTMR site area for over 30 years. Randolph further noted that he personally dumped trash at the site between the years of 1955 to 1967 when the site was a landfill.

Ogden personnel questioned Randolph about the three tanks listed in the Colorado Department of Health's 1989 Underground Storage Tank (UST) Inventory. Randolph confirmed that Sundstrand did have three USTs containing wastewater, waste oil, and petroleum. These three tanks were removed several years ago.

## **5.0 CURRENT SITE USE**

The subject site presently is vacant. The City of Arvada has zoned this property PUD-I (Planned Unit Development-Industrial). This zoning district allows for the construction of planned office/industrial parks.

The northern 25-acre portion of the site was subdivided in 1985 into five parcels: Block 1, Block 2, Block 3, Block 4-Lot 1, and Block 4-Lot 2). Streets and easements have been dedicated to the City of Arvada; but because no development has occurred, the streets have not been constructed, although scars for prior earthwork is present.

The southern 13-acre portion of the site has not been subdivided. It is separated from the northern portion of the site by Ralston Creek and its floodplain restraints.

## **6.0 ENVIRONMENTAL REGULATION RESEARCH**

### **6.1 FEDERAL AND STATE LISTINGS**

#### **CERCLIS (Comprehensive Environmental Response and Liability Information)**

AERRCO (American Ecological Recycle Research Corporation)

T25 RTOW S23+26 (on Highway 72 West of Indiana)

Arvada

Operable Unit = 00

Completion date = 6/1/88

#### **RCRA (Resource Conservation and Recovery Act) Master Facility List**

Cobe Labs Inc. Contact: Gary Wilson

Date: 8/15/80Haz. Waste Codes: D001, F001, F005, V238

EPA ID# = COD000716555

Generator = 1

Sundstrand Fluid Handling Contact: John Randolph

Date: 3/11/87Haz. Waste Codes: D001, F001, F003, F005

EPA ID# = COD095153292

Generator = 2

Systems Engineering Associates, Inc. Contact: Jenene Francis-Novotny

Date: 2/2/87Haz. Waste Codes: D001, F003, F005

EPA ID# = COD981547391

Generator = 2

Glass Tech Solar Inc. Contact: Mike Rosencrans

Date: 8/12/88Haz. Waste Codes: D001, F001, F002, F003

EPA ID# = COD982648438

Generator = 2

**SARA (Superfund Amendments and Reauthorization Act) TITLE III - Toxic Release Inventory**

Cobe Laboratories  
14401 W. 65th Way  
Arvada, CO 80004  
Elain Zummer (303) 231-4243  
75-09-2 Dichloromethane  
76-13-1 Freon 113  
107-68-8 Mathylene BIS (Phenyl Isocyn)

**NPDES (National Pollutant Discharge Elimination System) - none**

**Superfund Sites**

Rocky Flats Plant  
Golden, CO 80402

**TSD (treatment, storage and disposal) List - RCRA facilities - nothing in zip code 80004**

**Underground Storage Tank (Inventory)**

Colorado Highway Department; 1989, 2 tanks  
6555 Indiana St.  
Arvada, CO

Sundstrand - John Randolph; 1989, 3 tanks  
14845 W. 64th Av.  
Arvada, CO 80004

**LUST - Leaking Underground Storage Tanks**

Colorado Highway Department; notification date 01/05/91  
6555 Indiana St.

**Solid Waste Landfills**

| <u>Landfill Name</u>         | <u>Hazard Type</u> | <u>Water Type</u> |
|------------------------------|--------------------|-------------------|
| Ralston Creek-72nd & Indiana | unknown            | refuse            |
| Arvada Shops-66th & Indiana  | unknown            | refuse            |

## 6.2 AGENCY INTERVIEWS

In an effort to discover any past misuse or environmentally relevant occurrences pertinent to the LTMR property, contact was made with the following individuals:

Steve Steigleder, Deputy Fire Marshall at Arvada Fire Station #6, has lived in Arvada for 29 years. He remembers the landfill—described in the Site Reconnaissance Section—as being the major landfill for Northern Jefferson County at that time. He recalls that general rubbish and trash from the community was deposited there. He also stated that all of the hazardous material responses to the area have been only to Glass Tech Solar, Inc. These responses have been to false alarms. There was an underground storage tank that has contained acid near the north side of the building. Scott Brown, the owner of the building states that the tank was removed January 13, 1992.

Colorado Department of Natural Resources; no reclamation permits have been issued for Section 1, T3S, R70W.

Sharon Pansey of the Oil and Gas Commission stated that there are no oil or gas wells within Section 1, T3-S, R70W.

## **7.0 SITE RECONNAISSANCE**

### **7.1 GENERAL DESCRIPTION**

The 40-acre subject site is bisected in a west-to-east direction by Ralston Creek, which is a natural geomorphic surface drainage feature. The active stream channel averages about 5 ft wide, and the flood plain, including natural levies, ranges from 35 ft to 100 ft in width. Water depth was approximately 1 foot. The layout is clearly shown on the aerial photographs in Appendix B. Approximately 25 acres lie on the north side of the creek. Water was running through the property at the time of Ogden's investigation. The stream probably runs year-round and receives recharge from a combination of groundwater, surface runoff, and input from a mechanical canal meter gate at the east bank of the Croke Canal. Therefore, the flow volumes in the stream are highly variable over time. The flux in flow rates would certainly affect the concentration of contaminants that enter the stream from the adjacent buried refuse. These conditions must certainly affect the contaminant impact on the aquatic and wildlife environment of this wetland system. No fish were observed, but abundant algae is present adjacent to the subject property. A Jefferson County document, titled "Jefferson County Health Department, Methane Site Investigation, 1980," establishes the fact that the 13 acres south of the creek were a known landfill. The presence of methane from borehole punch surveys and landfill histories are presented in the above report.

The 13 acres south of the creek contain an abandoned landfill. In January 1982, Chen and Associates Consulting Geotechnical Engineers conducted a "soil and foundation investigation" on behalf of KKBNA (supposedly a land development company). The Chen report is contained in Appendix H of this report. Nine boreholes were drilled. The purpose of this investigation was to determine the structural suitability of the earth to support a bridge across Ralston Creek that would connect the entire proposed commercial development. Three auger holes were drilled on the creek bank to evaluate the weight bearing capacity of the soils. Six additional auger test holes were drilled on the south side of the creek to determine the depth of trash fill. It was determined that the refuse extended vertically from the surface to a depth of 25 ft. The landfill on the subject property represents a portion of a much larger refuse area that borders the subject property on the east, south, and west sides. Refer to the aerial photographs in Appendix B for orientation.

Four of the holes drilled by Chen encountered methane. Since three of the holes reported explosive levels of gas, the area is considered to be a hazard. Two of the Chen-drilled holes are



View looking west. Arvada City Water pumphouse along side Ralston Creek spillway into Croke canal. Note frozen creek water on west side of canal.



Ice formation on Ralston Creek, west of Croke Canal. Stream is visually clean from here westward to Arvada Reservoir.

C-LINE #52564  
4" X 6" PRINTS



View southeasterly along the north western bank of the LTMR site; Croke Canal front and right, gate to Ralston Creek on left. Very high canal banks here.



Landfill Site panorama.



Surface water sample point adjacent to landfill. Note that the stream is unfrozen.



Trash in stream adjacent to landfill on right side of photo. "Water Bed"? Note stream is running. Not iced over.



Ralston Creek adjacent to landfill. Note floating hydrocarbon (petroleum fluorescence) on each side of channel.



Ralston Creek adjacent to landfill. Polarizing lense on camera makes water transparent. Note orange scum and floating petroleum fluorescence next to bank.



Hole #1 with Mobile Drill Rig. Equipment operator for scale.



Pumping for groundwater sample.



Floating algae on main Ralston Creek channel with hydrocarbon sheen at each bank. Note water is not frozen.



Healthy green algae. Note: Petroleum sheen on water surface.

still identifiable at the surface. Both were cased with thin PVC and plugged with a grout; therefore, none were useful for bailing for groundwater sampling.

The Croke Canal meanders through the old landfill and comprises the south and western boundaries of the LTMR site. Water was actively flowing in December—during the time of our investigation. Water in the canal was not sampled for contaminants. There was no obvious visible pollution along the property boundary. However, it may be that the canal is receiving contaminants from the landfill materials. The nature and extent of any contamination was not determined since it is beyond the scope of the Phase I investigation.

## **7.2 MAGNETIC SURVEY**

Ogden conducted a magnetic survey to determine the distribution of buried refuse that is present on the property. This survey was accomplished by physically walking a controlled grid shown on the aerial photograph in Appendix B. The equipment employed was a Fisher model TW6, which is capable of detection to a depth of 30 ft below surface. Such magnetic induction devices respond to most iron metals. The assumption that some metal objects would be distributed ubiquitously within the landfill proved to be correct. It was determined that no landfill refuse is present on the subject property north of Ralston Creek, which is basically raw agricultural land. However, the 13 acres south of the creek is completely covered by landfill material. Some local spots indicated high magnetic responses (anomalies) that may signify large metal objects (e.g., drums). Future Phase II intrusive activities will need to clear these anomalies.

At various places, refuse is exposed. In one instance, newspapers and magazines were found that date back to 1972. Personal interviews revealed that dumping activity took place well into the 1970s, although the Jefferson county records hinted that the dump was closed in the 1950s.

## **7.3 RADIOLOGICAL SURVEY**

Since this landfill resides near the U.S. Department of Energy Rocky Flats Plant nuclear facility, Ogden elected to provide a cursory radiological survey as a courtesy to the client. No radiation materials were expected, but this particular survey was conducted to eliminate the possibility that lost or transient radiological materials might end up in this public dumping facility located so close to a known nuclear facility. A walkover survey was performed using a Ludlum model 19 Micro Rad Survey meter. Several background readings were taken both offsite and onsite, and the background level was 10 mR/hr gamma radiation, which is normal and acceptable.

The site was walked on a 20-foot grid with an approximate meter swing of 5 ft, thereby providing a 25% coverage survey. The maximum meter indication noted was 18 mR/hr, which is normal and acceptable as a natural soil background. These resultant readings are considered negative, thus confirming our assumption that no radiological sources are present on the landfill area.

#### 7.4 pH SURVEY

The pH readings from the drive-tube and the baseline well water sample ranged from 6.32 to 7.90, respectively. Samples taken from within the landfill tend to be more acidic (Table 1). In addition, two pH readings were taken from Ralston Creek within the property boundary.

Table 1. Field parameter data

| Well Hole                   | pH       | Conductivity | PID      | Explosiometer |
|-----------------------------|----------|--------------|----------|---------------|
| 1                           | 7.36     | 923          | NIL      | NIL           |
| 2                           | 7.59     | 1110         | NIL      | NIL           |
| 3                           | 7.84     | 528          | NIL      | NIL           |
| 4                           | *        | *            | .005 ppm | NIL           |
| 5                           | See Note |              |          |               |
| 6                           | 6.32     | 802          | NIL      | NIL           |
| 7                           | See Note |              |          |               |
| 8                           | 7.90     | 403          | NIL      | NIL           |
| Stream Sample<br>(► on map) | 5.56     | 503          | *        | *             |
| Upstream Sample             | 7.61     | 420          | *        | *             |

\*No sample taken.

Note: Wells 5 and 7 are nonexistent.

## **7.5 VISUAL OBSERVATIONS OF ENVIRONMENTAL IMPACTS**

### **7.5.1 Upstream**

None of the visual pollution was observed upstream, to the west side of Croke Canal. A visual survey was made upstream for the approximate distance of one-half mile, and this portion of the stream appeared unpolluted. However, it is appropriate to note that various parts of the upstream areas were frozen, and the ice could have hidden possible visual pollution effects in case some of the floating oils and/or orange-colored material has floated downstream from offsite of the Cottonwood Park property.

### **7.5.2 Adjacent**

Ralston Creek appears to be receiving contamination directly from the landfill. Visual contamination is apparent on the surface of the stream and along the shoreline. Actual refuse is in the stream channel (see photographs), and an oil scum is floating on the surface. There is orange discoloration of the channel bottom materials and submerged algae. This discoloration is possibly caused by oxidizing and/or acidizing fluids that periodically emit from the landfill. The floating oils and probable corrosive fluids that caused the orange discoloration of the stream probably entered Ralston Creek from the exposed landfill refuse that border the flood plain next to the subject property. There is no indication that these potential pollutants migrated onto the property from upstream. There is abundant green algae present in the stream for this time of the year, and it is more prolific adjacent to the landfill. The active growth algae colonies are likely enhanced due to nutrients emitting from the landfill, such as phosphorous and nitrogen.

### **7.5.3 Downstream**

The Ralston Creek flood plain is a public recreation facility in this area. There is a cement bicycle path that parallels the stream. The western limit of the paved bike path actually begins on the subject property and extends eastward. A downstream inspection also was made approximately one-quarter mile east of the property, and visible pollution is present.

It is a striking contrast that the upstream portion of Ralston Creek was frozen, in addition to being visually clear, and unfrozen adjacent to the subject landfill. Hydrocarbons, acids, and dissolved solids may provide an "antifreeze" effect that prevents the stream from freezing at the ambient temperatures, which existed during the time of our investigation. All stream pH readings were taken by hand-held equipment. Values recorded ranged from 5.56 to 7.11 adjacent to the landfill (refer to Table 1). Floating hydrocarbons could have a buffer effect.

and thus a broad range of pH measurements are explainable. Other variables that usually affect pH values are variable effluent sources and biologic activity.

## **7.6 DRIVE TUBE WELL INSTALLATIONS**

Part of this environmental site assessment effort was to acquire groundwater and surface water samples from the property. The 1982 Chen drilling activity revealed explosive levels of methane emanating from the subsurface. Methane is a common component of landfills and originates from the decay of buried organic material in the refuse. Since it was thus established that methane is present, Ogden utilized a drive tube technique of installing monitoring wells. The drive tube system is very cost effective and somewhat safer to operate in a potentially explosive atmosphere.

Six drive tube wells were installed and left in place for future sampling opportunity. Well #8 was placed north of the creek as a baseline control. The 25 acres north of the creek are basically raw agricultural land, although some shallow surface scraping has scarred the land. The earth moving was obviously the beginning of a construction effort to develop the Cottonwood land parcel. The effect can be viewed on the aerial photos (Appendix B). No other industrial or commercial activity is apparent, and no landfill material is present, so it was felt that this portion of the property would suffice for baseline analytical control.

For safety considerations, in addition to methane detection, a portable explosimeter and a portable photoionization detector (PID) were utilized. Each drive tube installation was monitored. Surprisingly, negligible levels of methane were detected. Only hole #4 demonstrated one-half of one percent by volume, volatile gasses. Comparing the 10-year old Chen report, where explosive levels of gas were reported, our measurements are unexpectedly on the low side. Cold air temperatures could have had a suppression effect, or biologic reduction of land fill organics may have declined over time.

## **7.7 SAMPLING AND ANALYSIS**

A total of six water samples were taken and analyzed for pH, volatile organics, and metals. One composite soil sample was taken for metal analysis. Note the aerial photographs in Appendix B for locations of wells and surface samples. All samples of water and soil were taken in accordance with standard EPA procedures. Laboratory reports for both the mobile/field gas chromatograph (GC) and the fixed-base GC/MS are located in Appendices I and F, respectively.

Water samples were collected to analyze for (VOA) volatile organics in two, 40-milliliter amber glass vials having a teflon-coated silicon septum. The vials contained no preservative and were filled in a manner to ensure that no headspace or bubbles were present. A total metals sample was also collected in a 1-liter polycarbonate, plastic container. The sample was preserved with 3 mL of nitric acid ( $\text{HNO}_3$ ) in order to adjust the pH to less than 2. An oil and grease sample containing no preservative was collected in a 1-liter amber glass jar with a teflon-coated septum. All containers were filled using a direct immersion method.

Soil samples were taken from two areas. A VOA sample was collected from an area of darkly-stained soil near borehole #4 in a 2-oz glass jar having a teflon-coated lid insert. The soil was lightly compressed into the jar providing zero headspace. An identical suite of samples was collected from a location approximately 150 ft north and slightly west of the dark stain. Samples were collected from an embankment that was eroded to expose strata of fill materials. These two samples were composited and submitted to the laboratory for total lead and polychlorinated biphenyls (PCBs).

Samples collected and analyzed are as follows:

- Field GC—five groundwater and one surface water, non-acid preserved
- ATI Laboratories—one groundwater for VOA, non-acid preserved
- ATI Laboratories—one groundwater for total lead, acid preserved with nitric acid ( $\text{HNO}_3$ ) to a pH of 2.0
- ATI Laboratories—one composite soil for PCBs and total lead
- ATI Laboratories—one soil for volatile organic analysis

#### **7.7.1 Field GC**

Six samples were taken and immediately analyzed in the field. A mobil GC was used to evaluate the samples for BTEX (benzene, toluene, ethylbenzene, xylenes). All field analyses data are located in Appendix I. Drive tube well numbers 1, 2, 3, 6, and 8 were analyzed, as well as one sample taken from Ralston Creek. Well number 8 (see aerial photo) was designated as the baseline control point for groundwater data comparisons within the subject property boundary.

None of the six samples analyzed in the field showed elevated levels from BTEX compounds.

## **7.7.2 Fixed Base Laboratory (ATI Laboratories, Inc.)**

### **7.7.2.1 Water**

One water sample was taken from borehole #6 in the center of the landfill, and one composite soil sample was taken directly from landfill cover.

The water was analyzed for volatile organics by EPA Method 8240, and nothing significant was noted.

The values in Appendix E are considered to be minimum and probably indicate sources of volatile organic materials buried in the landfill.

The water was also analyzed for total lead by EPA Method 239.1 and was found to contain an elevated level of lead that exceeds EPA drinking water standards.

### **7.7.2.2 Soil**

One composite soil sample was collected and analyzed for PCBs by EPA Method 8080 and for volatile organics by EPA Method 8240. The sample was found to contain trichlorofluoromethane (freon) and also lead at elevated levels. The test for PCB was negative. The soil sample also contained elevated levels of volatile organics. Methylene chloride, acetone, 1,1,1-trichloroethane, tetrachloroethane, ethylbenzene, toluene, and total xylenes were all present.

### **7.7.2.3 Stream water**

One surface water sample was taken from Ralston Creek to analyze for petroleum by EPA Modified Method 8015. The water was skimmed so as to collect as much floating product as possible. The compound was identified as diesel grade fuel oil (Appendix F). In addition, the laboratory also observed some late-eluting chromatographic peaks that indicate the presence of high molecular weight components, but these components could not be positively identified.

## **7.8 SAMPLING AND ANALYTICAL CAVEATS**

The drive tube wells were placed at 12 to 15 ft total depth below surface and were generally terminated at "refusal point." This means that these small-bore wells were not able to penetrate a sufficient depth into the harder ground below soil development and trash fill. The Chen drilling

activity reported groundwater levels to be around 10 to 12 ft below ground surface. Therefore, we assumed that drive tubes would be placed below the water table.

At the beginning of the project while sampling with drive tubes, we anticipated obtaining adequate groundwater samples. Surprisingly, the pumping of water from the wells proved very difficult. It is common and expected that water tables fluctuate from season to season. We were able to obtain minimum samples from five of the six drive tube wells. Hard suction pumping can result in the loss of volatile organics from samples. Since the analytical results on samples taken from this site were low, it makes the outcome of nondetect or relatively low levels of VOAs suspect. For any future site characterization activity, a bailing method and/or submersible bladder pump is preferable. However, the December 1991 sampling activity raised questions about the water table and our ability to identify and/or characterize contaminants with such a cursory level of effort dictated by a Phase I Site Assessment approach.

In the landfill, there is very likely a perched water table. This could be caused by "clay lifts" within the landfill. The underlying permanent water table must certainly be affected by the level of the Croke Canal seasonally. The banks of the canal were not measured for this report, but the Croke Canal is unusually deep (estimated 30- to 35-foot banks) on the subject site. The water to feed Croke Canal is supplied from Clear Creek.

There is also the man made Ralston/Arvada Reservoir and associated water treatment plant approximately two miles upstream. This reservoir is used for limited public recreation and also as a culinary water supply locally.

In addition, there is a large pumping facility immediately adjacent to the LTMR site. This pumping station was built by the Army Corps of Engineers and is now operated by the City of Arvada. It is for the purpose of extracting water from Croke Canal and pumping it up hydrological gradient, into Ralston/Arvada Reservoir.

These man made and artificially operated water mechanisms most certainly have significant effects on groundwater elevations. Artificial controls, combined with natural seasonal meteoric events, will cause large fluctuations in groundwater dynamics, water table elevations, and vadose zone moisture contents.

## 8.0 CONCLUSIONS

Caution should be taken when excavating in, or adjacent to, landfill materials. Proper ventilation of excavations and/or buildings will be required. Any structures built on or immediately adjacent to the landfill will require special explosive gas controls. Also, roads, parking areas, underground utilities and other facilities may be subjected to differential compaction and corrosive environments.

No contaminants were identified in the portable field GC analytical results. However, only BTEX compounds were analyzed. However, the fixed-base laboratory results indicated the presence of elevated levels of lead in the borehole water sample and soil sample. Volatile organic compounds were also detected in the soil sample near borehole #4. These results indicate that a more thorough monitoring program should be implemented.

From the methane levels reported by Chen in 1982 and our observations of visual hydrocarbons in Ralston Creek, a curious situation arises. We feel that the permanent unconfined groundwater table may be deeper than the drive tube well method was able to penetrate. In addition, many pollutants have a specific gravity greater than one, therefore these heavy compounds would seek lower elevations in the ground water aquifer. The penetrations that we made were not likely to have been deep enough to sample "heavy" contaminants. Indeed, it is possible that the drive tube efforts intersected either perched "water," or even under-saturated vadose pods. It appears that the drive tubes, and/or previously drilled Chen auger holes, are not deep enough to effectively collect representative groundwater samples.

It is apparent at this time that the "nature and extent" of pollution emanating from the landfill is not determinable with the Preliminary Phase II level of effort. However, the recently collected information is valid and acceptable, to plan further evaluations in progress toward an actual "site characterization."

The vacant land adjoining the LTMR site west of Croke Canal has been designated for use as "Jefferson County Parks Open Area." The subject site may, at some time in the future, become useful for open area park type of utilization. This could require some level of clean-up if the Ralston Creek area is confirmed to be contaminated. A comprehensive Phase II site assessment would need to be developed and implemented to make this determination. As part of any Phase II assessment, the impact of surrounding activities needs to be assessed (i.e., commercial nursery, use of pesticides, etc.).

## 9.0 SUMMARY

The following are pertinent data derived from the Ogden Phase I environmental assessment:

- There is an inactive landfill on the LTMR site south of Ralston Creek.
- The 25 acres of the LTMR site north of Ralston Creek does not appear to have been impacted by human activities.
- The property that borders the south bank of Ralston Creek appears to be polluted by discharges from the landfill. Visible hydrocarbons are on the water surface.
- Groundwater samples from the landfill contain lead at concentrations of .0065 mg/L, which is above the EPA drinking water standard of .0050 mg/L.
- Soil samples from the landfill contain volatile organic compounds. Offending analytes are methylenechloride, acetone, tetrachloroethane, toluene, and total xylenes.
- A composite soil sample demonstrated an excessive concentration of lead in the amount of 54 mg/kg.

## 10.0 RECOMMENDATIONS

Based on the evaluation of prior data and data collected during the Preliminary Phase II site assessment, it is probable that contaminants are present on the site and that the potential for migration to offsite localities exists. Therefore, we would recommend the following activities to more clearly define the extent and nature of contamination on the LTMR site:

- Excavate spot locations of high magnetic response to determine if leaking drums are present.
- Design a statistically-based random soil sampling program.
- Design a statistically-based groundwater sampling program.
- Install deeper auger drilled monitoring wells at 30 to 50 ft depth.
- Case with large enough PVC for retrieving samples by bailing or the bladder pump method.
- Screen shallow groundwater monitoring wells in the landfill material and schedule sampling to be collected to allow for seasonal flux of contaminants.
- Determine perched water elevation.
- Selectively screen below landfill in permanent water table at low aquifer confining elevations to test for heavy compounds. Determining permanent water table and, if possible, the lower base confining depth.
- Schedule interval time sampling for surface water monitoring of Ralston Creek. Identify flora/fauna kill mechanisms.
- Landfill area should not be developed for commercial or residential construction.
- Monitor contemporary methane presence.

## **11.0 REPORTING TO GOVERNMENT AGENCIES**

Low levels of lead were identified in water and soil samples taken from the landfill area. The concentrations in the water did exceed EPA drinking water standards. Therefore, it is necessary to report the findings to the Colorado Department of Health (CDH) and also to the Jefferson County Health Department. Since Colorado is a "primary state," the CDH will report to the EPA, should it be deemed necessary.

One original report containing the lead in water concentration values should be sent to:

Mr. Glenn Mallory  
Solid Waste Unit Leader  
Colorado Department of Health  
Hazardous Materials and Waste Management  
4210 East 11th Avenue  
Denver, Colorado 80220-3716

A carbon copy should also be sent to:

Mr. Cliff Myers  
Environmental Health Division  
Jefferson County Health Department  
260 South Kipling  
Lakewood, Colorado 80226

## **APPENDIX A**

### **1970 AERIAL PHOTOGRAPH - SITE VICINITY MAP, PRECOMMERCIAL DEVELOPMENT**



**APPENDIX A**

**1970 Aerial Photograph  
Site Vicinity Map  
Precommercial Development**



**DEPARTMENT OF PLANNING**

**COUNTY OF JEFFERSON  
STATE OF COLORADO**

**1829 01**

**APPR. SCALE 1"=200'**

**DATE 6-70**

## **APPENDIX B**

### **1986 AERIAL PHOTOGRAPH**

- 1) Survey Traverse Grid for Magnetic Survey and Radiological Survey
- 2) Drive tube well locations
- 3) ► = water sample taken from Ralston Creek
- 4) Site specific landfill boundary-highlighted in yellow

# .ORADO

**C Repro Inc.**

80011

PHOTO MAP

**S.            T.            R.**



A horizontal scale bar with markings at 0, 100, 200, 300, and 400. The word "SCALE" is above the 0 mark, "IN" is above the 200 mark, and "FEET" is above the 400 mark.

DATE \_\_\_\_\_

[illegible]

## **APPENDIX C**

### **LEGAL DESCRIPTION AND ACCOMPANYING MAP**

Recorded at \_\_\_\_\_ o'clock \_\_\_\_\_ M.  
Reception No. \_\_\_\_\_

RECORDED IN  
COUNTY OF JEFFERSON  
STATE OF COLORADO  
RECEPTION NO. 88040360  
04/28/88 10:20 9.00

THIS DEED, Made this 18th day of March  
19 88, between

COTTONWOOD WEST INDUSTRIAL PARK INC.  
a Colorado Corporation  
of the City and County of DENVER and State of Colo-  
rado, of the first part, and  
COTTONWOOD WEST LTD.  
a Colorado limited partnership \*\*\*\*  
of the  
County of DENVER and State of Colorado, of the second  
part;

WITNESSETH. That the said party of the first part, for and in consideration of the sum  
of TEN DOLLARS AND OTHER GOOD AND VALUABLE CONSIDERATION

Dollars,  
to the said party of the first part, in hand paid by the said party of the second part, the  
receipt whereof is hereby confessed and acknowledged, has granted, bargained, sold and conveyed,  
and by these presents does grant, bargain, sell, convey and confirm unto the said party of  
the second part, its heirs and assigns forever, all the following described lot or parcel  
of land, situate, lying and being in the County of JEFFERSON and State of  
Colorado, to wit:

SEE EXHIBIT A ATTACHED HERETO FOR LEGAL DESCRIPTION  
SEE EXHIBIT B ATTACHED HERETO FOR ADDITIONAL PROVISIONS

\*\*\*\* c/o Gibraltar Companies  
Denver Corporate Center Tower III  
7900 E. Union Avenue Suite 850  
Denver, Co. 80237

also known as street and number vacant land

Together with all and singular the hereditaments and appurtenances thereunto belonging, or in any-  
wise appertaining, and the reversion and reversions, remainder and remainders, rents, issues and  
profits thereof; and all the estate, right, title, interest, claim and demand whatsoever, of the said  
part of the first part, either in law or equity, of, in and to the above bargained premises, with  
the hereditaments and appurtenances; TO HAVE AND TO HOLD the said premises above bar-  
gained and described, with the appurtenances, unto

the said party of the second part, its  
heirs and assigns forever.

And the said  
part y of the first part, for it sel its heirs, executors and  
administrators, does covenant, grant, bargain and agree to and with the said part y of the  
second part, its heirs and assigns, the above bargained premises in the quiet and peaceable  
possession of said part y of the second part, its heirs and assigns, against all and every  
person or persons lawfully claiming or to claim the whole or any part thereof, by, through or under  
the said part y of the first part to WARRANT AND FOREVER DEFEND.


IN WITNESS WHEREOF, The said part y of the first part has hereunto set its  
hand and seal the day and year first above written.

Signed, Sealed and Delivered in the presence of [SEAL]  
COTTONWOOD WEST INDUSTRIAL  
PARK INC. [SEAL]  
James Moilanen, Pres. [SEAL]

STATE OF COLORADO,  
County of } ss.

The foregoing instrument was acknowledged before me this \_\_\_\_\_ day of March  
1988 by James Moilanen, President of Cottonwood West Industrial  
Park Inc., a Colorado corporation

My Commission expires 4/11/88, 19 \_\_\_\_\_ Witness my hand and official seal.



14612341 Denver 80237

EXHIBIT A  
TO SPECIAL WARRANTY DEED  
DATED MARCH 18, 1988

2  
2

Lot 7  
Cottonwood Park in Ralston Valley

and

A portion of the East 1/2 of Section 1, Township 3 South, Range 70 West of the 6th P.M., more particularly described as follows: Beginning at the Northeast corner of the Northwest 1/4 of the Southeast 1/4 of said Section 1; thence South 00 degrees 03 minutes 01 seconds East along the Easterly line of said Northwest 1/4 of the Southeast 1/4, 463.77 feet to the Northerly right-of-way line of the Croke Canal; thence Northwest along said Northerly right-of-way line the following 8 courses: (1) thence North 82 degrees 50 minutes 54 seconds West, 150.11 feet to a point of curve; (2) thence along a curve to the right having a radius of 963.78 feet, a central angle of 11 degrees 23 minutes 39 seconds, 191.66 feet to a point of tangent; (3) thence North 71 degrees 27 minutes 15 seconds West along said tangent, 276.15 feet to a point of curve; (4) thence along a curve to the right having a radius of 208.06 feet, a central angle of 37 degrees 31 minutes 18 seconds, 136.26 feet to a point of tangent; (5) thence North 33 degrees 55 minutes 57 seconds West along said tangent, 557.70 feet to a point of curve; (6) thence along a curve to the right having a radius of 388.56 feet, a central angle of 39 degrees 23 minutes 06 seconds, 267.10 feet to a point of tangent; (7) thence North 05 degrees 27 minutes 09 seconds East along said tangent, 755.43 feet to a point of curve; (8) thence along a curve to the right having a radius of 565.00 feet, a central angle of 09 degrees 47 minutes 25 seconds, 96.54 feet to the Northerly line of the Southwest 1/4 of the Northeast 1/4 of said Section 1; thence South 89 degrees 27 minutes 29 seconds East along said Northerly line, 991.49 feet to the Northeast corner of said Southwest 1/4 of the Northeast 1/4; thence South 00 degrees 03 minutes 48 seconds West along the Easterly line of said Southwest 1/4 of the Northeast 1/4, 1320.46 feet to the point of beginning.

Also known as All of Blocks 1, 2, 3, and 4  
Cottonwood West Industrial Park Filing No. 1,  
All situate in the County of Jefferson,  
State of Colorado

RECEPTION NO. 88040360

EXHIBIT B  
TO SPECIAL WARRANTY DEED  
DATED MARCH 18, 1988

3

3

By accepting this conveyance, second party hereby assumes and agrees to pay that certain obligation evidenced by that certain Promissory Note dated January 10, 1985 in the principal amount of \$2,425,000.00 payable to Otero Savings and Loan Association, secured by that certain Deed of Trust recorded January 11, 1985 under Reception No. 85003626, Jefferson County, Colorado public records, as said Note and Deed of Trust have been subsequently modified. Second party's assumption and agreement to pay the foregoing obligation includes its assumption and ratification of the acts of certain third parties as evidenced by instruments recorded at Reception Numbers 85003627, 86006149, 86088951 and 86088952, even if those parties had no authority to complete or perform those acts.

RECEPTION NO. 88040360

# DEDICATION:

NOW ALL MEN BY THESE PRESENTS: THAT THE UNDERSIGNED, BEING THE OWNERS OF A PARCEL OF LAND IN THE EAST 1/2 OF SECTION 1, TOWNSHIP 3 SOUTH, RANGE 70 WEST OF THE 6TH P.M., CITY OF ARVADA, COUNTY OF JEFFERSON, STATE OF COLORADO, MORE PARTICULARLY DESCRIBED AS FOLLOWS:

COMMENCING AT THE NORTHEAST CORNER OF SAID SECTION 1; THENCE SOUTH 00°02'54" EAST, ALONG THE EAST LINE OF THE NORTHEAST 1/4 OF SAID SECTION 1, A DISTANCE OF 1323.58 FEET TO THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1; THENCE NORTH 89°39'54" WEST, ALONG THE NORTH LINE OF SAID SOUTHEAST 1/4 OF THE NORTHEAST 1/4 A DISTANCE OF 1322.17 FEET TO THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1, THE TRUE POINT OF BEGINNING; THENCE SOUTH 00°11'39" EAST, ALONG THE EAST LINE OF SAID SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND ALONG THE WEST LINE OF LOT 1, RESUBDIVISION OF LOTS 5 AND 6, COTTONWOOD PARK IN RALSTON VALLEY, A SUBDIVISION RECORDED IN THE OFFICE OF THE JEFFERSON COUNTY CLERK AND RECORDER UNDER RECEPTION NUMBER 79058658, A DISTANCE OF 313.56 FEET; THENCE NORTH 89°47'39" EAST, ALONG THE SOUTH LINE OF SAID LOT 1, A DISTANCE OF 250.22 FEET TO A POINT ON THE WEST RIGHT-OF-WAY LINE OF JOYCE STREET; THENCE ALONG THE WEST RIGHT-OF-WAY LINE OF JOYCE STREET THE FOLLOWING THREE (3) COURSES:

- (1) SOUTH 29°55'40" WEST, A DISTANCE OF 68.23 FEET TO A POINT OF CURVE;
- (2) ALONG THE ARC OF A CURVE TO THE LEFT WITH A RADIUS OF 125.13 FEET AND A CENTRAL ANGLE OF 29°26'36" A DISTANCE OF 64.30 FEET, THE LONG CHORD OF WHICH BEARS SOUTH 15°12'22" WEST, A DISTANCE OF 63.60, TO A POINT OF TANGENCY;
- (3) SOUTH 00°29'04" WEST, A DISTANCE OF 201.41 FEET;

THENCE ALONG THE NORTH LINE OF LOT 18, COTTONWOOD PARK IN RALSTON VALLEY, A SUBDIVISION RECORDED IN THE OFFICE OF THE JEFFERSON COUNTY CLERK AND RECORDER IN BOOK 55 AT PAGE 11 THE FOLLOWING TWO (2) COURSES:

- (1) SOUTH 71°50'32" WEST, A DISTANCE OF 150.35 FEET;
- (2) NORTH 68°52'48" WEST, A DISTANCE OF 57.62 FEET TO A POINT ON THE EAST LINE OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1;

THENCE SOUTH 00°11'39" EAST, ALONG THE EAST LINE OF SAID SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND ALONG THE WEST LINE OF SAID LOT 18, A DISTANCE OF 104.00 FEET; THENCE SOUTH 53°57'00" WEST, A DISTANCE OF 542.86 FEET; THENCE NORTH 80°49'37" WEST A DISTANCE OF 464.19 FEET; THENCE SOUTH 84°04'28" WEST, A DISTANCE OF 154.44 FEET TO A POINT ON THE EASTERLY RIGHT-OF-WAY LINE OF THE CROAK CANAL; THENCE ALONG THE EASTERLY RIGHT-OF-WAY LINE OF SAID CROAK CANAL THE FOLLOWING THREE (3) COURSES:

- (1) ALONG THE ARC OF A NON-TANGENT CURVE TO THE RIGHT WITH A RADIUS OF 388.56 FEET AND A CENTRAL ANGLE OF 27°49'12" A DISTANCE OF 180.67 FEET, THE LONG CHORD OF WHICH BEARS NORTH 08°39'33" WEST, A DISTANCE OF 186.82 FEET TO A POINT OF TANGENCY;
- (2) NORTH 05°15'03" EAST, A DISTANCE OF 755.43 FEET TO A POINT OF CURVE;
- (3) ALONG THE ARC OF A CURVE TO THE RIGHT WITH A RADIUS OF 565.00 FEET AND A CENTRAL ANGLE OF 09°47'20" A DISTANCE OF 96.53 FEET, THE LONG CHORD OF WHICH BEARS NORTH 10°08'43" EAST, A DISTANCE OF 96.41 FEET TO A POINT ON THE NORTH LINE OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION;

THENCE SOUTH 89°39'54" EAST, ALONG THE NORTH LINE OF SAID SOUTHWEST 1/4 OF THE NORTHEAST 1/4, A DISTANCE OF 990.20 FEET TO THE TRUE POINT OF BEGINNING. CONTAINING 25.486 ACRES.

HAVE LAID OUT, PLATTED, AND SUBDIVIDED THE ABOVE DESCRIBED LAND, UNDER THE NAME AND STYLE OF COTTONWOOD WEST INDUSTRIAL PARK FILING NO. 1, AND BY THESE PRESENTS DO DEDICATE TO THE CITY OF ARVADA IN FEE SIMPLE THE STREETS AND PUBLIC WAYS AS SHOWN ON THE PLATS, AND GRANTS TO THE PUBLIC UTILITIES, AND THE CITY OF ARVADA, THE RIGHT TO INSTALL, MAINTAIN, AND OPERATE MAINS, TRANSMISSION LINES, SERVICE LINES, AND APPURTENANCES, AS MAY BE NECESSARY TO PROVIDE SUCH UTILITY, CABLE TELEVISION, AND SANITARY SERVICES WITHIN THIS SUBDIVISION OR PROPERTY CONTIGUOUS THERETO, THROUGH, OVER, UNDER, AND ACROSS STREETS, UTILITY AND OTHER EASEMENTS, AND OVER PUBLIC PLACES AS SHOWN ON THE PLAT.

COTTONWOOD WEST INDUSTRIAL PARK, INC., A COLORADO CORPORATION.

BY: Dennis M. Van  
PRESIDENT

ATTEST: D. Robert Clary  
Assistant Secretary  
SEAL

STATE OF COLORADO }  
COUNTY OF } ss

THE FOREGOING INSTRUMENT WAS ACKNOWLEDGED BEFORE ME THIS 21<sup>st</sup> DAY OF October, A.D., 1985, BY THE ABOVE PARTIES.

WITNESS MY HAND AND SEAL.  
MY COMMISSION EXPIRES 7-26-89

NAME Julia A. Mayes  
ADDRESS 828 So. Omaha  
Denver, CO 80224

HOLDER OF DEED OF TRUST

EARL N. MURRAY

RUTH M. MURRAY



## LEGAL DESCRIPTION

A PORTION OF THE EAST HALF OF SECTION 1, TOWNSHIP 3 SOUTH, RANGE 70 WEST OF THE SIXTH PRINCIPAL MERIDIAN, COUNTY OF JEFFERSON, STATE OF COLORADO, WHICH CONSIDERING THE EAST LINE OF THE SOUTHEAST 1/4 OF SAID SECTION 1 AS BEARING NORTH 00°02'49" WEST AND WITH ALL BEARINGS CONTAINED HEREIN RELATIVE THERETO IS MORE PARTICULARLY DESCRIBED AS FOLLOWS:

COMMENCING AT THE NORTHEAST CORNER OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 1; THENCE NORTH 89°32'02" WEST, ALONG THE NORTH LINE OF SAID NORTHEAST 1/4 OF THE SOUTHEAST 1/4, A DISTANCE OF 1318.84 FEET TO THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 1, THE TRUE POINT OF BEGINNING; THENCE SOUTH 00°15'07" EAST, ALONG THE EAST LINE OF SAID NORTHWEST 1/4 OF THE SOUTHEAST 1/4, A DISTANCE OF 463.77 FEET TO A POINT ON THE NORTHERLY RIGHT-OF-WAY LINE OF THE CROKE CANAL; THENCE NORTHWESTERLY ALONG SAID NORTHERLY RIGHT-OF-WAY LINE THE FOLLOWING EIGHT (8) COURSES:

- (1) NORTH 83°03'00" WEST, A DISTANCE OF 150.11 FEET TO A POINT OF CURVE;
- (2) ALONG THE ARC OF A CURVE TO THE RIGHT WITH A RADIUS OF 963.78 FEET AND A CENTRAL ANGLE OF 11°23'39" A DISTANCE OF 191.66 FEET; THE LONG CHORD OF WHICH BEARS NORTH 77°21'10" WEST, A DISTANCE OF 191.35 FEET TO A POINT OF TANGENT;
- (3) NORTH 71°39'21" WEST, A DISTANCE OF 276.15 FEET TO A POINT OF CURVE;
- (4) ALONG THE ARC OF A CURVE TO THE RIGHT WITH A RADIUS OF 208.06 FEET AND A CENTRAL ANGLE OF 37°31'18" A DISTANCE OF 136.26 FEET, THE LONG CHORD OF WHICH BEARS NORTH 52°53'42" WEST, A DISTANCE OF 133.83 FEET TO A POINT OF TANGENT;
- (5) NORTH 34°08'03" WEST, A DISTANCE OF 557.70 FEET TO A POINT OF CURVE;
- (6) ALONG THE ARC OF A CURVE TO THE RIGHT WITH A RADIUS OF 388.56 FEET AND A CENTRAL ANGLE OF 39°23'06" A DISTANCE OF 267.10 FEET, THE LONG CHORD OF WHICH BEARS NORTH 14°26'30" WEST, A DISTANCE OF 261.87 FEET TO A POINT OF TANGENT;
- (7) NORTH 05°15'03" EAST, A DISTANCE OF 755.43 FEET TO A POINT OF CURVE;
- (8) ALONG THE ARC OF A CURVE TO THE RIGHT WITH A RADIUS OF 565.00 FEET AND A CENTRAL ANGLE OF 09°47'20" A DISTANCE OF 96.53, THE LONG CHORD OF WHICH BEARS NORTH 10°08'43" EAST, A DISTANCE OF 96.41 FEET TO A POINT ON THE NORTH LINE OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1;

THENCE SOUTH 89°39'54" EAST ALONG SAID NORTH LINE, A DISTANCE OF 990.20 FEET TO THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1; THENCE SOUTH 00°11'39" EAST, ALONG THE EAST LINE OF SAID SOUTHWEST 1/4 OF THE NORTHEAST 1/4, A DISTANCE OF 313.56 FEET TO THE NORTHWEST CORNER OF LOT 7, COTTONWOOD PARK IN RALSTON VALLEY, RECORDED IN BOOK 55 AT PAGE 10 IN THE RECORDS OF JEFFERSON COUNTY; THENCE NORTH 89°47'39" EAST, ALONG THE NORTH LINE OF SAID LOT 7, A DISTANCE OF 250.22 FEET TO THE NORTHEAST CORNER OF SAID LOT 7; THENCE SOUTHERLY ALONG THE WESTERLY RIGHT-OF-WAY LINE OF JOYCE STREET THE FOLLOWING THREE (3) COURSES:

- (1) SOUTH 29°55'41" WEST, A DISTANCE OF 68.23 FEET TO A POINT OF CURVE;
- (2) ALONG THE ARC OF A CURVE TO THE LEFT WITH A RADIUS OF 125.00 FEET AND A CENTRAL ANGLE OF 29°26'36" A DISTANCE OF 64.30 FEET, THE LONG CHORD OF WHICH BEARS SOUTH 15°12'49" WEST, A DISTANCE OF 63.60 FEET TO A POINT OF TANGENT;
- (3) SOUTH 00°29'04" WEST A DISTANCE OF 201.41 FEET; THENCE ALONG THE SOUTHERLY LINE OF SAID LOT 7 THE FOLLOWING TWO (2) COURSES:
  - (1) SOUTH 71°50'32" WEST, A DISTANCE OF 150.35 FEET;
  - (2) NORTH 68°52'48" WEST, A DISTANCE OF 57.62 FEET TO A POINT ON THE EAST LINE OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1;

THENCE SOUTH 00°11'39" EAST ALONG SAID EAST LINE, A DISTANCE OF 659.88 FEET TO THE TRUE POINT OF BEGINNING. CONTAINING 39.497 ACRES.

CLARK, J. WICKHAM & DORIS L.  
& CLARK, J. WICKHAM  
7041 & 7031 INDIANA ST.  
GOLDEN, COLORADO 80403

FORBES, DONALD B.  
15000 W. 72nd AVE.  
GOLDEN, COLORADO  
80403

DIXON, KENNETH P.  
1882 S. SAND LILY DRIVE  
GOLDEN, COLORADO 80401

Block 1

W 68TH PLACE

Block 3

Block 2

PARCEL NO. 1  
20.497 ACRES

THE FARMERS RESERVOIR IRRIGATION CO.  
725 MALLEY DRIVE  
NORTHGLENN, CO

NOT A PART

GRAND CANAL

JOYCE STREET

GIRARD STREET

CLINTON STREET

250.58'

725.1'

1321.30'

N 09° 55' 34" W

210.0'

225.84'

300° 11' 35" E

313.56'

N 09° 17' 37" E

340'

340'

340'

340'

340'

340'

340'

340'

10' BUILDING LINE

10' UTILITY EASEMENT

10' BUILDING LINE

10' UTILITY EASEMENT

10' BUILDING LINE

10' UTILITY EASEMENT

10' BUILDING LINE

10' UTILITY EASEMENT

10' BUILDING LINE

10' UTILITY EASEMENT

10' BUILDING LINE

10' UTILITY EASEMENT

10' BUILDING LINE

10' UTILITY EASEMENT

100' FLOOD PLAIN

100' FLOOD PLAIN

100' FLOOD PLAIN

100' FLOOD PLAIN

100' FLOOD PLAIN

100' FLOOD PLAIN

100' FLOOD PLAIN

100' FLOOD PLAIN

VESTMENT CO.  
4096 YOUNGFIELD ST.  
WHEAT RIDGE, COLORADO 80033

KUNZ & BARBER  
DEVELOPERS  
4096 YOUNGFIELD ST.  
WHEAT RIDGE, COLORADO  
80033

CITY OF ARVADA  
8101 RALSTON RD.  
ARVADA, COLORADO 80002

TRUE POINT OF BEGINNING

Block 5

5' CONCRETE  
BICYCLE PATH

100' UTILITY, FLOODPLAIN, OPEN SPACE,  
AND PEDESTRIAN EASEMENT

OPEN SPACE TO THE  
CITY OF ARVADA

NEW BRIDGE

CITY OF  
ARVADA  
(SEE ABOVE)

MURRAY, EARL H.  
(SEE ABOVE)

AD.  
ROUT.  
6000

MURRAY  
1555  
GOL.

## **APPENDIX D**

### **JEFFERSON COUNTY QUARTER SECTION MAPS**

- 1) 1986 Aerial Photograph - Site vicinity map with street and waterway labels.
- 2) Jefferson County Quarter Section 30-01 map

30-014-  
00-004

5

017  
31  
CITY OF ARVADA  
83065600

FIGURE 2

JEFFERSON COUNTY  
VA SECTION 30-01

30-011-00-018

39

CROKE

CANAL

016

019

007

RESUB OF LOTS 586  
COTTONWOOD PARK  
IN RALSTON VALLEY

COTTONWOOD

PARK

RALSTON  
VALLEY

COTTONWOOD PARK  
IN RALSTON VALLEY  
REPLAT "A"

JEFFERSON COUNTY  
R-1 SCHOOL DISTRICT  
33  
B 2803-853

CITY OF ARVADA  
B 2707-90


2647.06' INDIANA STREET

Adjoining 39-06

E 1/4

S 00


FIGURE 1 1986 AERIAL PHOTOGRAPH  
SITE VICINITY MAP



## **APPENDIX E**

### **U.S.D.A. SOIL CONSERVATION SERVICE MAPS**

- 1) Soil Survey Map and Legend
- 2) General Soil Map



# SOIL LEGEND


## SYMBOL

## NAME

## SYMBOL

## NAME

|    |  |     |   |
|----|--|-----|---|
| 1  | Aida loam, 0 to 2 percent slopes   | 89  | Loveland Variant gravelly sandy loam, 0 to 2 percent slopes           |
| 2  | Aida-Niwot complex, 0 to 2 percent slopes                                  | 90  | Manzano fine sandy loam, 0 to 2 percent slopes                        |
| 3  | Allens Park Variant-Ratake-Rock outcrop complex, 30 to 50 percent slopes   | 91  | Manzanola clay loam, 0 to 5 percent slopes                            |
| 4  | Argus soils, loamy, 15 to 30 percent slopes                                | 92  | Manzanola clay loam, 5 to 9 percent slopes                            |
| 5  | Argus soils-Rock outcrop complex, 15 to 60 percent slopes                  | 93  | Manzanola clay loam, 9 to 15 percent slopes                           |
| 6  | Arvada clay loam, 0 to 2 percent slopes                                    | 94  | Manzanola clay loam, 15 to 25 percent slopes                          |
| 7  | Ascalon sandy loam, 5 to 9 percent slopes                                  | 95  | Manzanola cobbly clay loam, 15 to 25 percent slopes                   |
| 8  | Ascalon sandy loam, 9 to 15 percent slopes                                 | 96  | Manzanola-Renohill-Stoneham complex, 9 to 15 percent slopes           |
| 9  | Baller-Rock outcrop complex, 15 to 50 percent slopes                       | 97  | McClave clay loam, 0 to 3 percent slopes                              |
| 10 | Baller Variant-Lavine-Rock outcrop complex, 5 to 15 percent slopes         | 98  | Midway clay loam, 9 to 30 percent slopes                              |
| 11 | Baller Variant-Lavine-Rock outcrop complex, 15 to 30 percent slopes        | 99  | Midway stony clay loam, 15 to 40 percent slopes                       |
| 12 | Blakeford loamy sand, 0 to 9 percent slopes                                | 100 | Nederland very cobbly sandy loam, 15 to 50 percent slopes             |
| 13 | Blakeford loamy sand, 9 to 15 percent slopes                               | 101 | Nederland Variant very cobbly sandy loam, 30 to 50 percent slopes     |
| 14 | Breece sandy loam, 9 to 25 percent slopes                                  | 102 | Nunn clay loam, 0 to 2 percent slopes                                 |
| 15 | Breece sandy loam, 0 to 5 percent slopes                                   | 103 | Nunn clay loam, 2 to 5 percent slopes                                 |
| 16 | Breece gravelly sandy loam, 9 to 25 percent slopes                         | 104 | Nunn clay loam, 5 to 9 percent slopes                                 |
| 17 | Critchell gravelly sandy loam, 0 to 3 percent slopes                       | 105 | Nunn-Urban land complex, 0 to 2 percent slopes                        |
| 18 | Critchell gravelly sandy loam, 3 to 9 percent slopes                       | 106 | Nunn-Urban land complex, 2 to 5 percent slopes                        |
| 19 | Critchell gravelly sandy loam, 9 to 15 percent slopes                      | 107 | Nunn-Urban land complex, 5 to 9 percent slopes                        |
| 20 | Critchell stony sandy loam, 0 to 5 percent slopes                          | 108 | Nunn Variant-Urban land complex, 0 to 3 percent slopes                |
| 21 | Cryofluents, 0 to 5 percent slopes   | 109 | Paymaster sandy loam, 0 to 3 percent slopes                           |
| 22 | Cumulative Cryoborolia, loamy, 0 to 5 percent slopes                       | 110 | Pits, clayey  |
| 23 | Curecanti very stony sandy loam, 15 to 50 percent slopes                   | 111 | Pits, gravel  |
| 24 | Dacotah Variant gravelly clay loam, 0 to 3 percent slopes                  | 112 | Platner loam, 3 to 5 percent slopes                                   |
| 25 | Denver clay loam, 0 to 2 percent slopes                                    | 113 | Platner-Urban land complex, 0 to 3 percent slopes                     |
| 26 | Denver clay loam, 2 to 5 percent slopes                                    | 114 | Raleigh very gravelly sandy loam, 9 to 15 percent slopes              |
| 27 | Denver clay loam, 5 to 9 percent slopes                                    | 115 | Raleigh very gravelly sandy loam, 15 to 30 percent slopes             |
| 28 | Denver cobbly clay loam, 5 to 9 percent slopes                             | 116 | Raleigh very gravelly sandy loam, 30 to 50 percent slopes             |
| 29 | Denver-Kutch clay loams, 5 to 9 percent slopes                             | 117 | Raleigh very gravelly sandy loam, 2 to 9 percent south slopes         |
| 30 | Denver-Kutch clay loams, 9 to 15 percent slopes                            | 118 | Raleigh very gravelly sandy loam, 9 to 15 percent south slopes        |
| 31 | Denver-Kutch-Midway clay loams, 9 to 25 percent slopes                     | 119 | Raleigh very gravelly sandy loam, 15 to 30 percent south slopes       |
| 32 | Denver-Kutch-Urban land complex, 5 to 9 percent slopes                     | 120 | Raleigh stony sandy loam, 30 to 50 percent south slopes               |
| 33 | Denver-Kutch-Urban land complex, 9 to 15 percent slopes                    | 121 | Ratake-Rock outcrop complex, 50 to 70 percent slopes                  |
| 34 | Denver-Urban land complex, 0 to 2 percent slopes                           | 122 | Ratake-Cathedral very stony sandy loams, 25 to 60 percent slopes      |
| 35 | Denver-Urban land complex, 2 to 5 percent slopes                           | 123 | Ratake-Cathedral-Rock outcrop complex, 25 to 60 percent slopes        |
| 36 | Denver-Urban land complex, 5 to 9 percent slopes                           | 124 | Ratake-Cathedral-Rock outcrop complex, 25 to 60 percent north slopes  |
| 37 | Earcree gravelly sandy loam, 9 to 15 percent slopes                        | 125 | Ratake-Lininger stony sandy loams, 30 to 60 percent slopes            |
| 38 | Earcree Variant very gravelly sandy loam, 3 to 9 percent slopes            | 126 | Razor-Heldt clay loams, 9 to 25 percent slopes                        |
| 39 | Earcree Variant very gravelly sandy loam, 9 to 15 percent slopes           | 127 | Razor-Heldt-Midway cobbly clay loams, 15 to 30 percent slopes         |
| 40 | Earcree Variant-Variable complex, 0 to 15 percent slopes                   | 128 | Rednun clay loam, 0 to 3 percent slopes                               |
| 41 | Englewood clay loam, 0 to 2 percent slopes                                 | 129 | Rednun clay loam, 3 to 9 percent slopes                               |
| 42 | Englewood clay loam, 2 to 5 percent slopes                                 | 130 | Rednun clay loam, 9 to 15 percent slopes                              |
| 43 | Englewood clay loam, wet, 0 to 3 percent slopes                            | 131 | Rednun-Chapin Variant clay loams, 9 to 15 percent slopes              |
| 44 | Englewood-Urban land complex, 0 to 2 percent slopes                        | 132 | Renohill loam, 5 to 9 percent slopes                                  |
| 45 | Flatirons very cobbly sandy loam, 0 to 3 percent slopes                    | 133 | Renohill-Manzanola clay loams, 9 to 15 percent slopes                 |
| 46 | Flatirons very stony sandy loam, 0 to 5 percent slopes                     | 134 | Renohill-Midway complex, 9 to 15 percent slopes                       |
| 47 | Flatirons very stony sandy loam, 5 to 9 percent slopes                     | 135 | Resort-Schinx very gravelly sandy loams, 9 to 15 percent slopes       |
| 48 | Flatirons very stony sandy loam, 9 to 15 percent slopes                    | 136 | Resort-Schinx very gravelly sandy loams, 15 to 30 percent slopes      |
| 49 | Flatirons very stony sandy loam, 15 to 30 percent slopes                   | 137 | Resort-Schinx very gravelly sandy loams, 30 to 50 percent slopes      |
| 50 | Fluvialquents, sandy, 0 to 2 percent slopes                                | 138 | Rock outcrop, igneous and metamorphic                                 |
| 51 | Fondis loam, 0 to 3 percent slopes   | 139 | Rock outcrop, sedimentary   |
| 52 | Garber Variant very gravelly sandy loam, 5 to 9 percent slopes             | 140 | Rock outcrop-Cathedral-Ratake complex, 50 to 100 percent slopes       |
| 53 | Garber Variant very gravelly sandy loam, 9 to 15 percent slopes            | 141 | Rogert-Herberman-Rock outcrop complex, 30 to 70 percent slopes        |
| 54 | Grimstone stony sandy loam, 9 to 15 percent slopes                         | 142 | Rooney very cobbly sandy loam, 15 to 50 percent slopes                |
| 55 | Grimstone-Hiwan-Rock outcrop complex, 30 to 60 percent slopes              | 143 | Rooney-Primen-Layden complex, 15 to 50 percent slopes                 |
| 56 | Grimstone-Peeler-Rock outcrop complex, 15 to 30 percent slopes             | 144 | Rooney-Rock outcrop complex, 50 to 70 percent slopes                  |
| 57 | Grimstone-Peeler-Rock outcrop complex, 30 to 50 percent slopes             | 145 | Rosane sandy loam, 0 to 3 percent slopes                              |
| 58 | Hargreave sandy loam, 3 to 9 percent slopes                                | 146 | Rosane-Venable fine sandy loams, 0 to 3 percent slopes                |
| 59 | Hargreave-Bernal sandy loams, 9 to 15 percent slopes                       | 147 | Schinx-Resort-Rock outcrop complex, 50 to 70 percent slopes           |
| 60 | Haverson loam, 0 to 3 percent slopes                                       | 148 | Standley-Layden-Primen very stony clay loams, 15 to 30 percent slopes |
| 61 | Haverson loam, 3 to 9 percent slopes                                       | 149 | Standley-Nunn gravelly clay loams, 0 to 5 percent slopes              |
| 62 | Heldt clay, 3 to 9 percent slopes  | 150 | Tolvar very gravelly loamy sand, 15 to 30 percent slopes              |
| 63 | Heldt clay, 9 to 15 percent slopes   | 151 | Tomfluents, very gravelly, 0 to 3 percent slopes                      |
| 64 | Herbman-Sorucedale-Rock outcrop complex, 9 to 15 percent slopes            | 152 | Trag sandy loam, 3 to 9 percent slopes                                |
| 65 | Herbman-Sorucedale-Rock outcrop complex, 15 to 30 percent slopes           | 153 | Trag sandy loam, 9 to 25 percent slopes                               |
| 66 | Kittredge-Earcree complex, 3 to 9 percent slopes                           | 154 | Troutdale gravelly sandy loam, 3 to 9 percent slopes                  |
| 67 | Kittredge-Earcree complex, 9 to 20 percent slopes                          | 155 | Troutdale-Kittredge sandy loams, 5 to 15 percent slopes               |
| 68 | Kittredge-Venable complex, 0 to 15 percent slopes                          | 156 | Troutdale-Rogert-Kittredge complex, 15 to 30 percent slopes           |
| 69 | Laporte Variant complex, 15 to 60 percent slopes                           | 157 | Troutdale-Sorucedale gravelly sandy loams, 3 to 15 percent slopes     |
| 70 | Lavate sandy loam, 3 to 9 percent slopes                                   | 158 | Truckton sandy loam, 0 to 3 percent slopes                            |
| 71 | Lavate sandy loam, 9 to 15 percent slopes                                  | 159 | Truckton sandy loam, 3 to 9 percent slopes                            |
| 72 | Lavate-Bernal-Rock outcrop complex, 15 to 30 percent slopes                | 160 | Ulm clay loam, 5 to 9 percent slopes                                  |
| 73 | Lavine loam, very rocky, 0 to 5 percent slopes                             | 161 | Ulm-Urban land complex, 0 to 3 percent slopes                         |
| 74 | Leback clay loam, saline, 0 to 2 percent slopes                            | 162 | Ulm-Urban land complex, 3 to 5 percent slopes                         |
| 75 | Legault-Hiwan stony loamy sands, 5 to 15 percent slopes                    | 163 | Ulm-Urban land complex, 5 to 9 percent slopes                         |
| 76 | Legault-Hiwan stony loamy sands, 15 to 30 percent slopes                   | 164 | Ulm-Urban land complex, 9 to 18 percent slopes                        |
| 77 | Legault-Hiwan-Rock outcrop complex, 30 to 50 percent slopes                | 165 | Ustic Torriorthents, loamy, 15 to 50 percent slopes                   |
| 78 | Legault-Tolvar-Rock outcrop complex, 50 to 70 percent slopes               | 166 | Ustic Torriorthents, clayey, 0 to 50 percent slopes                   |
| 79 | Layden-Nunn-Rooney complex, 9 to 30 percent slopes                         | 167 | Ustorthents, cool-Rock outcrop complex, 15 to 50 percent slopes       |
| 80 | Layden-Primen-Standley cobbly clay loams, 15 to 50 percent slopes          | 168 | Vaimont clay loam, 0 to 3 percent slopes                              |
| 81 | Layden-Primen-Standley extremely stony clay loams, 30 to 70 percent slopes | 169 | Veldkamp-Nederland very cobbly sandy loams, 0 to 3 percent slopes     |
| 82 | Layden-Standley-Primen cobbly clay loams, 9 to 15 percent slopes           | 170 | Venable loam, 0 to 3 percent slopes                                   |
| 83 | Layden-Standley-Primen very cobbly clay loams, 30 to 60 percent slopes     | 171 | Venable loam, 3 to 9 percent slopes                                   |
| 84 | Lininger-Ratake complex, 5 to 15 percent slopes                            | 172 | Wann fine sandy loam, 0 to 2 percent slopes                           |
| 85 | Lininger-Ratake complex, 15 to 30 percent slopes                           | 173 | Willowman cobbly sandy loam, 0 to 5 percent slopes                    |
| 86 | Lininger-Trag sandy loams, 3 to 9 percent slopes                           | 174 | Willowman-Layden cobbly loams, 9 to 30 percent slopes                 |
| 87 | Lininger-Trag sandy loams, 9 to 20 percent slopes                          | 175 | Yoder Variant gravelly sandy loam, 9 to 30 percent slopes             |
| 88 | Loveland clay loam, 0 to 1 percent slopes                                  | 176 | Yoder Variant-Midway complex, 15 to 60 percent slopes                 |



# SOIL ASSOCIATIONS

1. **Humus Covered** - Nearly level to gently sloping, deep, well drained, clayey soils that formed in material derived from shale and slate.
2. **Loamier** - Moderately sloping to level, deep and moder-ately clayey soils that formed in material derived from mudstone and shale.
3. **Plumier** - Moderately sloping to level, deep and moder-ately clayey soils that formed in material derived from mudstone and shale.
4. **Clayey** - Moderately sloping to level, deep and moder-ately clayey soils that formed in material derived from mudstone and shale.
5. **Humus Covered** - Nearly level to gently sloping, deep, well drained, clayey soils that formed in material derived from shale and slate.
6. **Loamier** - Moderately sloping to level, deep and moder-ately clayey soils that formed in material derived from mudstone and shale.
7. **Plumier** - Moderately sloping to level, deep and moder-ately clayey soils that formed in material derived from mudstone and shale.
8. **Clayey** - Moderately sloping to level, deep and moder-ately clayey soils that formed in material derived from mudstone and shale.

11


12

13

14

11. **Humus Covered** - Nearly level to gently sloping, deep, well drained, clayey soils that formed in material derived from shale and slate.
12. **Loamier** - Moderately sloping to level, deep and moder-ately clayey soils that formed in material derived from mudstone and shale.
13. **Plumier** - Moderately sloping to level, deep and moder-ately clayey soils that formed in material derived from mudstone and shale.
14. **Clayey** - Moderately sloping to level, deep and moder-ately clayey soils that formed in material derived from mudstone and shale.

U. S. DEPARTMENT OF AGRICULTURE  
SOIL CONSERVATION SERVICE  
**GENERAL SOIL MAP**  
GOLDEN AREA COLORADO  
PARTS OF  
DENVER, DOUGLAS, JEFFERSON  
AND PARK COUNTIES.



Each area outlined on this map consists of more than one soil or soil type. The map is thus a generalization of the soil distribution in the area.

## **APPENDIX F**

### **LABORATORY RESULTS ATI (ANALYTICAL TECHNOLOGIES, INC.)**



Analytical Technologies, Inc.

225 Commerce Drive Fort Collins, Colorado 80524 (303) 490-1511

---

Message

Dave,

Here are your results.

Steve F.

To Dave Runyon Company ERCE  
Fax No. 843-6215 Date 1-14-92  
From Steve Fry Number of pages including this sheet 31

If you do not receive all the pages please call us back as soon as possible.



Analytical Technologies, Inc. 225 Commerce Drive Fort Collins, Colorado 80524 (303) 490-1511

January 14, 1992

Mr. Dave Runyon  
ERCE  
Stanford Place 3, Suite 415  
4582 South Ulster Street Parkway  
Denver, CO 80237

RE: ATI Workorder: 91-12-190  
Client Project Name: Cottonwood ESA

Dear Mr. Runyon:

Two soil samples and two water samples were received from ERCE on December 27, 1991. The samples were scheduled for the following analyses: Volatile Organics, PCB's, and Total Lead. Results for these analyses are contained in the following report.

Please note that the Volatile Organic surrogate recoveries for sample "001" were outside the method required limits. This sample was re-analyzed and the surrogates once again did not meet the required recovery limits. This is probably due to the matrix of the sample, i.e., the sample resembled activated carbon.

Thank you for your confidence in Analytical Technologies, Inc. Should you have any questions, please call.

Sincerely yours,

Steven Fry, Ph.D.  
Project Manager

SF/kcl

Enclosures



Analytical Technologies, Inc.

**QUALITY ASSURANCE  
DATA REVIEW**

The data contained in the following report has been reviewed and approved by the appropriate supervisory personnel listed below:

Alex Blanche, GC/GCMS Supervisor

**CERTIFICATION**


Analytical Technologies Inc. certifies that the analyses reported herein are true, complete and correct within the limits of the method employed.



Analytical Technologies, Inc.

**QUALITY ASSURANCE  
DATA REVIEW**

The data contained in the following report has been reviewed and approved by the appropriate supervisory personnel listed below:



Tom Austin, Jr.  
GC/HPLC/Fuels Supervisor

**CERTIFICATION**

Analytical Technologies, Inc. certifies that the analyses reported herein are true, complete and correct within the limits of the method employed.

## Method 8240

Client Sample ID:

Reagent Blank



Lab Name: Analytical Technologies Inc.

Lab Sample ID: 91-12-190-RB

Client Name: ERCE

Date Collected: N/A

Client Project ID: Cottonwood ESA

Date Analyzed: 01/09/92

Sample Matrix: Soil

Dilution Factor: 1

| COMPOUND NAME              | Concentration<br>ug/kg |     |              |
|----------------------------|------------------------|-----|--------------|
| Chloromethane              | <                      | 10  |              |
| Bromomethane               | <                      | 10  |              |
| Vinyl chloride             | <                      | 10  |              |
| Chloroethane               | <                      | 10  |              |
| Methylene chloride         | <                      | 5   |              |
| Acetone                    | <                      | 10  |              |
| Carbon disulfide           | <                      | 5   |              |
| 1,1-Dichloroethene         | <                      | 5   |              |
| 1,1-Dichloroethane         | <                      | 5   |              |
| 1,2-Dichloroethene (Total) | <                      | 5   |              |
| Chloroform                 | <                      | 5   |              |
| 1,2-Dichloroethane         | <                      | 5   |              |
| 2-Butanone                 | <                      | 10  |              |
| 1,1,1-Trichloroethane      | <                      | 5   |              |
| Carbon tetrachloride       | <                      | 5   |              |
| Vinyl Acetate              | <                      | 10  |              |
| Bromodichloromethane       | <                      | 5   |              |
| 1,2-Dichloropropane        | <                      | 5   |              |
| cis-1,3-Dichloropropene    | <                      | 5   |              |
| Trichloroethene            | <                      | 5   |              |
| Dibromochloromethane       | <                      | 5   |              |
| 1,1,2-Trichloroethane      | <                      | 5   |              |
| Benzene                    | <                      | 5   |              |
| trans-1,3-Dichloropropene  | <                      | 5   |              |
| Bromoform                  | <                      | 5   |              |
| 2-Hexanone                 | <                      | 10  |              |
| 4-Methyl-2-pentanone       | <                      | 10  |              |
| Tetrachloroethene          | <                      | 5   |              |
| 1,1,2,2-Tetrachloroethane  | <                      | 5   |              |
| Toluene                    | <                      | 5   |              |
| Chlorobenzene              | <                      | 5   |              |
| Ethylbenzene               | <                      | 5   |              |
| Styrene                    | <                      | 5   |              |
| Total Xylenes              | <                      | 5   |              |
| Surrogate Recoveries:      | %                      | Rec | % Rec Limits |
| 1,2-Dichloroethane-d4      |                        | 87  | 70-121       |
| Toluene-d8                 |                        | 104 | 81-117       |
| Bromofluorobenzene         |                        | 102 | 74-121       |

## Method 8240

Client Sample ID:

001



Lab Name: Analytical Technologies Inc.

Lab Sample ID: 91-12-190-01

Client Name: ERCE

Date Collected: 12/26/91

Client Project ID: Cottonwood ESA

Date Analyzed: 01/09/92

Sample Matrix: Soil

Dilution Factor: 1

| COMPOUND NAME              | Concentration (ug/kg) |       |              |
|----------------------------|-----------------------|-------|--------------|
| Chloromethane              | <                     | 10    |              |
| Bromomethane               | <                     | 10    |              |
| Vinyl chloride             | <                     | 10    |              |
| Chloroethane               | <                     | 10    |              |
| Methylene chloride         |                       | 120   |              |
| Acetone                    |                       | 68    |              |
| Carbon disulfide           | <                     | 5     |              |
| 1,1-Dichloroethene         |                       | 2     | J            |
| 1,1-Dichloroethane         | <                     | 5     |              |
| 1,2-Dichloroethene (Total) |                       | 4     | J            |
| Chloroform                 |                       | 3     | J            |
| 1,2-Dichloroethane         | <                     | 5     |              |
| 2-Butanone                 | <                     | 10    |              |
| 1,1,1-Trichloroethane      |                       | 12    |              |
| Carbon tetrachloride       | <                     | 5     |              |
| Vinyl Acetate              | <                     | 10    |              |
| Bromodichloromethane       | <                     | 5     |              |
| 1,2-Dichloropropane        | <                     | 5     |              |
| cis-1,3-Dichloropropene    | <                     | 5     |              |
| Trichloroethene            |                       | 4     | J            |
| Dibromochloromethane       | <                     | 5     |              |
| 1,1,2-Trichloroethane      | <                     | 5     |              |
| Benzene                    |                       | 4     | J            |
| trans-1,3-Dichloropropene  | <                     | 5     |              |
| Bromoform                  | <                     | 5     |              |
| 2-Hexanone                 | <                     | 10    |              |
| 4-Methyl-2-pentanone       | <                     | 10    |              |
| Tetrachloroethene          |                       | 23    |              |
| 1,1,2,2-Tetrachloroethane  | <                     | 5     |              |
| Toluene                    |                       | 24    |              |
| Chlorobenzene              |                       | 4     | J            |
| Ethylbenzene               |                       | 7     |              |
| Styrene                    | <                     | 5     |              |
| Total Xylenes              |                       | 43    |              |
| Surrogate Recoveries:      | %                     | Rec   | % Rec Limits |
| 1,2-Dichloroethane-d4      |                       | 93    | 70-121       |
| Toluene-d8                 |                       | 72 *  | 81-117       |
| Bromofluorobenzene         |                       | 122 * | 74-121       |

\* Outside control limits.

J = compound detected below practical quantitation limit.

## Tentatively Identified Compounds

Client Sample ID:



001

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Date Analyzed: 01/09/92

Client Project ID: Cottonwood ESA

Dilution Factor: 1

Lab Sample ID: 91-12-190-01

Matrix: Soil

Concentration units: ug/kg

| COMPOUND NAME          | RT | Concentration | Q |
|------------------------|----|---------------|---|
| Trichlorofluoromethane |    | 120 J         |   |

J = estimated value

## Method 8240

Client Sample ID:

Reagent Blank



Lab Name: Analytical Technologies Inc.

Client Name: ERCE

Client Project ID: Cottonwood ESA

Sample Matrix: Water

Lab Sample ID: 91-12-190-RB

Date Collected: N/A

Date Analyzed: 01/09/92

Dilution Factor: 1

| COMPOUND NAME              | Concentration<br>ug/L |              |  |
|----------------------------|-----------------------|--------------|--|
| Chloromethane              | < 10                  |              |  |
| Bromomethane               | < 10                  |              |  |
| Vinyl chloride             | < 10                  |              |  |
| Chloroethane               | < 10                  |              |  |
| Methylene chloride         | < 5                   |              |  |
| Acetone                    | < 10                  |              |  |
| Carbon disulfide           | < 5                   |              |  |
| 1,1-Dichloroethene         | < 5                   |              |  |
| 1,1-Dichloroethane         | < 5                   |              |  |
| 1,2-Dichloroethene (Total) | < 5                   |              |  |
| Chloroform                 | < 5                   |              |  |
| 1,2-Dichloroethane         | < 5                   |              |  |
| 2-Butanone                 | < 10                  |              |  |
| 1,1,1-Trichloroethane      | < 5                   |              |  |
| Carbon tetrachloride       | < 5                   |              |  |
| Vinyl Acetate              | < 10                  |              |  |
| Bromodichloromethane       | < 5                   |              |  |
| 1,2-Dichloropropane        | < 5                   |              |  |
| cis-1,3-Dichloropropene    | < 5                   |              |  |
| Trichloroethene            | < 5                   |              |  |
| Dibromochloromethane       | < 5                   |              |  |
| 1,1,2-Trichloroethane      | < 5                   |              |  |
| Benzene                    | < 5                   |              |  |
| trans-1,3-Dichloropropene  | < 5                   |              |  |
| Bromoform                  | < 5                   |              |  |
| 2-Hexanone                 | < 10                  |              |  |
| 4-Methyl-2-pentanone       | < 10                  |              |  |
| Tetrachloroethene          | < 5                   |              |  |
| 1,1,2,2-Tetrachloroethane  | < 5                   |              |  |
| Toluene                    | < 5                   |              |  |
| Chlorobenzene              | < 5                   |              |  |
| Ethylbenzene               | < 5                   |              |  |
| Styrene                    | < 5                   |              |  |
| Total Xylenes              | < 5                   |              |  |
| Surrogate Recoveries:      | % Rec                 | % Rec Limits |  |
| 1,2-Dichloroethane-d4      | 87                    | 76-116       |  |
| Toluene-d8                 | 104                   | 88-110       |  |
| Bromofluorobenzene         | 102                   | 86-115       |  |

## Method 8240

Client Sample ID:

004



Lab Name: Analytical Technologies Inc.

Lab Sample ID: 91-12-190-03

Client Name: ERCE

Date Collected: 12/26/91

Client Project ID: Cottonwood ESA

Date Analyzed: 01/09/92

Sample Matrix: Water

Dilution Factor: 1

| COMPOUND NAME              | Concentration (ug/L) |     |              |
|----------------------------|----------------------|-----|--------------|
| Chloromethane              | <                    | 10  |              |
| Bromomethane               | <                    | 10  |              |
| Vinyl chloride             | <                    | 10  |              |
| Chloroethane               | <                    | 10  |              |
| Methylene chloride         | <                    | 5   |              |
| Acetone                    | <                    | 10  |              |
| Carbon disulfide           | <                    | 5   |              |
| 1,1-Dichloroethene         | <                    | 5   |              |
| 1,1-Dichloroethane         | <                    | 5   |              |
| 1,2-Dichloroethene (Total) | <                    | 5   |              |
| Chloroform                 | <                    | 5   |              |
| 1,2-Dichloroethane         | <                    | 5   |              |
| 2-Butanone                 | <                    | 10  |              |
| 1,1,1-Trichloroethane      | <                    | 5   |              |
| Carbon tetrachloride       | <                    | 5   |              |
| Vinyl Acetate              | <                    | 10  |              |
| Bromodichloromethane       | <                    | 5   |              |
| 1,2-Dichloropropane        | <                    | 5   |              |
| cis-1,3-Dichloropropene    | <                    | 5   |              |
| Trichloroethene            | <                    | 5   |              |
| Dibromochloromethane       | <                    | 5   |              |
| 1,1,2-Trichloroethane      | <                    | 5   |              |
| Benzene                    | <                    | 5   |              |
| trans-1,3-Dichloropropene  | <                    | 5   |              |
| Bromoform                  | <                    | 5   |              |
| 2-Hexanone                 | <                    | 10  |              |
| 4-Methyl-2-pentanone       | <                    | 10  |              |
| Tetrachloroethene          | <                    | 5   |              |
| 1,1,2,2-Tetrachloroethane  | <                    | 5   |              |
| Toluene                    | <                    | 5   |              |
| Chlorobenzene              | <                    | 5   |              |
| Ethylbenzene               | <                    | 5   |              |
| Styrene                    | <                    | 5   |              |
| Total Xylenes              | <                    | 5   |              |
| Surrogate Recoveries:      | %                    | Rec | % Rec Limits |
| 1,2-Dichloroethane-d4      |                      | 87  | 76-116       |
| Toluene-d8                 |                      | 102 | 88-110       |
| Bromofluorobenzene         |                      | 101 | 86-115       |

Client Sample ID

004

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Date Analyzed: 01/09/92

Client Project ID: Cottonwood ESA

Dilution Factor: 1 1

Lab Sample ID: 91-12-190-03

Matrix: Water

Concentration units: ug/L

| COMPOUND NAME        | RT | Concentration | Q |
|----------------------|----|---------------|---|
| Methyl-t-butyl ether |    | 10 J          |   |

J = estimated value

# **VOLATILE MATRIX SPIKE/MATRIX SPIKE DUPLICATE RECOVERY** **Method 8240**



Lab Name: Analytical Technologies, Inc.

Client Sample ID:

**In House**

Client Name: ERCE

Lab Sample ID: 20199905/AZ

Sample Matrix: Water

Date Analyzed: 01/09/92

| Compound           | Spike Added (ug/L) | Sample Concentration (ug/L) | MS Concentration (ug/L) | MS % REC |
|--------------------|--------------------|-----------------------------|-------------------------|----------|
| 1,1-Dichloroethene | 50                 | < 5                         | 57                      | 114      |
| Trichloroethene    | 50                 | < 5                         | 43                      | 86       |
| Benzene            | 50                 | < 5                         | 39                      | 78       |
| Toluene            | 50                 | < 5                         | 51                      | 102      |
| Chlorobenzene      | 50                 | < 5                         | 50                      | 100      |

| Compound           | Spike Added (ug/L) | MSD Concentration (ug/L) | MSD % REC | % RPD |
|--------------------|--------------------|--------------------------|-----------|-------|
| 1,1-Dichloroethene | 50                 | 58                       | 116       | 2     |
| Trichloroethene    | 50                 | 44                       | 88        | 2     |
| Benzene            | 50                 | 41                       | 82        | 5     |
| Toluene            | 50                 | 49                       | 98        | 4     |
| Chlorobenzene      | 50                 | 51                       | 102       | 2     |

## **QUALITY CONTROL LIMITS**

| Compound           | Water    |     | Soil     |     |
|--------------------|----------|-----|----------|-----|
|                    | %REC     | RPD | % Rec    | RPD |
| 1,1-Dichloroethene | 61 - 145 | 14  | 59 - 172 | 22  |
| Trichloroethene    | 71 - 120 | 14  | 62 - 137 | 24  |
| Benzene            | 76 - 127 | 11  | 60 - 133 | 21  |
| Toluene            | 76 - 125 | 13  | 59 - 139 | 21  |
| Chlorobenzene      | 75 - 130 | 13  | 66 - 142 | 21  |

**PCB ANALYSIS DATA SHEET**  
Method 8080

Lab Name: Analytical Technologies Inc.

Client Name: ERCE

Client Project ID: Cottonwood ESA

Lab Sample ID: 91-12-190-RBS

Sample Matrix: Sodium Sulfate

Sample Weight: 30 g

GPC Cleanup: N

Client Sample ID:

Reagent Blank

Date Collected: N/A

Date Extracted: 12/30/91

Date Analyzed: 01/03/92

Extract Volume: 10 mL

Dilution Factor: 1

| Compound | Conc (mg/kg) |
|----------|--------------|
| PCB 1016 | < 0.03       |
| PCB 1221 | < 0.03       |
| PCB 1232 | < 0.03       |
| PCB 1242 | < 0.03       |
| PCB 1248 | < 0.03       |
| PCB 1254 | < 0.03       |
| PCB 1260 | < 0.03       |

**SURROGATE RECOVERY**

| Compound             | % Recovery |
|----------------------|------------|
| Tetrachloro-m-xylene | 86         |

**PCB ANALYSIS DATA SHEET**  
Method 8080

Lab Name: Analytical Technologies Inc.

Client Name: ERCE

Client Project ID: Cottonwood ESA

Lab Sample ID: 91-12-190-02A

Sample Matrix: Soil

Sample Weight: 30 g

GPC Cleanup: N

Client Sample ID:

002

Date Collected: 12/26/91

Date Extracted: 12/30/91

Date Analyzed: 01/03/92

Extract Volume: 10 mL

Dilution Factor: 1

| Compound | Conc (mg/kg) |
|----------|--------------|
| PCB 1016 | < 0.03       |
| PCB 1221 | < 0.03       |
| PCB 1232 | < 0.03       |
| PCB 1242 | < 0.03       |
| PCB 1248 | < 0.03       |
| PCB 1254 | < 0.03       |
| PCB 1260 | < 0.03       |

**SURROGATE RECOVERY**

| Compound             | % Recovery |
|----------------------|------------|
| Tetrachloro-m-xylene | 98         |

**PCB MATRIX SPIKE RESULTS**  
**Method 8080****Lab Name:** Analytical Technologies, Inc.**Client Sample ID:****Client Name:** ERCE**In House****Lab Sample ID:** 91-12-114-01A**Date Analyzed:** 12/19/91**Sample Matrix:** Soil**GC Column:** DB-1701

| Compound | Spike Added (mg/kg) | Sample Concentration (mg/kg) | MS Concentration (mg/kg) | MS Percent Recovery |
|----------|---------------------|------------------------------|--------------------------|---------------------|
| PCB 1260 | 0.50                | < 0.3                        | 0.597                    | 119                 |

| Compound | Spike Added (mg/kg) | MSD Concentration (mg/kg) | MSD Percent Recovery | RPD |
|----------|---------------------|---------------------------|----------------------|-----|
| PCB 1260 | 0.50                | 0.607                     | 121                  | 2   |



**PCB ON-GOING PRECISION AND RECOVERY**  
**Method 8080**

**Lab Name:** Analytical Technologies, Inc.

**Lab Sample ID:** 91-12-190-OPR

**Client Name:** ERCE

**Date Analyzed:** 01/03/92

**Sample Matrix:** Soil

**GC Column:** DB-608

| Compound | Spike Added (mg/kg) | OPR Concentration (mg/kg) | OPR Percent Recovery |
|----------|---------------------|---------------------------|----------------------|
| PCB 1260 | 0.50                | 0.590                     | 118                  |

| Compound | Spike Added (mg/kg) | OPRD Concentration (mg/kg) | OPRD Percent Recovery | RPD |
|----------|---------------------|----------------------------|-----------------------|-----|
| PCB 1260 | 0.50                | 0.657                      | 131                   | 11  |



Analytical Technologies, Inc.

**QUALITY ASSURANCE  
DATA REVIEW**

The data contained in the following report has been reviewed and approved by the appropriate supervisory personnel listed below:

Steve Workman, GC/HPLC/Inorganics Supervisor

**CERTIFICATION**

Analytical Technologies Inc. certifies that the analyses reported herein are true, complete and correct within the limits of the method employed.

**TOTAL LEAD ANALYSIS DATA SHEET****Laboratory Name:** Analytical Technologies, Inc.**Date Collected:** 12/26/91**Client Name:** ERCE**Prep Date:** 01/02/92**Client Project ID:** Cottonwood ESA**Date Analyzed:** 01/03/92**Workorder Number:** 91-12-190**Sample Matrix:** Soil

| Client ID.    | ATI ID.      | Lead Conc.<br>(mg/kg) |
|---------------|--------------|-----------------------|
| Reagent Blank | 91-12-190-RB | < 5                   |
| 002           | 91-12-190-02 | 56                    |

**TOTAL LEAD ANALYSIS DATA SHEET****Laboratory Name:** Analytical Technologies, Inc.**Date Collected:** 12/26/91**Client Name:** ERCE**Prep Date:** 01/02/92**Client Project ID:** Cottonwood ESA**Date Analyzed:** 01/02/92**Workorder Number:** 91-12-190**Sample Matrix:** Water

| Client ID.    | ATI ID.      | Lead Conc.<br>(mg/L) |
|---------------|--------------|----------------------|
| Reagent Blank | 91-12-190-RB | < 3.003              |
| 005           | 91-12-190-04 | 0.065                |

**TOTAL LEAD MATRIX SPIKE**

Client Sample ID:

In House

Laboratory Name: Analytical Technologies, Inc.

Client Name: ERCE

Prep Date: 01/02/92

Lab Sample ID: 9659A/FL

Date Analyzed: 01/03/92

Sample Matrix: Soil

| Compound | Spike Added<br>(mg/kg) | Sample Concentration<br>(mg/kg) | MS Concentration<br>(mg/kg) | MS Percent Recovery |
|----------|------------------------|---------------------------------|-----------------------------|---------------------|
| Lead     | 50                     | < 5                             | 54                          | 108                 |

**TOTAL LEAD MATRIX SPIKE****Client Sample ID:****In House****Laboratory Name: Analytical Technologies, Inc.****Client Name: ERCE****Prep Date: 01/02/92****Lab Sample ID: 9600B-1/FL****Date Analyzed: 01/02/92****Sample Matrix: Water**

| Compound | Spike Added (mg/L) | Sample Concentration (mg/L) | MS Concentration (mg/L) | MS Percent Recovery |
|----------|--------------------|-----------------------------|-------------------------|---------------------|
| Lead     | 0.80               | < 0.003                     | 0.80                    | 100                 |

CON...ACTOR ERCE SAMPLERS Ron C. Holme, Will Glasgow PROJECT - COTTONWOOD ESA  
 SITE CONTACT/PHONE DAVE RUNYON 843-6210 LAB/LOCATION ATI - FORT COLLINS

C-O-C NUMBER

0001

E&amp;S ROCKY MOUNTAIN, CHAIN OF CUSTODY

ERCE (DENVER)  
 DENVER TECH CENTER  
 STANFORD PLACE #3 STE 415 DENVER CO

01  
 02  
 \*  
 03  
 04

| DATE/TIME     | SAMPLE NUMBER | LOCATION  | CONTAINER TYPE | NUMBER OF CONTAINERS | MEDIA SOIL(S) WATER (W) | FILTERED-F POT DISS-P | TURN AROUND RUSH -R | OUT OF SPEC REPORTS | COOLED TO 4 C | HCl | NaOH | HNO3 | H2SO4 | VOA | OIL-GLASS | PER + METALS | TOTAL METALS |
|---------------|---------------|-----------|----------------|----------------------|-------------------------|-----------------------|---------------------|---------------------|---------------|-----|------|------|-------|-----|-----------|--------------|--------------|
| 12/26/91 1330 | 001           | LANDFILL  | 20Z GLASS      | 1                    | S                       |                       |                     |                     | Y             |     |      |      |       | X   |           |              |              |
| 1335          | 002           | LANDFILL  | 20Z GLASS      | 2                    | S                       |                       |                     |                     | Y             |     |      |      |       |     | X         |              |              |
| 1420          | 003           | 2nd Creek | 20Z GLASS      | 1                    | W                       |                       |                     |                     | Y             |     |      |      |       |     | X         |              |              |
| 1500          | 004           | HAE #6    | 40m Aches      | 2                    | W                       |                       |                     |                     | Y             |     |      |      | X     |     |           | X            |              |
| 1505          | 005           | HAE #6    | 15m Aches      | 1                    | W                       |                       |                     |                     | Y             |     |      | X    |       |     |           | X            |              |

| RELINQUISHED BY | DATE/TIME     | RECEIVED BY  | DATE/TIME       | LABORATORY USE ONLY                      | Y | N |
|-----------------|---------------|--------------|-----------------|--|---|---|
| Ron C. Holme    | 12/27/91 0919 | Debi Burdick | 12/27/91 9:15am | PCKG RECD/CUSTODY SEALS INTACT           | ✓ |   |
|                 |               |              |                 | SAMPLE LABELS/COCs AGREE                 | ✓ |   |
|                 |               |              |                 | TEMPERATURE WITHIN SPECIFICATION _____ C |   |   |
|                 |               |              |                 | CORRECTED COPY ATTACHED                  |   |   |
| REMARKS         |               |              |                 | PROBLEMS OR DISCREPANCIES                |   |   |


SHIPMENT METHOD

personal delivery by Ron.

\* HOLD SAMPLE - DO NOT RUN. NOT ENOUGH SAMPLE. RON WILL GET BACK TO US  
 OF ANOTHER SAMPLING (TOTAL METALS FOR SOIL & WATER SAMPLES) 12/27/91 & ?

## **APPENDIX A**

### **1970 AERIAL PHOTOGRAPH - SITE VICINITY MAP, PRECOMMERCIAL DEVELOPMENT**



**APPENDIX A**

**1970 Aerial Photograph  
Site Vicinity Map  
Precommercial Development**



**DEPARTMENT OF PLANNING**

**COUNTY OF JEFFERSON  
STATE OF COLORADO**

**1829 01**

**APPR. SCALE 1"=200'**

**DATE 6-70**

## **APPENDIX B**

### **1986 AERIAL PHOTOGRAPH**

- 1) Survey Traverse Grid for Magnetic Survey and Radiological Survey
- 2) Drive tube well locations
- 3) ► = water sample taken from Ralston Creek
- 4) Site specific landfill boundary-highlighted in yellow

# APPENDIX B

1986 Aerial Photograph

- 1) Survey Traverse Grid For Magnetic Survey & Radiological Survey
- 2) Drive tube well locations
- 3) ▶ = water sample taken from Ralston Creek
- 4) Site specific landfill boundary

## PHOTO MAP

S. T. R.



DATE

# ORADO

C Repro Inc.



462 - F Laredo  
Aurora Colorado

80011

(303) 360-9001

## **APPENDIX C**

### **LEGAL DESCRIPTION AND ACCOMPANYING MAP**

Recorded at \_\_\_\_\_ o'clock \_\_\_\_\_ M.

Reception No. \_\_\_\_\_

RECORDED IN  
COUNTY OF JEFFERSON  
STATE OF COLORADO  
RECEPTION NO. 88040360  
04/28/88 10:20 9.00

THIS DEED, Made this 18th day of March  
19 88, between

COTTONWOOD WEST INDUSTRIAL PARK INC.  
a Colorado Corporation  
of the City and County of DENVER and State of Colo-  
rado, of the first part, and  
COTTONWOOD WEST LTD.  
a Colorado limited partnership, \*\*\*\*  
of the  
County of DENVER and State of Colorado, of the second  
part;

WITNESSETH, That the said party of the first part, for and in consideration of the sum  
of TEN DOLLARS AND OTHER GOOD AND VALUABLE CONSIDERATION Dollars,  
to the said party of the first part, in hand paid by the said party of the second part, the  
receipt whereof is hereby confessed and acknowledged, has granted, bargained, sold and conveyed,  
and by these presents does grant, bargain, sell, convey and confirm unto the said party of  
the second part, its heirs and assigns forever, all the following described lot or parcel  
of land, situate, lying and being in the County of JEFFERSON and State of  
Colorado, to wit:

SEE EXHIBIT A ATTACHED HERETO FOR LEGAL DESCRIPTION  
SEE EXHIBIT B ATTACHED HERETO FOR ADDITIONAL PROVISIONS

\*\*\*\* c/o Gibraltar Companies  
Denver Corporate Center Tower III  
7900 E. Union Avenue Suite 850  
Denver, Co. 80237

also known as street and number vacant land

Together with all and singular the hereditaments and appurtenances thereunto belonging, or in any-  
wise appertaining, and the reversion and reversions, remainder and remainders, rents, issues and  
profits thereof; and all the estate, right, title, interest, claim and demand whatsoever, of the said  
part of the first part, either in law or equity, of, in and to the above bargained premises, with  
the hereditaments and appurtenances; TO HAVE AND TO HOLD the said premises above bar-  
gained and described, with the appurtenances, unto

the said party of the second part, its  
heirs and assigns forever.

And the said

part y of the first part, for it sel its heirs, executors and  
administrators, do es covenant, grant, bargain and agree to and with the said part y of the  
second part, its heirs and assigns, the above bargained premises in the quiet and peaceable  
possession of said part y of the second part, its heirs and assigns, against all and every  
person or persons lawfully claiming or to claim the whole or any part thereof, by, through or under  
the said part y of the first part to WARRANT AND FOREVER DEFEND.

IN WITNESS WHEREOF, The said part y of the first part has hereunto set its  
hand and seal the day and year first above written.

Signed, Sealed and Delivered in the presence of

.....[SEAL]  
COTTONWOOD WEST INDUSTRIAL  
PARK INC. ....[SEAL]  
.....[SEAL]  
James Moilanen, Pres.

STATE OF COLORADO.


County of

The foregoing instrument was acknowledged before me this 18th day of March  
1988 by James Moilanen, President of Cottonwood West Industrial  
Park Inc., a Colorado corporation

My Commission expires 2/11/90

19

Witness my hand and official seal.



Notary Public  
M. L. Smith - Denver 80202

EXHIBIT A  
TO SPECIAL WARRANTY DEED  
DATED MARCH 18, 1988

2  
2

Lot 7  
Cottonwood Park in Ralston Valley

and

A portion of the East 1/2 of Section 1, Township 3 South, Range 70 West of the 6th P.M., more particularly described as follows: Beginning at the Northeast corner of the Northwest 1/4 of the Southeast 1/4 of said Section 1; thence South 00 degrees 03 minutes 01 seconds East along the Easterly line of said Northwest 1/4 of the Southeast 1/4, 463.77 feet to the Northerly right-of-way line of the Croke Canal; thence Northwesterly along said Northerly right-of-way line the following 8 courses: (1) thence North 82 degrees 50 minutes 54 seconds West, 150.11 feet to a point of curve; (2) thence along a curve to the right having a radius of 963.78 feet, a central angle of 11 degrees 23 minutes 39 seconds, 191.66 feet to a point of tangent; (3) thence North 71 degrees 27 minutes 15 seconds West along said tangent, 276.15 feet to a point of curve; (4) thence along a curve to the right having a radius of 208.06 feet, a central angle of 37 degrees 31 minutes 18 seconds, 136.26 feet to a point of tangent; (5) thence North 33 degrees 55 minutes 57 seconds West along said tangent, 557.70 feet to a point of curve; (6) thence along a curve to the right having a radius of 388.56 feet, a central angle of 39 degrees 23 minutes 06 seconds, 267.10 feet to a point of tangent; (7) thence North 05 degrees 27 minutes 09 seconds East along said tangent, 755.43 feet to a point of curve; (8) thence along a curve to the right having a radius of 565.00 feet, a central angle of 09 degrees 47 minutes 25 seconds, 96.54 feet to the Northerly line of the Southwest 1/4 of the Northeast 1/4 of said Section 1; thence South 89 degrees 27 minutes 29 seconds East along said Northerly line, 991.49 feet to the Northeast corner of said Southwest 1/4 of the Northeast 1/4; thence South 00 degrees 03 minutes 48 seconds West along the Easterly line of said Southwest 1/4 of the Northeast 1/4, 1320.46 feet to the point of beginning.

Also known as All of Blocks 1, 2, 3, and 4  
Cottonwood West Industrial Park Filing No. 1,  
All situate in the County of Jefferson,  
State of Colorado

RECEPTION NO. 88040360

EXHIBIT B  
TO SPECIAL WARRANTY DEED  
DATED MARCH 18, 1988

3  
3

By accepting this conveyance, second party hereby assumes and agrees to pay that certain obligation evidenced by that certain Promissory Note dated January 10, 1985 in the principal amount of \$2,425,000.00 payable to Otero Savings and Loan Association, secured by that certain Deed of Trust recorded January 11, 1985 under Reception No. 85003626, Jefferson County, Colorado public records, as said Note and Deed of Trust have been subsequently modified. Second party's assumption and agreement to pay the foregoing obligation includes its assumption and ratification of the acts of certain third parties as evidenced by instruments recorded at Reception Numbers 85003627, 86006149, 86088951 and 86088952, even if those parties had no authority to complete or perform those acts.

RECEPTION NO. 88040360

HOW ALL MEN BY THESE PRESENTS: THAT THE UNDERSIGNED, BEING THE OWNERS OF A PARCEL OF LAND IN THE EAST 1/2 OF SECTION 1, TOWNSHIP 3 SOUTH, RANGE 70 WEST OF THE 6TH P.M., CITY OF ARVADA, COUNTY OF JEFFERSON, STATE OF COLORADO, MORE PARTICULARLY DESCRIBED AS FOLLOWS:

COMMENCING AT THE NORTHEAST CORNER OF SAID SECTION 1; THENCE SOUTH 00°02'54" EAST, ALONG THE EAST LINE OF THE NORTHEAST 1/4 OF SAID SECTION 1, A DISTANCE OF 1323.58 FEET TO THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1; THENCE NORTH 89°39'54" WEST, ALONG THE NORTH LINE OF SAID SOUTHEAST 1/4 OF THE NORTHEAST 1/4 A DISTANCE OF 1322.17 FEET TO THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1, THE TRUE POINT OF BEGINNING; THENCE SOUTH 00°11'39" EAST, ALONG THE EAST LINE OF SAID SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND ALONG THE WEST LINE OF LOT 1, RESUBDIVISION OF LOTS 5 AND 6, COTTONWOOD PARK IN RALSTON VALLEY, A SUBDIVISION RECORDED IN THE OFFICE OF THE JEFFERSON COUNTY CLERK AND RECORDER UNDER RECEPTION NUMBER 79058658, A DISTANCE OF 313.56 FEET; THENCE NORTH 89°47'39" EAST, ALONG THE SOUTH LINE OF SAID LOT 1, A DISTANCE OF 250.22 FEET TO A POINT ON THE WEST RIGHT-OF-WAY LINE OF JOYCE STREET; THENCE ALONG THE WEST RIGHT-OF-WAY LINE OF JOYCE STREET THE FOLLOWING THREE (3) COURSES:  
(1) SOUTH 29°55'40" WEST, A DISTANCE OF 68.23 FEET TO A POINT OF CURVE;  
(2) ALONG THE ARC OF A CURVE TO THE LEFT WITH A RADIUS OF 125.13 FEET AND A CENTRAL ANGLE OF 29°26'36" A DISTANCE OF 64.30 FEET, THE LONG CHORD OF WHICH BEARS SOUTH 15°12'22" WEST, A DISTANCE OF 63.60, TO A POINT OF TANGENCY;  
(3) SOUTH 00°29'04" WEST, A DISTANCE OF 201.41 FEET;  
THENCE ALONG THE NORTH LINE OF LOT 18, COTTONWOOD PARK IN RALSTON VALLEY, A SUBDIVISION RECORDED IN THE OFFICE OF THE JEFFERSON COUNTY CLERK AND RECORDER IN BOOK 55 AT PAGE 11 THE FOLLOWING TWO (2) COURSES:  
(1) SOUTH 71°50'32" WEST, A DISTANCE OF 150.35 FEET;  
(2) NORTH 68°52'48" WEST, A DISTANCE OF 57.62 FEET TO A POINT ON THE EAST LINE OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1;  
THENCE SOUTH 00°11'39" EAST, ALONG THE EAST LINE OF SAID SOUTHWEST 1/4 OF THE NORTHEAST 1/4, AND ALONG THE WEST LINE OF SAID LOT 18, A DISTANCE OF 104.00 FEET; THENCE SOUTH 53°57'00" WEST, A DISTANCE OF 542.86 FEET; THENCE NORTH 80°49'37" WEST A DISTANCE OF 464.19 FEET; THENCE SOUTH 84°04'28" WEST, A DISTANCE OF 154.44 FEET TO A POINT ON THE EASTERLY RIGHT-OF-WAY LINE OF THE CROAK CANAL; THENCE ALONG THE EASTERLY RIGHT-OF-WAY LINE OF SAID CROAK CANAL THE FOLLOWING THREE (3) COURSES:  
(1) ALONG THE ARC OF A NON-TANGENT CURVE TO THE RIGHT WITH A RADIUS OF 388.56 FEET AND A CENTRAL ANGLE OF 27°49'12" A DISTANCE OF 188.67 FEET, THE LONG CHORD OF WHICH BEARS NORTH 08°39'33" WEST, A DISTANCE OF 186.82 FEET TO A POINT OF TANGENCY;  
(2) NORTH 05°15'03" EAST, A DISTANCE OF 755.43 FEET TO A POINT OF CURVE;  
(3) ALONG THE ARC OF A CURVE TO THE RIGHT WITH A RADIUS OF 565.00 FEET AND A CENTRAL ANGLE OF 09°47'20" A DISTANCE OF 96.53 FEET, THE LONG CHORD OF WHICH BEARS NORTH 10°08'43" EAST, A DISTANCE OF 96.41 FEET TO A POINT ON THE NORTH LINE OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION;  
THENCE SOUTH 89°39'54" EAST, ALONG THE NORTH LINE OF SAID SOUTHWEST 1/4 OF THE NORTHEAST 1/4, A DISTANCE OF 990.20 FEET TO THE TRUE POINT OF BEGINNING. CONTAINING 25.486 ACRES.

HAVE LAID OUT, PLATTED, AND SUBDIVIDED THE ABOVE DESCRIBED LAND, UNDER THE NAME AND STYLE OF COTTONWOOD WEST INDUSTRIAL PARK FILING NO. 1, AND BY THESE PRESENTS DO DEDICATE TO THE CITY OF ARVADA IN FEE SIMPLE THE STREETS AND PUBLIC WAYS AS SHOWN ON THE PLATS, AND GRANTS TO THE PUBLIC UTILITIES, AND THE CITY OF ARVADA, THE RIGHT TO INSTALL, MAINTAIN, AND OPERATE MAINS, TRANSMISSION LINES, SERVICE LINES, AND APPURTENANCES, AS MAY BE NECESSARY TO PROVIDE SUCH UTILITY, CABLE TELEVISION, AND SANITARY SERVICES WITHIN THIS SUBDIVISION OR PROPERTY CONTIGUOUS THERETO, THROUGH, OVER, UNDER, AND ACROSS STREETS, UTILITY AND OTHER EASEMENTS, AND FOR PUBLIC PLACES AS SHOWN ON THE PLAT.

COTTONWOOD WEST INDUSTRIAL PARK, INC., A COLORADO CORPORATION.

BY: Dennis M. In  
PRESIDENT

ATTEST: D. Robert Clary  
Assistant Secretary  
SEAL

STATE OF COLORADO }  
COUNTY OF } SS

THE FOREGOING INSTRUMENT WAS ACKNOWLEDGED BEFORE ME THIS 21<sup>st</sup> DAY OF October, A.D., 1995, BY THE ABOVE PARTIES.

WITNESS MY HAND AND SEAL.  
MY COMMISSION EXPIRES 7-26-89

NAME Julia A. Mayes  
ADDRESS 828 So. Osmond  
Denver, CO 80224

HOLDER OF DEED OF TRUST

EARL N. MURRAY

RUTH M. MURRAY



## LEGAL DESCRIPTION

A PORTION OF THE EAST HALF OF SECTION 1, TOWNSHIP 3 SOUTH, RANGE 70 WEST OF THE SIXTH PRINCIPAL MERIDIAN, COUNTY OF JEFFERSON, STATE OF COLORADO, WHICH CONSIDERING THE EAST LINE OF THE SOUTHEAST 1/4 OF SAID SECTION 1 AS BEARING NORTH 00°02'49" WEST AND WITH ALL BEARINGS CONTAINED HEREIN RELATIVE THERETO IS MORE PARTICULARLY DESCRIBED AS FOLLOWS:

COMMENCING AT THE NORTHEAST CORNER OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 1; THENCE NORTH 89°32'02" WEST, ALONG THE NORTH LINE OF SAID NORTHEAST 1/4 OF THE SOUTHEAST 1/4, A DISTANCE OF 1318.84 FEET TO THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SAID SECTION 1, THE TRUE POINT OF BEGINNING; THENCE SOUTH 00°15'07" EAST, ALONG THE EAST LINE OF SAID NORTHWEST 1/4 OF THE SOUTHEAST 1/4, A DISTANCE OF 463.77 FEET TO A POINT ON THE NORTHERLY RIGHT-OF-WAY LINE OF THE CROKE CANAL; THENCE NORTHWESTERLY ALONG SAID NORTHERLY RIGHT-OF-WAY LINE THE FOLLOWING EIGHT (8) COURSES:

- (1) NORTH 83°03'00" WEST, A DISTANCE OF 150.11 FEET TO A POINT OF CURVE;
- (2) ALONG THE ARC OF A CURVE TO THE RIGHT WITH A RADIUS OF 963.78 FEET AND A CENTRAL ANGLE OF 11°23'39" A DISTANCE OF 191.65 FEET; THE LONG CHORD OF WHICH BEARS NORTH 77°21'10" WEST, A DISTANCE OF 191.35 FEET TO A POINT OF TANGENT;
- (3) NORTH 71°39'21" WEST, A DISTANCE OF 276.15 FEET TO A POINT OF CURVE;
- (4) ALONG THE ARC OF A CURVE TO THE RIGHT WITH A RADIUS OF 208.06 FEET AND A CENTRAL ANGLE OF 37°31'18" A DISTANCE OF 136.26 FEET, THE LONG CHORD OF WHICH BEARS NORTH 52°53'42" WEST, A DISTANCE OF 133.83 FEET TO A POINT OF TANGENT;
- (5) NORTH 34°08'03" WEST, A DISTANCE OF 557.70 FEET TO A POINT OF CURVE;
- (6) ALONG THE ARC OF A CURVE TO THE RIGHT WITH A RADIUS OF 388.56 FEET AND A CENTRAL ANGLE OF 39°23'06" A DISTANCE OF 267.10 FEET, THE LONG CHORD OF WHICH BEARS NORTH 14°26'30" WEST, A DISTANCE OF 261.87 FEET TO A POINT OF TANGENT;
- (7) NORTH 05°15'03" EAST, A DISTANCE OF 755.43 FEET TO A POINT OF CURVE;
- (8) ALONG THE ARC OF A CURVE TO THE RIGHT WITH A RADIUS OF 565.00 FEET AND A CENTRAL ANGLE OF 09°47'20" A DISTANCE OF 96.53, THE LONG CHORD OF WHICH BEARS NORTH 10°08'43" EAST, A DISTANCE OF 96.41 FEET TO A POINT ON THE NORTH LINE OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1;

THENCE SOUTH 89°39'54" EAST ALONG SAID NORTH LINE, A DISTANCE OF 990.20 FEET TO THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1; THENCE SOUTH 00°11'39" EAST, ALONG THE EAST LINE OF SAID SOUTHWEST 1/4 OF THE NORTHEAST 1/4, A DISTANCE OF 313.56 FEET TO THE NORTHWEST CORNER OF LOT 7, COTTONWOOD PARK IN RALSTON VALLEY, RECORDED IN BOOK 55 AT PAGE 10 IN THE RECORDS OF JEFFERSON COUNTY; THENCE NORTH 89°47'39" EAST, ALONG THE NORTH LINE OF SAID LOT 7, A DISTANCE OF 250.22 FEET TO THE NORTHEAST CORNER OF SAID LOT 7; THENCE SOUTHERLY ALONG THE WESTERLY RIGHT-OF-WAY LINE OF JOYCE STREET THE FOLLOWING THREE (3) COURSES:

- (1) SOUTH 29°55'41" WEST, A DISTANCE OF 68.23 FEET TO A POINT OF CURVE;
- (2) ALONG THE ARC OF A CURVE TO THE LEFT WITH A RADIUS OF 125.00 FEET AND A CENTRAL ANGLE OF 29°26'36" A DISTANCE OF 64.30 FEET, THE LONG CHORD OF WHICH BEARS SOUTH 15°12'49" WEST, A DISTANCE OF 63.60 FEET TO A POINT OF TANGENT;
- (3) SOUTH 00°29'04" WEST A DISTANCE OF 201.41 FEET; THENCE ALONG THE SOUTHERLY LINE OF SAID LOT 7 THE FOLLOWING TWO (2) COURSES:
  - (1) SOUTH 71°50'32" WEST, A DISTANCE OF 150.35 FEET;
  - (2) NORTH 68°52'48" WEST, A DISTANCE OF 57.62 FEET TO A POINT ON THE EAST LINE OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 1;

THENCE SOUTH 00°11'39" EAST ALONG SAID EAST LINE, A DISTANCE OF 659.88 FEET TO THE TRUE POINT OF BEGINNING. CONTAINING 39.497 ACRES.

DIXON, KENNETH P.  
1662 S. SAND LILY DRIVE  
GOLDEN, COLORADO 80401

CLARK, J. WICKHAM & DORIS L.  
& CLARK, J. WICKHAM II  
7041 S. 7031 MIDLAND ST.  
GOLDEN, COLORADO 80403

FORBES, DONALD B.  
15000 W. 72nd AVE  
GOLDEN, COLORADO 80403

THE FARMERS RESERVOIR IRRIGATION CO.  
725 MALLEY DRIVE  
NORTHGLENN, CO

NOT A PART

Block 1

Block 3

Block 2

Block

PARCEL NO. 1  
29.497 ACRES

100' FLOOD PLAIN

CHERRY CREEK CANAL

JOYCE STREET

W 68th PLACE

N 1st STREET

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

10' UTILITY EASEMENT  
20' BUILDING LINE  
10' UTILITY EASEMENT

VESTMENT CO.  
OUNGFIELD ST  
HDGE, COLORADO 80033

KUNZ & BARBER  
DEVELOPERS  
4096 YOUNGFIELD ST  
WHEAT RIDGE, COLORADO 80033

TRUE POINT OF BEGINNING

CITY OF ARVADA  
8101 RALSTON RD.  
ARVADA, COLORADO 80002

Block 5

CONCRETE  
BICYCLE PATH


100' UTILITY, FLOOD PLAIN, OPEN SPACE,  
AND PEDESTRIAN EASEMENT

OPEN SPACE TO THE  
CITY OF ARVADA

NEW BRIDGE

CITY OF  
ARVADA  
(SEE ABOVE)

MURRAY, EARL H.  
(SEE ABOVE)



## **APPENDIX D**

### **JEFFERSON COUNTY QUARTER SECTION MAPS**

- 1) 1986 Aerial Photograph - Site vicinity map with street and waterway labels.
- 2) Jefferson County Quarter Section 30-01 map




FIGURE 2 JEFFERSON COUNTY  
1A SECTION 30-01




FIGURE 1 1966 AERIAL PHOTOGRAPH  
SITE VICINITY MAP


## **APPENDIX E**

### **U.S.D.A. SOIL CONSERVATION SERVICE MAPS**

- 1) Soil Survey Map and Legend
- 2) General Soil Map

# SOIL LEGEND

| SYMBOL | NAME   | SYMBOL | NAME  |
|--------|--|--------|---|
| 1      | Aida loam, 0 to 2 percent slopes   | 89     | Loveland Variant gravelly sandy loam, 0 to 2 percent slopes           |
| 2      | Aida-Niwot complex, 0 to 2 percent slopes                                  | 90     | Manzano fine sandy loam, 0 to 2 percent slopes                        |
| 3      | Allens Park Variant-Ratake-Rock outcrop complex, 30 to 50 percent slopes   | 91     | Manzanola clay loam, 0 to 5 percent slopes                            |
| 4      | Arguslois, loamy, 15 to 30 percent slopes                                  | 92     | Manzanola clay loam, 5 to 9 percent slopes                            |
| 5      | Arguslois-Rock outcrop complex, 15 to 60 percent slopes                    | 93     | Manzanola clay loam, 9 to 15 percent slopes                           |
| 6      | Arvada clay loam, 0 to 2 percent slopes                                    | 94     | Manzanola clay loam, 15 to 25 percent slopes                          |
| 7      | Arcelon sandy loam, 5 to 9 percent slopes                                  | 95     | Manzanola cobbly clay loam, 15 to 25 percent slopes                   |
| 8      | Arcelon sandy loam, 9 to 15 percent slopes                                 | 96     | Manzanola-Renonill-Stoneham complex, 9 to 15 percent slopes           |
| 9      | Bailer-Rock outcrop complex, 15 to 50 percent slopes                       | 97     | McClave clay loam, 0 to 3 percent slopes                              |
| 10     | Bailer Variant-Lavina-Rock outcrop complex, 5 to 15 percent slopes         | 98     | Midway clay loam, 9 to 30 percent slopes                              |
| 11     | Bailer Variant-Lavina-Rock outcrop complex, 15 to 30 percent slopes        | 99     | Midway stony clay loam, 15 to 40 percent slopes                       |
| 12     | Blakeland loamy sand, 0 to 9 percent slopes                                | 100    | Nederland very cobbly sandy loam, 15 to 50 percent slopes             |
| 13     | Blakeland loamy sand, 9 to 15 percent slopes                               | 101    | Nederland Variant very cobbly sandy loam, 30 to 50 percent slopes     |
| 14     | Breeca sandy loam, 9 to 25 percent slopes                                  | 102    | Nunn clay loam, 0 to 2 percent slopes                                 |
| 15     | Bresser sandy loam, 0 to 5 percent slopes                                  | 103    | Nunn clay loam, 2 to 5 percent slopes                                 |
| 16     | Bresser gravelly sandy loam, 9 to 25 percent slopes                        | 104    | Nunn clay loam, 5 to 9 percent slopes                                 |
| 17     | Critchell gravelly sandy loam, 0 to 3 percent slopes                       | 105    | Nunn-Urban land complex, 0 to 2 percent slopes                        |
| 18     | Critchell gravelly sandy loam, 3 to 9 percent slopes                       | 106    | Nunn-Urban land complex, 2 to 5 percent slopes                        |
| 19     | Critchell gravelly sandy loam, 9 to 15 percent slopes                      | 107    | Nunn-Urban land complex, 5 to 9 percent slopes                        |
| 20     | Critchell stony sandy loam, 0 to 5 percent slopes                          | 108    | Nunn Variant-Urban land complex, 0 to 3 percent slopes                |
| 21     | Cryofluvents, 0 to 5 percent slopes  | 109    | Paymaster sandy loam, 0 to 3 percent slopes                           |
| 22     | Cumelic Cryopodsols, loamy, 0 to 5 percent slopes                          | 110    | Pits, clayey  |
| 23     | Cuscann very stony sandy loam, 15 to 50 percent slopes                     | 111    | Pits, gravel  |
| 24     | Dacono Variant gravelly clay loam, 0 to 3 percent slopes                   | 112    | Platner loam, 3 to 5 percent slopes                                   |
| 25     | Denver clay loam, 0 to 2 percent slopes                                    | 113    | Platner-Urban land complex, 0 to 3 percent slopes                     |
| 26     | Denver clay loam, 2 to 5 percent slopes                                    | 114    | Raleigh very gravelly sandy loam, 9 to 15 percent slopes              |
| 27     | Denver clay loam, 5 to 9 percent slopes                                    | 115    | Raleigh very gravelly sandy loam, 15 to 30 percent slopes             |
| 28     | Denver cobbly clay loam, 5 to 9 percent slopes                             | 116    | Raleigh very gravelly sandy loam, 30 to 50 percent slopes             |
| 29     | Denver-Kutch clay loams, 5 to 9 percent slopes                             | 117    | Raleigh very gravelly sandy loam, 2 to 9 percent south slopes         |
| 30     | Denver-Kutch clay loams, 9 to 15 percent slopes                            | 118    | Raleigh very gravelly sandy loam, 9 to 15 percent south slopes        |
| 31     | Denver-Kutch-Midway clay loams, 9 to 25 percent slopes                     | 119    | Raleigh very gravelly sandy loam, 15 to 30 percent south slopes       |
| 32     | Denver-Kutch-Urban land complex, 5 to 9 percent slopes                     | 120    | Raleigh stony sandy loam, 30 to 50 percent south slopes               |
| 33     | Denver-Kutch-Urban land complex, 9 to 15 percent slopes                    | 121    | Ratake-Rock outcrop complex, 50 to 70 percent slopes                  |
| 34     | Denver-Urban land complex, 0 to 2 percent slopes                           | 122    | Ratake-Cathedral very stony sandy loams, 25 to 60 percent slopes      |
| 35     | Denver-Urban land complex, 2 to 5 percent slopes                           | 123    | Ratake-Cathedral-Rock outcrop complex, 25 to 60 percent slopes        |
| 36     | Denver-Urban land complex, 5 to 9 percent slopes                           | 124    | Ratake-Cathedral-Rock outcrop complex, 25 to 60 percent north slopes  |
| 37     | Earfree gravelly sandy loam, 9 to 15 percent slopes                        | 125    | Ratake-Lininger stony sandy loams, 30 to 60 percent slopes            |
| 38     | Earfree Variant very gravelly sandy loam, 3 to 9 percent slopes            | 126    | Razor-Heldt clay loams, 9 to 25 percent slopes                        |
| 39     | Earfree Variant very gravelly sandy loam, 9 to 15 percent slopes           | 127    | Razor-Heldt-Midway cobbly clay loams, 15 to 30 percent slopes         |
| 40     | Earfree Variant-Venable complex, 0 to 15 percent slopes                    | 128    | Redrun clay loam, 0 to 3 percent slopes                               |
| 41     | Englewood clay loam, 0 to 2 percent slopes                                 | 129    | Redrun clay loam, 3 to 9 percent slopes                               |
| 42     | Englewood clay loam, 2 to 5 percent slopes                                 | 130    | Redrun clay loam, 9 to 15 percent slopes                              |
| 43     | Englewood clay loam, wet, 0 to 3 percent slopes                            | 131    | Redrun-Chesom Variant clay loams, 9 to 15 percent slopes              |
| 44     | Englewood-Urban land complex, 0 to 2 percent slopes                        | 132    | Renonill loam, 5 to 9 percent slopes                                  |
| 45     | Flatirons very cobbly sandy loam, 0 to 3 percent slopes                    | 133    | Renonill-Manzanola clay loams, 9 to 15 percent slopes                 |
| 46     | Flatirons very stony sandy loam, 0 to 5 percent slopes                     | 134    | Renonill-Midway complex, 9 to 15 percent slopes                       |
| 47     | Flatirons very stony sandy loam, 5 to 9 percent slopes                     | 135    | Resort-Sohinx very gravelly sandy loams, 9 to 15 percent slopes       |
| 48     | Flatirons very stony sandy loam, 9 to 15 percent slopes                    | 136    | Resort-Sohinx very gravelly sandy loams, 15 to 30 percent slopes      |
| 49     | Flatirons very stony sandy loam, 15 to 30 percent slopes                   | 137    | Resort-Sohinx very gravelly sandy loams, 30 to 50 percent slopes      |
| 50     | Fruvaguents, sandy, 0 to 2 percent slopes                                  | 138    | Rock outcrop, igneous and metamorphic                                 |
| 51     | Fondis loam, 0 to 3 percent slopes   | 139    | Rock outcrop, sedimentary   |
| 52     | Garber Variant very gravelly sandy loam, 5 to 9 percent slopes             | 140    | Rock outcrop-Cathedral-Ratake complex, 50 to 100 percent slopes       |
| 53     | Garber Variant very gravelly sandy loam, 9 to 15 percent slopes            | 141    | Robert-Heroman-Rock outcrop complex, 30 to 70 percent slopes          |
| 54     | Grimstone stony sandy loam, 9 to 15 percent slopes                         | 142    | Rooney very cobbly sandy loam, 15 to 50 percent slopes                |
| 55     | Grimstone-Hiwan-Rock outcrop complex, 30 to 60 percent slopes              | 143    | Rooney-Primen-Leyden complex, 15 to 50 percent slopes                 |
| 56     | Grimstone-Peeler-Rock outcrop complex, 15 to 30 percent slopes             | 144    | Rooney-Rock outcrop complex, 50 to 70 percent slopes                  |
| 57     | Grimstone-Peeler-Rock outcrop complex, 30 to 50 percent slopes             | 145    | Rosane sandy loam, 0 to 3 percent slopes                              |
| 58     | Hargrave sandy loam, 3 to 9 percent slopes                                 | 146    | Rosane-Venable fine sandy loams, 0 to 3 percent slopes                |
| 59     | Hargrave-Bernal sandy loams, 9 to 15 percent slopes                        | 147    | Sohinx-Resort-Rock outcrop complex, 50 to 70 percent slopes           |
| 60     | Haverson loam, 0 to 3 percent slopes                                       | 148    | Standley-Leyden-Primen very stony clay loams, 15 to 30 percent slopes |
| 61     | Haverson loam, 3 to 9 percent slopes                                       | 149    | Standley-Nunn gravelly clay loams, 0 to 5 percent slopes              |
| 62     | Heldt clay, 3 to 9 percent slopes  | 150    | Talvar very gravelly loamy sand, 15 to 30 percent slopes              |
| 63     | Heldt clay, 9 to 15 percent slopes   | 151    | Tamfluents, very gravelly, 0 to 3 percent slopes                      |
| 64     | Heroman-Sorucedale-Rock outcrop complex, 9 to 15 percent slopes            | 152    | Trag sandy loam, 3 to 9 percent slopes                                |
| 65     | Heroman-Sorucedale-Rock outcrop complex, 15 to 30 percent slopes           | 153    | Trag sandy loam, 9 to 25 percent slopes                               |
| 66     | Kittredge-Earfree complex, 3 to 9 percent slopes                           | 154    | Troutdale gravelly sandy loam, 3 to 9 percent slopes                  |
| 67     | Kittredge-Earfree complex, 9 to 20 percent slopes                          | 155    | Troutdale-Kittredge sandy loams, 5 to 15 percent slopes               |
| 68     | Kittredge-Venable complex, 0 to 15 percent slopes                          | 156    | Troutdale-Rogert-Kittredge complex, 15 to 30 percent slopes           |
| 69     | Laporte Variant complex, 15 to 60 percent slopes                           | 157    | Troutdale-Sorucedale gravelly sandy loams, 3 to 15 percent slopes     |
| 70     | Lavate sandy loam, 3 to 9 percent slopes                                   | 158    | Truckton sandy loam, 0 to 3 percent slopes                            |
| 71     | Lavate sandy loam, 9 to 15 percent slopes                                  | 159    | Truckton sandy loam, 3 to 9 percent slopes                            |
| 72     | Lavate-Bernal-Rock outcrop complex, 15 to 30 percent slopes                | 160    | Ulm clay loam, 5 to 9 percent slopes                                  |
| 73     | Lavina loam, very rocky, 0 to 5 percent slopes                             | 161    | Ulm-Urban land complex, 0 to 3 percent slopes                         |
| 74     | Leasack clay loam, saline, 0 to 2 percent slopes                           | 162    | Ulm-Urban land complex, 3 to 5 percent slopes                         |
| 75     | Legault-Hiwan stony loamy sands, 5 to 15 percent slopes                    | 163    | Ulm-Urban land complex, 5 to 9 percent slopes                         |
| 76     | Legault-Hiwan stony loamy sands, 15 to 30 percent slopes                   | 164    | Ulm-Urban land complex, 9 to 18 percent slopes                        |
| 77     | Legault-Hiwan-Rock outcrop complex, 30 to 50 percent slopes                | 165    | Ustic Tornorments, loamy, 15 to 50 percent slopes                     |
| 78     | Legault-Talvar-Rock outcrop complex, 50 to 70 percent slopes               | 166    | Ustic Tornorments, clayey, 0 to 50 percent slopes                     |
| 79     | Leyden-Nunn-Rooney complex, 9 to 30 percent slopes                         | 167    | Ustic Tornorments, cool-Rock outcrop complex, 15 to 50 percent slopes |
| 80     | Leyden-Primen-Standley cobbly clay loams, 15 to 50 percent slopes          | 168    | Vainmont clay loam, 0 to 3 percent slopes                             |
| 81     | Leyden-Primen-Standley extremely stony clay loams, 30 to 70 percent slopes | 169    | Veldkamp-Nederland very cobbly sandy loams, 0 to 3 percent slopes     |
| 82     | Leyden-Standley-Primen cobbly clay loams, 9 to 15 percent slopes           | 170    | Venable loam, 0 to 3 percent slopes                                   |
| 83     | Leyden-Standley-Primen very cobbly clay loams, 30 to 60 percent slopes     | 171    | Venable loam, 3 to 9 percent slopes                                   |
| 84     | Lininger-Ratake complex, 5 to 15 percent slopes                            | 172    | Wann fine sandy loam, 0 to 2 percent slopes                           |
| 85     | Lininger-Ratake complex, 15 to 30 percent slopes                           | 173    | Willowman cobbly sandy loam, 0 to 5 percent slopes                    |
| 86     | Lininger-Trag sandy loams, 3 to 9 percent slopes                           | 174    | Willowman-Leyden cobbly loams, 9 to 30 percent slopes                 |
| 87     | Lininger-Trag sandy loams, 9 to 20 percent slopes                          | 175    | Yoder Variant gravelly sandy loam, 9 to 30 percent slopes             |
| 88     | Loveland clay loam, 0 to 1 percent slopes                                  | 176    | Yoder Variant-Midway complex, 15 to 60 percent slopes                 |



### SOIL ASSOCIATIONS

#### COMMONLY WELL DRAINED CLAYEY AND LOAMY SOILS ON HIGH TERRACES, HILL SLOPES AND FANS

1. **Denver** Heavy to very heavy, deep, well-drained, clayey soils that formed in material derived from mudstones and shales.
2. **Denver** Heavy to very heavy, deep, well-drained, clayey soils that formed in material derived from mudstones and shales.
3. **Denver** Heavy to very heavy, deep, well-drained, clayey soils that formed in material derived from mudstones and shales.
4. **Denver** Heavy to very heavy, deep, well-drained, clayey soils that formed in material derived from mudstones and shales.
5. **Denver** Heavy to very heavy, deep, well-drained, clayey soils that formed in material derived from mudstones and shales.
6. **Denver** Heavy to very heavy, deep, well-drained, clayey soils that formed in material derived from mudstones and shales.
7. **Denver** Heavy to very heavy, deep, well-drained, clayey soils that formed in material derived from mudstones and shales.
8. **Denver** Heavy to very heavy, deep, well-drained, clayey soils that formed in material derived from mudstones and shales.

10.9A

10.9B

11

12

13

14

#### COMMONLY SOMEWHAT EXCESSIVELY DRAINED AND SANDY SOILS ON FLOOD PLAINS AND LOW TERRACES

10.9A

#### COMMONLY SOMEWHAT EXCESSIVELY DRAINED AND WELL DRAINED SANDY AND LOAMY SOILS ON HIGH TERRACES AND HILL SLOPES

10.9B

#### COMMONLY WELL DRAINED STONY, GRAVELLY, LOAMY AND SANDY SOILS ON MOUNTAIN SLOPES AND STABLE SUMMITS AND IN CANYONS

11

#### COMMONLY WELL DRAINED STONY, GRAVELLY, LOAMY AND SANDY SOILS ON MOUNTAIN SLOPES AND STABLE SUMMITS AND IN CANYONS

12

#### COMMONLY WELL DRAINED STONY, GRAVELLY, LOAMY AND SANDY SOILS ON MOUNTAIN SLOPES AND STABLE SUMMITS AND IN CANYONS

13

#### COMMONLY WELL DRAINED STONY, GRAVELLY, LOAMY AND SANDY SOILS ON MOUNTAIN SLOPES AND STABLE SUMMITS AND IN CANYONS

14

#### U. S. DEPARTMENT OF AGRICULTURE SOIL CONSERVATION SERVICE

### GENERAL SOIL MAP GOLDEN AREA COLORADO PARTS OF DENVER, DOUGLAS, JEFFERSON AND PARK COUNTIES.

Scale 1:253,440  
0 1 2 3 4 Miles  
0 1 2 3 4 Miles

## **APPENDIX F**

### **LABORATORY RESULTS ATI (ANALYTICAL TECHNOLOGIES, INC.)**



Analytical Technologies, Inc.

229 Commerce Drive Fort Collins, Colorado 80524 (303) 490-1511

---

Message

Dave,

Here are your results.

Steve F.

To Dave Runyon Company ERCE  
Fax No. 843-6215 Date 1-14-92  
From Steven Fry Number of pages including this sheet 31

If you do not receive all the pages please call us back as soon as possible.

**Analytical Technologies, Inc.**

225 Commerce Drive Fort Collins, Colorado 80524 (303) 490-1511

January 14, 1992

Mr. Dave Runyon  
ERCE  
Stanford Place 3, Suite 415  
4582 South Ulster Street Parkway  
Denver, CO 80237

RE: ATI Workorder: 91-12-190  
Client Project Name: Cottonwood ESA

Dear Mr. Runyon:

Two soil samples and two water samples were received from ERCE on December 27, 1991. The samples were scheduled for the following analyses: Volatile Organics, PCB's, and Total Lead. Results for these analyses are contained in the following report.

Please note that the Volatile Organic surrogate recoveries for sample "001" were outside the method required limits. This sample was re-analyzed and the surrogates once again did not meet the required recovery limits. This is probably due to the matrix of the sample, i.e., the sample resembled activated carbon.

Thank you for your confidence in Analytical Technologies, Inc. Should you have any questions, please call.

Sincerely yours,

Steven Fry, Ph.D.  
Project Manager

SF/kci

Enclosures



Analytical Technologies, Inc.

**QUALITY ASSURANCE  
DATA REVIEW**

The data contained in the following report has been reviewed and approved by the appropriate supervisory personnel listed below:

Alex Blanche, GC/GCMS Supervisor

**CERTIFICATION**

Analytical Technologies Inc. certifies that the analyses reported herein are true, complete and correct within the limits of the method employed.



Analytical Technologies, Inc.

**QUALITY ASSURANCE  
DATA REVIEW**

The data contained in the following report has been reviewed and approved by the appropriate supervisory personnel listed below:

Tom Austin, Jr.  
GC/HPLC/Fuels Supervisor

**CERTIFICATION**

Analytical Technologies, Inc. certifies that the analyses reported herein are true, complete and correct within the limits of the method employed.

## Method 8240



Client Sample ID:

Reagent Blank

Lab Name: Analytical Technologies Inc.

Lab Sample ID: 91-12-190-RB

Client Name: ERCE

Date Collected: N/A

Client Project ID: Cottonwood ESA

Date Analyzed: 01/09/92

Sample Matrix: Soil

Dilution Factor: 1

| COMPOUND NAME              | Concentration<br>ug/kg |     |              |
|----------------------------|------------------------|-----|--------------|
| Chloromethane              | <                      | 10  |              |
| Bromomethane               | <                      | 10  |              |
| Vinyl chloride             | <                      | 10  |              |
| Chloroethane               | <                      | 10  |              |
| Methylene chloride         | <                      | 5   |              |
| Acetone                    | <                      | 10  |              |
| Carbon disulfide           | <                      | 5   |              |
| 1,1-Dichloroethene         | <                      | 5   |              |
| 1,1-Dichloroethane         | <                      | 5   |              |
| 1,2-Dichloroethene (Total) | <                      | 5   |              |
| Chloroform                 | <                      | 5   |              |
| 1,2-Dichloroethane         | <                      | 5   |              |
| 2-Butanone                 | <                      | 10  |              |
| 1,1,1-Trichloroethane      | <                      | 5   |              |
| Carbon tetrachloride       | <                      | 5   |              |
| Vinyl Acetate              | <                      | 10  |              |
| Bromodichloromethane       | <                      | 5   |              |
| 1,2-Dichloropropane        | <                      | 5   |              |
| cis-1,3-Dichloropropene    | <                      | 5   |              |
| Trichloroethene            | <                      | 5   |              |
| Dibromochloromethane       | <                      | 5   |              |
| 1,1,2-Trichloroethane      | <                      | 5   |              |
| Benzene                    | <                      | 5   |              |
| trans-1,3-Dichloropropene  | <                      | 5   |              |
| Bromoform                  | <                      | 5   |              |
| 2-Hexanone                 | <                      | 10  |              |
| 4-Methyl-2-pentanone       | <                      | 10  |              |
| Tetrachloroethene          | <                      | 5   |              |
| 1,1,2,2-Tetrachloroethane  | <                      | 5   |              |
| Toluene                    | <                      | 5   |              |
| Chlorobenzene              | <                      | 5   |              |
| Ethylbenzene               | <                      | 5   |              |
| Styrene                    | <                      | 5   |              |
| Total Xylenes              | <                      | 5   |              |
| Surrogate Recoveries:      | %                      | Rec | % Rec Limits |
| 1,2-Dichloroethane-d4      |                        | 87  | 70-121       |
| Toluene-d8                 |                        | 104 | 81-117       |
| Bromofluorobenzene         |                        | 102 | 74-121       |

## Method 8240

Client Sample ID:

001



Lab Name: Analytical Technologies Inc.

Lab Sample ID: 91-12-190-01

Client Name: ERCE

Date Collected: 12/26/91

Client Project ID: Cottonwood ESA

Date Analyzed: 01/09/92

Sample Matrix: Soil

Dilution Factor: 1

| COMPOUND NAME              | Concentration (ug/kg) |       |              |
|----------------------------|-----------------------|-------|--------------|
| Chloromethane              | <                     | 10    |              |
| Bromomethane               | <                     | 10    |              |
| Vinyl chloride             | <                     | 10    |              |
| Chloroethane               | <                     | 10    |              |
| Methylene chloride         |                       | 120   |              |
| Acetone                    |                       | 68    |              |
| Carbon disulfide           | <                     | 5     |              |
| 1,1-Dichloroethene         |                       | 2     | J            |
| 1,1-Dichloroethane         | <                     | 5     |              |
| 1,2-Dichloroethene (Total) |                       | 4     | J            |
| Chloroform                 |                       | 3     | J            |
| 1,2-Dichloroethane         | <                     | 5     |              |
| 2-Butanone                 | <                     | 10    |              |
| 1,1,1-Trichloroethane      |                       | 12    |              |
| Carbon tetrachloride       | <                     | 5     |              |
| Vinyl Acetate              | <                     | 10    |              |
| Bromodichloromethane       | <                     | 5     |              |
| 1,2-Dichloropropane        | <                     | 5     |              |
| cis-1,3-Dichloropropene    | <                     | 5     |              |
| Trichloroethene            |                       | 4     | J            |
| Dibromochloromethane       | <                     | 5     |              |
| 1,1,2-Trichloroethane      | <                     | 5     |              |
| Benzene                    |                       | 4     | J            |
| trans-1,3-Dichloropropene  | <                     | 5     |              |
| Bromoform                  | <                     | 5     |              |
| 2-Hexanone                 | <                     | 10    |              |
| 4-Methyl-2-pentanone       | <                     | 10    |              |
| Tetrachloroethene          |                       | 23    |              |
| 1,1,2,2-Tetrachloroethane  | <                     | 5     |              |
| Toluene                    |                       | 24    |              |
| Chlorobenzene              |                       | 4     | J            |
| Ethylbenzene               |                       | 7     |              |
| Styrene                    | <                     | 5     |              |
| Total Xylenes              |                       | 43    |              |
| Surrogate Recoveries:      | %                     | Rec   | % Rec Limits |
| 1,2-Dichloroethane-d4      |                       | 93    | 70-121       |
| Toluene-d8                 |                       | 72 *  | 81-117       |
| Bromofluorobenzene         |                       | 122 * | 74-121       |

\* Outside control limits.

J = compound detected below practical quantitation limit.

## VOLATILE ORGANICS DATA SHEET

## Tentatively Identified Compounds

Client Sample ID:

001



Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Date Analyzed: 01/09/92

Client Project ID: Cottonwood ESA

Dilution Factor: 1

Lab Sample ID: 91-12-190-01

Matrix: Soil

Concentration units: ug/kg

| COMPOUND NAME          | RT | Concentration | Q |
|------------------------|----|---------------|---|
| Trichlorofluoromethane |    | 120 J         |   |

J = estimated value

## Method 8240

Client Sample ID:

Reagent Blank



Lab Name: Analytical Technologies Inc.

Lab Sample ID: 91-12-190-RB

Client Name: ERCE

Date Collected: N/A

Client Project ID: Cottonwood ESA

Date Analyzed: 01/09/92

Sample Matrix: Water

Dilution Factor: 1

| COMPOUND NAME              | Concentration<br>ug/L |              |
|----------------------------|-----------------------|--------------|
| Chloromethane              | < 10                  |              |
| Bromomethane               | < 10                  |              |
| Vinyl chloride             | < 10                  |              |
| Chloroethane               | < 10                  |              |
| Methylene chloride         | < 5                   |              |
| Acetone                    | < 10                  |              |
| Carbon disulfide           | < 5                   |              |
| 1,1-Dichloroethene         | < 5                   |              |
| 1,1-Dichloroethane         | < 5                   |              |
| 1,2-Dichloroethene (Total) | < 5                   |              |
| Chloroform                 | < 5                   |              |
| 1,2-Dichloroethane         | < 5                   |              |
| 2-Butanone                 | < 10                  |              |
| 1,1,1-Trichloroethane      | < 5                   |              |
| Carbon tetrachloride       | < 5                   |              |
| Vinyl Acetate              | < 10                  |              |
| Bromodichloromethane       | < 5                   |              |
| 1,2-Dichloropropane        | < 5                   |              |
| cis-1,3-Dichloropropene    | < 5                   |              |
| Trichloroethene            | < 5                   |              |
| Dibromochloromethane       | < 5                   |              |
| 1,1,2-Trichloroethane      | < 5                   |              |
| Benzene                    | < 5                   |              |
| trans-1,3-Dichloropropene  | < 5                   |              |
| Bromoform                  | < 5                   |              |
| 2-Hexanone                 | < 10                  |              |
| 4-Methyl-2-pentanone       | < 10                  |              |
| Tetrachloroethene          | < 5                   |              |
| 1,1,2,2-Tetrachloroethane  | < 5                   |              |
| Toluene                    | < 5                   |              |
| Chlorobenzene              | < 5                   |              |
| Ethylbenzene               | < 5                   |              |
| Styrene                    | < 5                   |              |
| Total Xylenes              | < 5                   |              |
| Surrogate Recoveries:      | % Rec                 | % Rec Limits |
| 1,2-Dichloroethane-d4      | 87                    | 76-116       |
| Toluene-d8                 | 104                   | 88-110       |
| Bromofluorobenzene         | 102                   | 86-115       |

## Method 8240

Client Sample ID:

004



Lab Name: Analytical Technologies Inc.

Lab Sample ID: 91-12-190-03

Client Name: ERCE

Date Collected: 12/26/91

Client Project ID: Cottonwood ESA

Date Analyzed: 01/09/92

Sample Matrix: Water

Dilution Factor: 1

| COMPOUND NAME              | Concentration (ug/L) |
|----------------------------|----------------------|
| Chloromethane              | < 10                 |
| Bromomethane               | < 10                 |
| Vinyl chloride             | < 10                 |
| Chloroethane               | < 10                 |
| Methylene chloride         | < 5                  |
| Acetone                    | < 10                 |
| Carbon disulfide           | < 5                  |
| 1,1-Dichloroethene         | < 5                  |
| 1,1-Dichloroethane         | < 5                  |
| 1,2-Dichloroethene (Total) | < 5                  |
| Chloroform                 | < 5                  |
| 1,2-Dichloroethane         | < 5                  |
| 2-Butanone                 | < 10                 |
| 1,1,1-Trichloroethane      | < 5                  |
| Carbon tetrachloride       | < 5                  |
| Vinyl Acetate              | < 10                 |
| Bromodichloromethane       | < 5                  |
| 1,2-Dichloropropane        | < 5                  |
| cis-1,3-Dichloropropene    | < 5                  |
| Trichloroethene            | < 5                  |
| Dibromochloromethane       | < 5                  |
| 1,1,2-Trichloroethane      | < 5                  |
| Benzene                    | < 5                  |
| trans-1,3-Dichloropropene  | < 5                  |
| Bromoform                  | < 5                  |
| 2-Hexanone                 | < 10                 |
| 4-Methyl-2-pentanone       | < 10                 |
| Tetrachloroethene          | < 5                  |
| 1,1,2,2-Tetrachloroethane  | < 5                  |
| Toluene                    | < 5                  |
| Chlorobenzene              | < 5                  |
| Ethylbenzene               | < 5                  |
| Styrene                    | < 5                  |
| Total Xylenes              | < 5                  |
| Surrogate Recoveries:      | % Rec % Rec Limits   |
| 1,2-Dichloroethane-d4      | 87 76-116            |
| Toluene-d8                 | 102 88-110           |
| Bromofluorobenzene         | 101 86-115           |

## Tentatively Identified Compounds

Client Sample ID: 

004

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Date Analyzed: 01/09/92

Client Project ID: Cottonwood ESA

Dilution Factor: 1 1

Lab Sample ID: 91-12-190-03

Matrix: Water

Concentration units: ug/L

| COMPOUND NAME        | RT | Concentration | Q |
|----------------------|----|---------------|---|
| Methyl-t-butyl ether |    | 10 J          |   |

J = estimated value

# VOLATILE MATRIX SPIKE/MATRIX SPIKE DUPLICATE RECOVERY

## Method 8240



Lab Name: Analytical Technologies, Inc.

Client Sample ID:

In House

Client Name: ERCE

Lab Sample ID: 20199905/AZ

Sample Matrix: Water

Date Analyzed: 01/09/92

| Compound           | Spike Added (ug/L) | Sample Concentration (ug/L) | MS Concentration (ug/L) | MS % REC |
|--------------------|--------------------|-----------------------------|-------------------------|----------|
| 1,1-Dichloroethene | 50                 | < 5                         | 57                      | 114      |
| Trichloroethene    | 50                 | < 5                         | 43                      | 86       |
| Benzene            | 50                 | < 5                         | 39                      | 78       |
| Toluene            | 50                 | < 5                         | 51                      | 102      |
| Chlorobenzene      | 50                 | < 5                         | 50                      | 100      |

| Compound           | Spike Added (ug/L) | MSD Concentration (ug/L) | MSD % REC | % RPD |
|--------------------|--------------------|--------------------------|-----------|-------|
| 1,1-Dichloroethene | 50                 | 58                       | 116       | 2     |
| Trichloroethene    | 50                 | 44                       | 88        | 2     |
| Benzene            | 50                 | 41                       | 82        | 5     |
| Toluene            | 50                 | 49                       | 98        | 4     |
| Chlorobenzene      | 50                 | 51                       | 102       | 2     |

### QUALITY CONTROL LIMITS

| Compound           | Water    |     | Soil     |     |
|--------------------|----------|-----|----------|-----|
|                    | %REC     | RPD | % Rec    | RPD |
| 1,1-Dichloroethene | 61 - 145 | 14  | 59 - 172 | 22  |
| Trichloroethene    | 71 - 120 | 14  | 62 - 137 | 24  |
| Benzene            | 76 - 127 | 11  | 60 - 133 | 21  |
| Toluene            | 76 - 125 | 13  | 59 - 139 | 21  |
| Chlorobenzene      | 75 - 130 | 13  | 66 - 142 | 21  |

**PCB ANALYSIS DATA SHEET**  
Method 8080

Lab Name: Analytical Technologies Inc.

Client Name: ERCE

Client Project ID: Cottonwood ESA

Lab Sample ID: 91-12-190-RBS

Sample Matrix: Sodium Sulfate

Sample Weight: 30 g

GPC Cleanup: N

Client Sample ID:

Reagent Blank

Date Collected: N/A

Date Extracted: 12/30/91

Date Analyzed: 01/03/92

Extract Volume: 10 mL

Dilution Factor: 1

| Compound | Conc (mg/kg) |
|----------|--------------|
| PCB 1016 | < 0.03       |
| PCB 1221 | < 0.03       |
| PCB 1232 | < 0.03       |
| PCB 1242 | < 0.03       |
| PCB 1248 | < 0.03       |
| PCB 1254 | < 0.03       |
| PCB 1260 | < 0.03       |

**SURROGATE RECOVERY**

| Compound             | % Recovery |
|----------------------|------------|
| Tetrachloro-m-xylene | 86         |

**PCB ANALYSIS DATA SHEET**  
Method 8080

Lab Name: Analytical Technologies Inc.

Client Name: ERCE

Client Project ID: Cottonwood ESA

Lab Sample ID: 91-12-190-02A

Sample Matrix: Soil

Sample Weight: 30 g

GPC Cleanup: N

Client Sample ID:

002

Date Collected: 12/26/91

Date Extracted: 12/30/91

Date Analyzed: 01/03/92

Extract Volume: 10 mL

Dilution Factor: 1

| Compound | Conc (mg/kg) |
|----------|--------------|
| PCB 1016 | < 0.03       |
| PCB 1221 | < 0.03       |
| PCB 1232 | < 0.03       |
| PCB 1242 | < 0.03       |
| PCB 1248 | < 0.03       |
| PCB 1254 | < 0.03       |
| PCB 1260 | < 0.03       |

**SURROGATE RECOVERY**

| Compound             | % Recovery |
|----------------------|------------|
| Tetrachloro-m-xylene | 98         |

**PCB MATRIX SPIKE RESULTS**  
**Method 8080****Lab Name:** Analytical Technologies, Inc.**Client Sample ID:****In House****Client Name:** ERCE**Lab Sample ID:** 91-12-114-01A**Date Analyzed:** 12/19/91**Sample Matrix:** Soil**GC Column:** DB-1701

| Compound | Spike Added (mg/kg) | Sample Concentration (mg/kg) | MS Concentration (mg/kg) | MS Percent Recovery |
|----------|---------------------|------------------------------|--------------------------|---------------------|
| PCB 1260 | 0.50                | < 0.3                        | 0.597                    | 119                 |

| Compound | Spike Added (mg/kg) | MSD Concentration (mg/kg) | MSD Percent Recovery | RPD |
|----------|---------------------|---------------------------|----------------------|-----|
| PCB 1260 | 0.50                | 0.607                     | 121                  | 2   |



**PCB ON-GOING PRECISION AND RECOVERY**  
**Method 8080**

Lab Name: Analytical Technologies, Inc.

Lab Sample ID: 91-12-190-OPR

Client Name: ERCE

Date Analyzed: 01/03/92

Sample Matrix: Soil

GC Column: DB-608

| Compound | Spike Added (mg/kg) | OPR Concentration (mg/kg) | OPR Percent Recovery |
|----------|---------------------|---------------------------|----------------------|
| PCB 1260 | 0.50                | 0.590                     | 118                  |

| Compound | Spike Added (mg/kg) | OPRD Concentration (mg/kg) | OPRD Percent Recovery | RPD |
|----------|---------------------|----------------------------|-----------------------|-----|
| PCB 1260 | 0.50                | 0.657                      | 131                   | 11  |



Analytical Technologies, Inc.

**QUALITY ASSURANCE  
DATA REVIEW**

The data contained in the following report has been reviewed and approved by the appropriate supervisory personnel listed below:

Steve Workman, GC/HPLC/Inorganics Supervisor

**CERTIFICATION**

Analytical Technologies Inc. certifies that the analyses reported herein are true, complete and correct within the limits of the method employed.

**TOTAL LEAD ANALYSIS DATA SHEET**

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Prep Date: 01/02/92

Client Project ID: Cottonwood ESA

Date Analyzed: 01/03/92

Workorder Number: 91-12-190

Sample Matrix: Soil

| Client ID.    | ATI ID.      | Lead Conc.<br>(mg/kg) |
|---------------|--------------|-----------------------|
| Reagent Blank | 91-12-190-RB | < 5                   |
| 002           | 91-12-190-02 | 56                    |

**TOTAL LEAD ANALYSIS DATA SHEET****Laboratory Name:** Analytical Technologies, Inc.**Date Collected:** 12/26/91**Client Name:** ERCE**Prep Date:** 01/02/92**Client Project ID:** Cottonwood ESA**Date Analyzed:** 01/02/92**Workorder Number:** 91-12-190**Sample Matrix:** Water

| Client ID.    | ATI ID.      | Lead Conc.<br>(µg/L) |
|---------------|--------------|----------------------|
| Reagent Blank | 91-12-190-RB | < 0.003              |
| 005           | 91-12-190-04 | 0.065                |

**TOTAL LEAD MATRIX SPIKE**

Client Sample ID:

**In House**

Laboratory Name: Analytical Technologies, Inc.

Client Name: ERCE

Prep Date: 01/02/92

Lab Sample ID: 9659A/FL

Date Analyzed: 01/03/92

Sample Matrix: Soil

| Compound | Spike Added<br>(mg/kg) | Sample Concentration<br>(mg/kg) | MS Concentration<br>(mg/kg) | MS Percent Recovery |
|----------|------------------------|---------------------------------|-----------------------------|---------------------|
| Lead     | 50                     | < 5                             | 54                          | 108                 |



## TOTAL LEAD MATRIX SPIKE

Client Sample ID:

In House

Laboratory Name: Analytical Technologies, Inc.

Client Name: ERCE

Prep Date: 01/02/92

Lab Sample ID: 9600B-1/FL

Date Analyzed: 01/02/92

Sample Matrix: Water

| Compound | Spike Added (mg/L) | Sample Concentration (mg/L) | MS Concentration (mg/L) | MS Percent Recovery |
|----------|--------------------|-----------------------------|-------------------------|---------------------|
| Lead     | 0.80               | < 0.003                     | 0.80                    | 100                 |

CONTRACTOR ERCE SAMPLERS Rene H. H. , Will Glasgow PROJECT COTTONWOOD ESA  
 SITE CONTACT/PHONE DAVE RUNYON 843-6210 LAB/LOCATION ATI - FORT COLLINS

C-D-C NUMBER

0001

## EPC-RS-001-1, CHAIN OF CUSTODY

ERCE (DENVER)  
 DENVER TECH CENTER  
 STANFORD PLACE #3 STE 415 DENVER CO

|      | DATE/TIME | SAMPLE NUMBER | LOCATION | CONTAINER TYPE | NUMBER OF CONTAINERS | MEDIA (S) / WATER (W) | FILTERED-F POT DISS-P | TURN AROUND RUSH -R | OUT OF SPEC REPORTS | PRESERVATIVE  |     |      |      |       | VOA | OIL-GROSS | Pb + METALS | TOTAL METALS |
|------|-----------|---------------|----------|----------------|----------------------|-----------------------|-----------------------|---------------------|---------------------|---------------|-----|------|------|-------|-----|-----------|-------------|--------------|
|      |           |               |          |                |                      |                       |                       |                     |                     | COOLED TO 4 C | HCl | NaOH | HNO3 | H2SO4 |     |           |             |              |
| 01   | 12/26/91  | 1330          | 001      | LANDFILL       | 20Z GLASS            | 1 S                   |                       |                     |                     | Y             |     |      |      |       | X   |           |             |              |
| 02   |           | 1335          | 002      | LANDFILL       | 20Z GLASS            | 2 S                   |                       |                     |                     | Y             |     |      |      |       | X   | X         |             |              |
| * 03 |           | 1420          | 003      | RAILROAD CREEK | 20Z GLASS            | 1 W                   |                       |                     |                     | Y             |     |      |      |       | X   |           |             |              |
| 04   |           | 1500          | 004      | H&E #6         | 40m A Chku           | 2 W                   |                       |                     |                     | Y             |     |      |      | X     |     |           |             |              |
|      |           | 1505          | 005      | H&E #6         | 12oz                 | 1 W                   |                       |                     |                     | Y             |     | X    |      |       |     | X         |             |              |

| RELINQUISHED BY | DATE/TIME     | RECEIVED BY  | DATE/TIME       | LABORATORY USE ONLY                      |     |
|-----------------|---------------|--------------|-----------------|--|-----|
| Rene Holme      | 12/27/91 0919 | Debi Burdick | 12/27/91 9:15am | PCKG RECD/CUSTODY SEALS INTACT           | Y N |
|                 |               |              |                 | SAMPLE LABELS/COCs AGREE                 | Y N |
|                 |               |              |                 | TEMPERATURE WITHIN SPECIFICATION _____ C |     |
|                 |               |              |                 | CORRECTED COPY ATTACHED                  |     |
| REMARKS         |               |              |                 | PROBLEMS OR DISCREPANCIES                |     |

SHIPMENT METHOD

personal delivery by R&amp;A.

\* HOLD SAMPLE - DO NOT RUN. NOT ENOUGH SAMPLE. ~~AT~~ ROW WILL GET BACK TO US  
 OF ANOTHER CAMP ONLY (TOTAL METALS FOR SOIL & WATER SAMPLES) 12/27/91



Analytical Technologies, Inc. 225 Commerce Drive Fort Collins, Colorado 80524 (303) 490-1511

January 3, 1992

Mr. Dave Runyon  
ERCE  
Stanford Place 3, Suite 415  
4582 South Ulster Street Parkway  
Denver, CO 80237

RE: ATI Workorder: 91-12-195  
Client Project Name: Cottonwood ESA

Dear Mr. Runyon:

One water sample was received from ERCE on December 27, 1991. The sample was scheduled for Total Extractable Petroleum Hydrocarbons analysis. Results for this analysis are contained in the following report.

Thank you for your confidence in Analytical Technologies, Inc. Should you have any questions, please call.

Sincerely yours,

*Steven Fry*

Steven Fry, Ph.D.  
Project Manager

SF/jw

Enclosures



Analytical Technologies, Inc.

**QUALITY ASSURANCE  
DATA REVIEW**

The data contained in the following report has been reviewed and approved by the appropriate supervisory personnel listed below:

Eddy Hamnerquist  
Eddy Hamnerquist, Fuels Supervisor

**CERTIFICATION**

Analytical Technologies, Inc. certifies that the analyses reported herein are true, complete and correct within the limits of the method employed.

**TOTAL EXTRACTABLE PETROLEUM HYDROCARBONS**  
**Modified Method 8015****Lab Name:** Analytical Technologies, Inc.**Date Collected:** 12/27/91**Client Name:** ERCE**Date Extracted:** 12/31/91**Client Project ID:** Cottonwood ESA**Date Analyzed:** 12/31/91**ATI Workorder Number:** 91-12-195**Sample Matrix:** Water

| Client Sample ID | Lab Sample ID | Dilution Factor | Conc. TEPH (mg/L) |
|------------------|---------------|-----------------|-------------------|
| Reagent Blank    | 91-12-195-RB  | 1               | < 1               |
| 006              | 91-12-195-01  | 1               | 2                 |

**Note:** Sample 006 contains high molecular weight components which could not be quantified by TPH-D analytical conditions.

**TOTAL EXTRACTABLE PETROLEUM HYDROCARBONS  
MATRIX SPIKE RESULTS**  
Modified Method 8015

Lab Name: Analytical Technologies, Inc.

Client Sample ID:

008

Client Name: ERCE

Lab Sample ID: 91-12-195-01

Date Analyzed: 12/31/91

Sample Matrix: Water

GC Column: DB-5

| Compound | Spike Added (mg/L) | Sample Concentration (mg/L) | MS Concentration (mg/L) | MS Percent Recovery |
|----------|--------------------|-----------------------------|-------------------------|---------------------|
| TEPH     | 10                 | 2                           | 10                      | 80                  |

| Compound | Spike Added (mg/L) | MSD Concentration (mg/L) | MSD Percent Recovery | Matrix Spike RPD |
|----------|--------------------|--------------------------|----------------------|------------------|
| TEPH     | 10                 | 9.8                      | 78                   | 2                |



## APPENDIX G

### DATA VALIDATION SUMMARY OF LABORATORY RESULTS

Date: 01\15\92  
Client: D. Runyon (Ogden)  
Reviewer: T. Perrin

### Data Validation Summary

#### Samples and Analyses

| Client Sample ID | Lab Sample ID | Analysis   | Matrix |
|------------------|---------------|------------|--------|
| 001              | 91-12-190-01  | Volatiles  | SOIL   |
| 004              | 91-12-190-03  | Volatiles  | WATER  |
| 002              | 91-12-190-02A | PCBs       | SOIL   |
| 002              | 91-12-190-02  | Total Lead | SOIL   |
| 005              | 91-12-190-04  | Total Lead | WATER  |

#### Volatile Organics:

1.

##### Overall Assessment:

Only result summaries were provided so compound identification could not be confirmed from raw instrument results nor could the calculations be verified. No data for instrument tuning or calibration was provided. Data is acceptable with qualifications as noted below.

2.

##### Holding times:

Per W. Glasgow the sample for volatile water analysis was not preserved with acid. The holding time for volatile analysis of an unpreserved water sample is 7 days. The sample was analyzed at 14 days after collection, therefore analytes were qualified "UJ" in sample 004. Since there are no guidelines for soils the soil sample was not qualified.

3.

Surrogate Recoveries:

Surrogate compounds were added to the samples as a measure of purging efficiency. Surrogate recoveries were acceptable for both reagent blanks and sample 004. Recovery for surrogate toluene-d8 was low and bromofluorobenzene high for soil sample 001. All detects were qualified as estimated "J" and all quantitation limits as estimated "UJ" in sample 001 for this QC exceedance. In the case narrative the lab attributed the non-compliant surrogate recoveries to a matrix effect because on reanalysis the surrogate performance did not improve.

4.

Reagent Blank:

A reagent blank was analyzed to evaluate possible laboratory-introduced contamination. No target analytes were reported in the reagent blanks. A TIC result page was not provided for the reagent blanks. Whether this is an omission by the lab or whether no TICs were detected in the reagent blanks is unknown. One tentatively identified compound (TIC) was reported in each sample. Trichlorofluoromethane (freon) is a common laboratory contaminant and therefore may not be a true sample constituent in analysis 001.

5.

Matrix Spike/Matrix Spike Duplicate:

An associated matrix spike/matrix spike duplicate was performed on a water sample although not on the Ogden water sample. % Recoveries and RPDs were acceptable.

PCBs:

1.

Overall Assessment:

No PCBs were reported in the sample. Only result summaries were provided so compound identification could not be confirmed from raw instrument results nor could the calculations be verified. No qualification of data was required.

2.

Holding times:

Holding times were acceptable.

3.

Surrogate Recoveries:

A surrogate compound was added to the sample before extraction as a measure of the extraction efficiency. The surrogate recoveries at 86 and 98% are considered acceptable for the reagent blank and sample 002 respectively.

4. Reagent Blank:  
A reagent blank was analyzed to evaluate possible laboratory-introduced contamination. No target analytes were reported in the method blank.
5. Matrix Spike/Matrix Spike Duplicate:  
A matrix spike/matrix spike duplicate was performed on a soil sample although not on the Ogden soil sample. The MS/MSD was analyzed 11 days before sample 002 was extracted so is not really indicative of extraction conditions for sample 002. % Recoveries and RPDs were acceptable. No qualifications were required.

Total Lead:

1. Overall Assessment:  
Raw data was not provided for review; therefore, sample results and QC data were reviewed based on information presented in the respective summary forms. Sample results were acceptable without qualifications.
2. Holding Times:  
The soil and water sample were analyzed within the water holding time of six months. The water sample was preserved with  $\text{HNO}_3$ .
3. Blanks:  
Blank data presented on the Total Lead analysis data sheet was acceptable.
4. Matrix Spike:  
An acceptable Matrix Spike percent recovery (%R) of 108% and 100% were recorded on the Total Lead Matrix Spike sheet for the soil and water samples respectively.

## Method 8240

Client Sample ID:

001



Lab Name: Analytical Technologies Inc.

Lab Sample ID: 91-12-190-01

Client Name: ERCE

Date Collected: 12/26/91

Client Project ID: Cottonwood ESA

Date Analyzed: 01/09/92

Sample Matrix: Soil

Dilution Factor: 1

| COMPOUND NAME              | Concentration (ug/kg) | Rev          | Qual | Val |
|----------------------------|-----------------------|--------------|------|-----|
| Chloromethane              | < 10                  | CS           | S    | VV  |
| Bromomethane               | < 10                  |              |      |     |
| Vinyl chloride             | < 10                  |              |      |     |
| Chloroethane               | < 10                  |              |      |     |
| Methylene chloride         | 120                   |              |      |     |
| Acetone                    | 68                    |              |      |     |
| Carbon disulfide           | < 5                   | CS           |      |     |
| 1,1-Dichloroethene         | 2 J                   | CS           |      |     |
| 1,1-Dichloroethane         | < 5                   | CS           |      |     |
| 1,2-Dichloroethene (Total) | 4 J                   | CS           |      |     |
| Chloroform                 | 3 J                   | CS           |      |     |
| 1,2-Dichloroethane         | < 5                   | CS           |      |     |
| 2-Butanone                 | < 10                  | CS           |      |     |
| 1,1,1-Trichloroethane      | 12                    | CS           |      |     |
| Carbon tetrachloride       | < 5                   | CS           |      |     |
| Vinyl Acetate              | < 10                  |              |      |     |
| Bromodichloromethane       | < 5                   |              |      |     |
| 1,2-Dichloropropane        | < 5                   |              |      |     |
| cis-1,3-Dichloropropene    | < 5                   |              |      |     |
| Trichloroethene            | 4 J                   | CS           |      |     |
| Dibromochloromethane       | < 5                   | CS           |      |     |
| 1,1,2-Trichloroethane      | < 5                   | CS           |      |     |
| Benzene                    | 4 J                   | CS           |      |     |
| trans-1,3-Dichloropropene  | < 5                   | CS           |      |     |
| Bromoform                  | < 5                   |              |      |     |
| 2-Hexanone                 | < 10                  |              |      |     |
| 4-Methyl-2-pentanone       | < 10                  |              |      |     |
| Tetrachloroethene          | 23                    |              |      |     |
| 1,1,2,2-Tetrachloroethane  | < 5                   | CS           |      |     |
| Toluene                    | 24                    | CS           |      |     |
| Chlorobenzene              | 4 J                   | CS           |      |     |
| Ethylbenzene               | 7                     | CS           |      |     |
| Styrene                    | < 5                   | CS           |      |     |
| Total Xylenes              | 43                    |              |      |     |
| Surrogate Recoveries:      | % Rec                 | % Rec Limits |      |     |
| 1,2-Dichloroethane-d4      | 93                    | 70-121       |      |     |
| Toluene-d8                 | 72 *                  | 81-117       |      |     |
| Bromofluorobenzene         | 122 *                 | 74-121       |      |     |

\* Outside control limits.

J = compound detected below practical quantitation limit.

OGDEN VALIDATED

## Tentatively Identified Compounds

Client Sample ID:



001

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Date Analyzed: 01/09/92

Client Project ID: Cottonwood ESA

Dilution Factor: 1

Lab Sample ID: 91-12-190-01

Matrix: Soil

Concentration units: ug/kg

| COMPOUND NAME          | RT | Concentration | Q | Raw<br>Data | Qual<br>Code | Val<br>Code |
|------------------------|----|---------------|---|-------------|--------------|-------------|
| Trichlorofluoromethane |    | 120 J         |   | NJ          |              | WV          |

J = estimated value

**OGDEN VALIDATED**

Method 8240

Client Sample ID:

004



Lab Name: Analytical Technologies Inc.

Lab Sample ID: 91-12-190-03

Client Name: ERCE

Date Collected: 12/26/91

Client Project ID: Cottonwood ESA

Date Analyzed: 01/09/92

Sample Matrix: Water

Dilution Factor: 1

| COMPOUND NAME              | Concentration (ug/L) | Rev<br>Qual  | Qual<br>Code | Val<br>Code |
|----------------------------|----------------------|--------------|--------------|-------------|
| Chloromethane              | < 10                 | UJ           | H            | VV          |
| Bromomethane               | < 10                 |              |              |             |
| Vinyl chloride             | < 10                 |              |              |             |
| Chloroethane               | < 10                 |              |              |             |
| Methylene chloride         | < 5                  |              |              |             |
| Acetone                    | < 10                 |              |              |             |
| Carbon disulfide           | < 5                  |              |              |             |
| 1,1-Dichloroethene         | < 5                  |              |              |             |
| 1,1-Dichloroethane         | < 5                  |              |              |             |
| 1,2-Dichloroethene (Total) | < 5                  |              |              |             |
| Chloroform                 | < 5                  |              |              |             |
| 1,2-Dichloroethane         | < 5                  |              |              |             |
| 2-Butanone                 | < 10                 |              |              |             |
| 1,1,1-Trichloroethane      | < 5                  |              |              |             |
| Carbon tetrachloride       | < 5                  |              |              |             |
| Vinyl Acetate              | < 10                 |              |              |             |
| Bromodichloromethane       | < 5                  |              |              |             |
| 1,2-Dichloropropane        | < 5                  |              |              |             |
| cis-1,3-Dichloropropene    | < 5                  |              |              |             |
| Trichloroethene            | < 5                  |              |              |             |
| Dibromochloromethane       | < 5                  |              |              |             |
| 1,1,2-Trichloroethane      | < 5                  |              |              |             |
| Benzene                    | < 5                  |              |              |             |
| trans-1,3-Dichloropropene  | < 5                  |              |              |             |
| Bromoform                  | < 5                  |              |              |             |
| 2-Hexanone                 | < 10                 |              |              |             |
| 4-Methyl-2-pentanone       | < 10                 |              |              |             |
| Tetrachloroethene          | < 5                  |              |              |             |
| 1,1,2,2-Tetrachloroethane  | < 5                  |              |              |             |
| Toluene                    | < 5                  |              |              |             |
| Chlorobenzene              | < 5                  |              |              |             |
| Ethylbenzene               | < 5                  |              |              |             |
| Styrene                    | < 5                  |              |              |             |
| Total Xylenes              | < 5                  |              |              |             |
| Surrogate Recoveries:      | % Rec                | % Rec Limits |              |             |
| 1,2-Dichloroethane-d4      | 87                   | 76-116       |              |             |
| Toluene-d8                 | 102                  | 88-110       |              |             |
| Bromofluorobenzene         | 101                  | 86-115       |              |             |

OGDEN VALIDATED

## Tentatively Identified Compounds

Client Sample ID

004

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Date Analyzed: 01/09/92

Client Project ID: Cottonwood ESA

Dilution Factor: 1 1

Lab Sample ID: 91-12-190-03

Matrix: Water

Concentration units: ug/L

| COMPOUND NAME        | RT | Concentration | Q |
|----------------------|----|---------------|---|
| Methyl-t-butyl ether |    | 10 J          |   |

|      |      |      |
|------|------|------|
| Rev  | Qual | Val  |
| Qual | Code | Code |
| NJ   |      | VV   |

J = estimated value

**OGDEN VALIDATED**

**PCB ANALYSIS DATA SHEET**  
Method 8080

Lab Name: Analytical Technologies Inc.

Client Name: ERCE

Client Project ID: Cottonwood ESA

Lab Sample ID: 91-12-190-02A

Sample Matrix: Soil

Sample Weight: 30 g

GPC Cleanup: N

Client Sample ID:

002

Date Collected: 12/26/91

Date Extracted: 12/30/91

Date Analyzed: 01/03/92

Extract Volume: 10 mL

Dilution Factor: 1

| Compound | Conc (mg/kg) | Res<br>Qual | Qual<br>Code | Vol<br>Code |
|----------|--------------|-------------|--------------|-------------|
| PCB 1016 | < 0.03       | U           |              | VV          |
| PCB 1221 | < 0.03       |             |              |             |
| PCB 1232 | < 0.03       |             |              |             |
| PCB 1242 | < 0.03       |             |              |             |
| PCB 1248 | < 0.03       |             |              |             |
| PCB 1254 | < 0.03       |             |              |             |
| PCB 1260 | < 0.03       |             |              |             |

**SURROGATE RECOVERY**

| Compound             | % Recovery |
|----------------------|------------|
| Tetrachloro-m-xylene | 98         |

**OGDEN VALIDATED**



## TOTAL LEAD ANALYSIS DATA SHEET

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Prep Date: 01/02/92

Client Project ID: Cottonwood ESA

Date Analyzed: 01/02/92

Workorder Number: 91-12-190

Sample Matrix: Water

| Client ID.    | ATI ID.      | Lead Conc.<br>(mg/L) |
|---------------|--------------|----------------------|
| Reagent Blank | 91-12-190-RB | < 3.003              |
| 005           | 91-12-190-04 | 0.065                |

|             |              |             |
|-------------|--------------|-------------|
| Raw<br>Qual | Qual<br>Code | Val<br>Code |
|             |              | VV          |

OGDEN VALIDATED

**TOTAL LEAD ANALYSIS DATA SHEET**

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Prep Date: 01/02/92

Client Project ID: Cottonwood ESA

Date Analyzed: 01/03/92

Workorder Number: 91-12-190

Sample Matrix: Soil

| Client ID.    | ATI ID.      | Lead Conc.<br>(mg/kg) | Rev<br>Qual | Qual<br>Code | Val<br>Code |
|---------------|--------------|-----------------------|-------------|--------------|-------------|
| Reagent Blank | 91-12-190-RB | < 5                   |             |              |             |
| 002           | 91-12-190-02 | 56                    |             |              | VV          |

**OGDEN VALIDATED**

Qualifier Codes for Organics

- |   |    |
|---|----|
| 1) Holding times were exceeded:   | H  |
| 2) Tuning (BFB or DETPP) was non-compliant:   | M  |
| 3) Calibration:   |    |
| a) RRF was <0.05:   | R  |
| b) %RSD or %D was outside of QC limits:   | C  |
| 4) Blanks:  |    |
| a) Presumed contamination from method blank:  | B  |
| b) Presumed contamination from trip blank:  | T  |
| c) Presumed contamination from field blank:   | F  |
| 5) Surrogate recovery was outside of QC limits:   | S  |
| 6) MS/MSD recovery was poor or RPD high:  | Q  |
| 7) Field duplicates showed poor agreement:  | E  |
| 8) IS Performance was unsatisfactory:   | I  |
| 9) Compound ID:   |    |
| a) False positive (reported compound was not present):  | +  |
| b) False Negative (compound was present but not reported):  | -  |
| 10) Reported result or other information was incorrect:   | \$ |
| 11) TIC identity or reported retention time has been changed:   | ?  |
| 12) Original analyses, dilutions, reanalyses or duplicate data that should not be used because another more technically sound analysis is available:  | D  |
| 13) Instrument performance for pesticides was poor:   | P  |
| 14) Unusual problems with the data that have been described in the Data Summary in a specific section. For example, *11 indicates that an unusual problem has been described in section 11 of the Data Summary: | *# |

### Reviewer Codes

- U     The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.
- J     The analyte was positively identified in the sample, but the associated numerical value may not be an accurate representation of the amount actually present in the environmental sample. Values are of limited use.
- R     The data are unusable (presence or absence cannot be determined). Resampling and/or reanalysis is necessary for verification.
- N     Presumptive evidence of the presence of the material.
- NJ    Presumptive evidence of the presence of the material at an estimated quantity.
- UU    The material was analyzed for but was not detected. The sample quantitation limit is an estimated quantity.

Validation Codes


| Validation Code | Definition        | Usability  |
|-----------------|-------------------|--|
| VV              | Validated Valid   | Usable data  |
| VI              | Validated Invalid | Unusable for any purpose.                              |
| UN              | Unvalidated       | All data which has not been validated e.g. trip blanks |

## APPENDIX H

### CHEN AND ASSOCIATES CONSULTING GEOTECHNICAL ENGINEERS


"Soil & Foundation Investigation Proposed Bridge Across Ralston  
Creek Cottonwood Subdivision"

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 6 CH 1 PID  
 Conditions : RH02 WS01 5ML PURGE COLLECTED @ 1330 @ 15'  
 ERCE 59TH & INDIANA ARVADA, CO  
 SW-846 METHOD 8015/8020  
 File : 1225C6.CHR  
 Temperature : 8020.TEM  
 Components : 8020C.CPT  
 Date : 12/26/1991  
 Time : 14:43:34




| Component                | Number | Retention | Area    | External | Internal | Units |
|--------------------------|--------|-----------|---------|----------|----------|-------|
| Toluene                  | 1      | 16.391    | 61.62   | N/A      | N/A      | NG    |
| 1,4-Dichlorobenzene surr | 2      | 17.033    | 994.28  | 887.36   | 150.0000 | NG    |
| Toluene                  | 3      | 18.000    | 78.47   | N/A      | N/A      | NG    |
| m/p-Xylene               | 6      | 20.258    | 112.90  | N/A      | N/A      | NG    |
| o-Xylene                 | 7      | 20.883    | 29.75   | N/A      | N/A      | NG    |
| BFB - surr               | 8      | 21.783    | 749.35  | 279.53   | 150.0000 | NG    |
|                          |        |           | 2026.38 | 224.01   | 296.0000 |       |

Control File : 8020.CUN  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 6 CH 1 PID  
 Conditions : 5ML DI H2O BLANK (250NG SURR'S)  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225C4.CHR  
 Temperature : 8020.TEM  
 Components : 8020CD23.CPT  
 Date : 12/26/1991  
 Time : 11:29:45




| Component    | Number | Retention | Area   | External | Internal | Units |
|--------------|--------|-----------|--------|----------|----------|-------|
| Toluene      | 1      | 16.366    | 83.15  | N/A      | N/A      | NG    |
| Toluene surr | 2      | 17.166    | 814.00 | 734.82   | 150.0000 | NG    |
| Toluene      | 3      | 18.133    | 92.30  | N/A      | N/A      | NG    |
| m/p-Xylene   | 4      | 20.358    | 68.40  | N/A      | N/A      | NG    |
| o-Xylene     | 7      | 20.983    | 35.00  | N/A      | N/A      | NG    |
| BFB - surr   | 8      | 21.908    | 785.03 | 291.92   | 150.0000 | NG    |

Control file : 8020.CON  
 Operator : GED ENVIRONMENTAL  
 Description : INSTRUMENT 6 CH 1 PID  
 Conditions : 5000NG BTEX CALIB STD (250NG SURR'S)  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225C3.CHR  
 Temperature : 8020.TEM  
 Components : 8020CD23.CPT  
 Date : 12/26/1991  
 Time : 10:50:50




| Component      | Number | Retention | Area     | External | Internal  | Units |
|----------------|--------|-----------|----------|----------|-----------|-------|
| Xylene         | 1      | 16.083    | 17514.46 | 5001.31  | 1943.2584 | NG    |
| p-Toluene surr | 2      | 16.816    | 403.14   | 386.05   | 150.0000  | NG    |
| Toluene        | 3      | 17.766    | 15964.05 | 5001.31  | 1943.2552 | NG    |
| Ethylbenzene   | 5      | 19.758    | 7608.69  | 4999.09  | 3967.3364 | NG    |
| m/p-Xylene     | 6      | 19.958    | 8484.13  | 5002.66  | 3970.1669 | NG    |
| o-Xylene       | 7      | 20.591    | 12297.65 | 4998.99  | 3967.2535 | NG    |
| BFB - surr     | 8      | 21.225    | 91.21    | 51.07    | 150.0000  | NG    |
| BFB - surr     | 8      | 21.458    | 488.58   | 189.01   | 150.0000  | NG    |

Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 6 CH 2 FID  
 Conditions : 250NG BTEX CALIB STD  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225D1.CHR  
 Temperature : 8020.TEM  
 Components : 8020TPGH.CPT  
 Date : 12/26/1991  
 Time : 07:07:01




| Component      | Number | Retention | Area    | External | Internal | Units |
|----------------|--------|-----------|---------|----------|----------|-------|
| TOTL PRGBL H-C | 1      | 16.375    | 6655.88 | N/A      | N/A      |       |
| 1              |        |           | 6655.88 | N/A      | N/A      |       |

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 6 CH 1 PID  
 Conditions : 250NG BTEX CALIB STD  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225C1.CHR  
 Temperature : 8020.TEM  
 Components : 8020CD23.CPT  
 Date : 12/26/1991  
 Time : 07:07:01




| Component          | Number | Retention | Area    | External | Internal | Units |
|--------------------|--------|-----------|---------|----------|----------|-------|
| Benzene            | 1      | 16.308    | 1413.79 | 251.12   | 74.7528  | NG    |
| Fluorobenzene surr | 2      | 17.025    | 541.97  | 503.90   | 150.0000 | NG    |
| Toluene            | 3      | 17.841    | 58.60   | N/A      | N/A      | NG    |
| Toluene            | 4      | 18.025    | 1231.83 | 250.59   | 74.5956  | NG    |
| Ethylbenzene       | 5      | 20.091    | 758.58  | 249.01   | 190.3119 | NG    |
| m/p-Xylene         | 6      | 20.283    | 1102.80 | 251.80   | 192.4420 | NG    |
| o-Xylene           | 7      | 20.916    | 1284.35 | 251.87   | 192.4984 | NG    |
| BFB - surr         | 8      | 21.825    | 509.49  | 196.27   | 150.0000 | NG    |

Control file : 8020.CON  
 Operator : GED ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 1 PID  
 Conditions : BHO6 WSO1 5ML PURGE COLLECTED @ 1453 @ 18'  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225A6.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 15:19:45




| Component       | Number | Retention | Area    | External | Internal | Units |
|-----------------|--------|-----------|---------|----------|----------|-------|
| Benzene         | 1      | 16.333    | 49.60   | 6.53     | 1.6474   | NG    |
| F3-Toluene surr | 2      | 16.958    | 771.58  | 594.23   | 150.0000 | NG    |
| I - surr        | 8      | 21.566    | 439.30  | 148.56   | 150.0000 | NG    |
| 3               |        |           | 1260.48 | 749.32   | 301.6474 |       |

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 1 PID  
 Conditions : BH03 WS01 SML PURGE COLLECTED @ 1352 @ 18'  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225A5.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 14:21:11




| Component       | Number | Retention | Area    | External | Internal | Units |
|-----------------|--------|-----------|---------|----------|----------|-------|
| F3-Toluene surr | 2      | 17.075    | 732.33  | 566.76   | 150.0000 | NG    |
| Toluene         | 6      | 17.991    | 27.98   | 3.68     | 0.9742   | NG    |
| F3 - surr       | 8      | 21.708    | 402.92  | 141.17   | 150.0000 | NG    |
| 3               |        |           | 1163.23 | 711.61   | 300.9742 |       |

Control File : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 1 PID  
 Conditions : RALSTON CRK WS01 5ML PURGE COLLT'D @1325@SURF.  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225A4.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 13:33:35




| Component       | Number | Retention | Area    | External | Internal | Units |
|-----------------|--------|-----------|---------|----------|----------|-------|
| F3-Toluene surr | 2      | 17.008    | 754.44  | 582.24   | 150.0000 | NG    |
| Toluene         | 3      | 17.908    | 32.62   | 4.29     | 1.1059   | NG    |
| m-Xylene        | 6      | 20.091    | 39.45   | 10.60    | 10.4128  | NG    |
| l - surr        | 8      | 21.600    | 460.04  | 152.77   | 150.0000 | NG    |
| 4               |        |           | 1286.55 | 749.90   | 311.5188 |       |

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 1 PID  
 Conditions : BHD1 WS01 5ML PURGE COLLECTED @ 1057 @ 12'  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225A3.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 11:11:45




| Component       | Number | Retention | Area    | External | Internal | Units |
|-----------------|--------|-----------|---------|----------|----------|-------|
| Benzene         | 1      | 16.391    | 38.15   | 5.02     | 1.3140   | NG    |
| E3-Toluene surr | 2      | 17.025    | 741.30  | 573.04   | 150.0000 | NG    |
| Toluene         | 3      | 17.941    | 34.55   | 4.55     | 1.1900   | NG    |
| m-Xylene        | 6      | 20.100    | 43.50   | 11.69    | 12.0738  | NG    |
| BFB - surr      | 8      | 21.625    | 423.13  | 145.28   | 150.0000 | NG    |
|                 | 5      |           | 1280.63 | 739.58   | 314.5778 |       |

Operator : GED ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 1 PID  
 Conditions : 5 ML DI H2O BLANK (250NG SURR'S)  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225A2.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 09:26:18




| Component       | Number | Retention | Area    | External | Internal | Units |
|-----------------|--------|-----------|---------|----------|----------|-------|
| Benzene         | 1      | 16.391    | 26.05   | 3.43     | 0.8672   | NG    |
| FS-Toluene surr | 2      | 17.041    | 750.60  | 579.54   | 150.0000 | NG    |
| Toluene         | 3      | 17.941    | 57.50   | 7.57     | 1.9582   | NG    |
| m-Xylene        | 6      | 20.066    | 78.28   | 21.04    | 24.7398  | NG    |
| o-Xylene        | 7      | 20.691    | 69.00   | 13.27    | 15.6013  | NG    |
| BFB - surr      | 8      | 21.575    | 335.93  | 127.58   | 150.0000 | NG    |
|                 | 6      |           | 1317.35 | 752.43   | 343.1865 |       |

Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 2 FID  
 Conditions : 250NG BTEX CALIB STD  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225B1.CHR  
 Temperature : 8020.TEM  
 Components : 8020TPGH.CPT  
 Date : 12/26/1991  
 Time : 07:06:29



| Component      | Number | Retention | Area    | External | Internal | Units |
|----------------|--------|-----------|---------|----------|----------|-------|
| TOTL PRGBL H-C | 1      | 16.450    | 9788.09 | N/A      | N/A      |       |
| 1              |        |           | 9788.09 | N/A      | N/A      |       |

Description : INSTRUMENT 5 CH 1 PID  
 Conditions : 250NG BTEX CALIB STD  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225A1.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 07:06:29



| Component       | Number | Retention | Area    | External | Internal  | Units |
|-----------------|--------|-----------|---------|----------|-----------|-------|
| Benzene         | 1      | 16.425    | 1566.06 | 206.06   | 76.4270   | NG    |
| F3-Toluene surr | 2      | 17.100    | 500.43  | 404.42   | 150.0000  | NG    |
| Toluene         | 3      | 18.041    | 1360.70 | 179.04   | 66.4053   | NG    |
| Ethylbenzene    | 5      | 20.083    | 372.12  | 186.06   | 271.8159  | NG    |
| m-Xylene        | 6      | 20.275    | 806.92  | 216.91   | 316.8863  | NG    |
| o-Xylene        | 7      | 20.916    | 1161.59 | 223.38   | 326.3371  | NG    |
| BFB - surr      | 8      | 21.833    | 213.23  | 102.68   | 150.0000  | NG    |
|                 | 7      |           | 5981.06 | 1518.56  | 1357.8717 |       |

Client: ERCE  
Chromatographer: Adam P. Macdonald  
Analysis Date: December 26, 1991  
Analysis: SW-846 Method 8015/8020  
Location: 69th & Indiana Arvada, CO  
Sample Number: BH06 WS01

| Analyte                     | Concentration |
|-----------------------------|---------------|
| Benzene                     | <5 ug/L       |
| Toluene                     | <5 ug/L       |
| Ethylbenzene                | <5 ug/L       |
| Total Xylenes               | <5 ug/L       |
| Total Volatile Hydrocarbons | <2 mg/L       |

Client: ERCE  
Chromatographer: Adam P. Macdonald  
Analysis Date: December 26, 1991  
Analysis: SW-846 Method 8015/8020  
Location: 69th & Indiana Arvada, CO  
Sample Number: RALSTON CRK WS01

| Analyte                     | Concentration |
|-----------------------------|---------------|
| Benzene                     | <5 ug/L       |
| Toluene                     | <5 ug/L       |
| Ethylbenzene                | <5 ug/L       |
| Total Xylenes               | <5 ug/L       |
| Total Volatile Hydrocarbons | <2 mg/L       |



# chen and associates

CONSULTING GEOTECHNICAL ENGINEERS


98 SOUTH ZUNI STREET • DENVER, COLORADO 80223 • 303/744-7105

SOIL & FOUNDATION INVESTIGATION  
PROPOSED BRIDGE ACROSS RALSTON CREEK  
COTTONWOOD SUBDIVISION  
JEFFERSON COUNTY, COLORADO

Prepared for:

KKBNA  
7456 W. 5th Avenue  
Denver CO 80226

Attn: Mr. Gary Thomas



K-K-B-N-A

Job No. 23,548

January 27, 1982

OFFICES: CASPER • COLORADO SPRINGS • GLENWOOD SPRINGS • SALT LAKE CITY

## TABLE OF CONTENTS

|  |    |
|--|----|
| CONCLUSIONS                                  | 1  |
| PURPOSE AND SCOPE OF STUDY                   | 2  |
| PROPOSED CONSTRUCTION                        | 2  |
| SITE CONDITIONS                              | 2  |
| SUBSURFACE CONDITIONS                        | 3  |
| EXISTING LANDFILL                            | 4  |
| FOUNDATION RECOMMENDATIONS                   | 6  |
| FOUNDATION ALTERNATES                        | 9  |
| ABUTMENT AND WINGWALL BACKFILL               | 11 |
| LIMITATIONS                                  | 11 |
| FIG. 1 - LOCATION OF EXPLORATORY HOLES       |    |
| FIG. 2 - LOGS OF EXPLORATORY HOLES           |    |
| FIG. 3 - LEGEND & NOTES                      |    |
| FIG. 4 - SWELL-CONSOLIDATION TEST RESULTS    |    |
| FIG. 5 - GRADATION TEST RESULTS              |    |
| TABLE I - SUMMARY OF LABORATORY TEST RESULTS |    |

## PURPOSE AND SCOPE OF STUDY

This report presents the results of a soil and foundation investigation for a bridge across Ralston Creek in Cottonwood Subdivision, Jefferson County, Colorado. The project site is shown on Fig. 1.

This report has been prepared to summarize the data obtained and to present our conclusions and recommendations based on the conditions encountered. Design parameters and a discussion of geotechnical engineering considerations related to construction of the proposed facility are included.

## PROPOSED CONSTRUCTION

An 80 foot long single-span structure is proposed for the site. The structure will be approximately 44 feet wide and include two 15 foot lanes and two 5 foot sidewalks with parapets. The type of construction had not been finalized at the time of our investigation. For purposes of this report, the foundation loads were assumed to range between 100 and 300 kips per abutment.

If loadings or conditions are significantly different from those described above, we should be notified to re-evaluate the recommendations contained in this report.

## SITE CONDITIONS

The bridge site is located in the Cottonwood Subdivision on Kilmer Street. The structure will provide access across Ralston Creek. At the time of our investigation, the creek was approximately 4 feet wide

with flowing water about 6 inches deep. The north bank is nearly vertical with an overall depth of approximately 12 feet. The south bank is on a 1:1 slope with an intermediate bench.

The site was vacant at the time of our investigation. The vegetation consists of native grasses, weeds and deciduous trees along Ralston Creek.

Croke Canal is approximately 300 feet west of the proposed ditch site and runs perpendicular to Ralston Creek. The flow in the canal is approximately 15 feet wide with the water level at approximately elevation 60. A gate controls the flow from the canal into the creek. At the time of our investigation, the gate was closed. It appears that water seeps from the canal into the creek.

#### SUBSURFACE CONDITIONS

To evaluate the subsurface conditions at the bridge site, 3 test holes were drilled at the approximate locations shown on Fig. 1. Six additional test holes were drilled in the subdivision south of Ralston Creek to determine the extent and depth of trash fill.

In general, the subsoils at the site were highly variable. They consisted of 20 to 25 feet of trash fill, organic silt, clay, sand and gravel overlying bedrock. Trash fill varied in depth from 8 to 16 feet across the entire area south of Ralston Creek. This is an old landfill which consists of approximately 3 feet of sandy clay overlying various metal, plastic, wood, paper, glass and organic material. The exact lateral and vertical extent of the fill was not determined as a result of this investigation.

A 2.5 to 3 foot layer of organic silt was encountered in Test Holes 1, 7 and 9 below the trash fill. The clay is sandy and medium stiff and the sand is clayey and medium dense. The gravel and sand layer varied in thickness from 7 to 13 feet. This material is poorly graded and dense to very dense with scattered cobbles.

Claystone bedrock underlies the overburden soils. The claystone consists of a 1.5 to 2.5 foot weathered mantel overlying sandy and hard to very hard claystone. Field penetration tests and unconfined compression tests indicate that the bedrock is capable of supporting moderate foundation loads without undergoing significant settlements. Results of laboratory tests are shown on Figs 4 and 5 and summarized on Table I.

Free water was encountered at depths of 10.5 to 14 feet below the ground surface at the time of drilling and when measured 4 to 8 days after drilling, see Figs. 2 and 3. } Ground intersect landfill


#### EXISTING LANDFILL

Landfill debris consisting of mixtures of wood, paper, glass, plastic and metal was encountered in all of the test holes drilled south of Ralston Creek. This area and two areas to the south have been identified by the Jefferson County Health Department as known landfills. The approximate locations of these fills, results of bar hole punch gas surveys and landfill histories, are presented in a report prepared by the department.<sup>1</sup>

1. Jefferson County Health Department, Methane Site Investigation, 1980.

Combustible gas measurements were taken during our investigation to determine if combustible gases were present in the landfill. The measurements were obtained with an MSA Model 53 gas scope. This instrument allows the measurement of the percent by volume of combustible gas in air and the percent lower explosive limit (LEL). The measurements obtained indicated 85% to 100% of the LEL and 3% to 28% combustible gases. The readings are summarized below:

| <u>Hole No.</u> | <u>% LEL</u> | <u>% Gas</u> |
|-----------------|--------------|--------------|
| 4               | 100          | 10           |
| 5               | 85           | 3            |
| 6               | 100          | 28           |
| 9               | 100          | 13           |

 Based on these readings, it appears that combustible gas is being generated within this landfill in quantities sufficient to be considered a hazard. The combustible range of methane gas is between 5% and 15% by volume in air. Concentrations above this range are too rich to burn. However, gas migration or exposure to the atmosphere will result in dilution of the gas and result in a flammable condition.

*both for  
excavation  
& parking*

Care should be taken when excavating within or adjacent to the landfill mass. Venting of excavations will be required. Any structures built over the landfill will require special methane gas controls. There are 2 basic approaches to controlling the migration of methane into structures. These include barriers separating the proposed structure from the landfill and ventilation systems. Access roads, parking areas, underground utilities and other facilities constructed on landfill materials will be subjected to large differential movements and a corrosive environment. The owner should

be aware of the high risk of distress associated with construction on landfills.

#### FOUNDATION RECOMMENDATIONS

Based on the subsurface conditions encountered at the site and the proposed construction, we recommend that the bridge be supported on drilled piers founded in the underlying unweathered bedrock. The following design and construction details should be observed for a drilled pier foundation system:

- (1) Piers should be designed for a maximum end bearing pressure of 40,000 psf and a skin friction of 4,000 psf for the portion of the pier in unweathered bedrock. Piers should be designed for a minimum dead load pressure of 15,000 psf based on end area only. Uplift on the piers can be resisted by utilizing 50% of the skin friction value plus the weight of the pier.
- (2) Piers should penetrate at least three pier diameters into the competent bedrock. A minimum penetration of 5 feet into the bedrock is recommended.
- (3) Piers should be designed to resist lateral loads assuming a modulus of horizontal subgrade reaction in the clay of 40 tcf, a constant of horizontal subgrade reaction in the granular soils of 60 tcf and a modulus of horizontal subgrade reaction of 200 tcf in the bedrock. Resistance to lateral loads should be neglected in the trash fill and all materials above estimated scour depth.
- (4) The minimum spacing requirements between caissons on the site should be 3 diameters from center to center. At this spacing, no

reduction in axial or horizontal soil modulus values is required. Piers grouped less than 3 diameters center to center should be studied on an individual basis to determine the appropriate reduction in both lateral and axial capacity.

- (5) A minimum pier diameter of 24 inches is recommended to facilitate proper cleaning and observation of the pier hole.
- (6) Concrete utilized in the piers should be a fluid mix with sufficient slump so that concrete will fill the void between reinforcing steel and the pier hole.
- (7) Rock penetration in all pier holes should be roughened artificially to assist the development of peripheral shear between the pier and the bedrock. The roughening should be installed with a grooving tool in a pattern approved by the soil engineer.

The specifications should allow the soil engineer to eliminate the requirements for pier roughening if it appears the roughening procedure is not beneficial. This could occur if the pier hole is sufficiently roughened by the drilling process or if the presence of water results in a degradation of the pier hole during the roughening procedure.

- (8) Based on the results of our field exploration, laboratory testing and experience with similiar, properly constructed caisson foundations, we estimate that pier settlement will be low. Generally, we estimate that settlement for a 24 to 36 inch diameter pier will be approximately  $3/4$  to 1 inch when designed with the criteria presented herein. The settlement of closely

spaced piers will be larger and should be studied on an individual basis.

- (9) Pier holes should be properly cleaned prior to the placement of concrete.
- (10) The presence of water and the nature of overburden strata encountered at the site indicates that the use of casing will be required to reduce water infiltration into the pier holes. If water cannot be removed prior to placement of concrete, the tremie method should be used after the hole has been well cleaned. In no case should concrete be placed in more than 3 inches of water.
- (11) Gravel and cobbles were encountered during drilling of our test holes. These conditions will complicate the drilling process and may reduce the effectiveness or prevent seating of the casing in the upper bedrock surface. The drilling contractor should be made aware of this information and should be prepared for these conditions during the pier installation.
- (12) Adequate construction equipment should be used to drill the piers to the required penetration and seat the casing into the bedrock materials. If shallow refusal is encountered in the bedrock our office should be notified to evaluate the conditions and establish that true refusal has been met with adequate equipment.
- (13) A representative of the soil engineer should observe the pier drilling operations.

## FOUNDATION ALTERNATES

Based on the subsurface conditions encountered, the proposed bridge may be supported on high-capacity driven piles or spread footings.

Driven Pile Alternate: The following design and construction details should be closely followed for a driven pile foundation system.

- (1) The maximum allowable pile capacity should not exceed a service stress of 12,000 psi.
- (2) The pile type should consist of heavy steel H-pile with tip reinforcement.
- (3) The piles should penetrate a minimum of 3 feet into unweathered bedrock.
- (4) The piles should be designed to resist lateral loads using a modulus of subgrade reaction of 40 tcf, a constant of horizontal subgrade reaction in the clay of 60 tcf and a modulus of horizontal subgrade reaction of 200 tcf in the bedrock.  
Resistance to lateral loads should be neglected in the trash fill material and all material above the estimated scour depths.
- (5) All piers should be advanced to virtual refusal. Virtual refusal is defined as 20 blows per inch with an approved pile hammer.
- (6) The rated energy output of the hammer should be between 1800 and 2,000 foot-pounds per square inch of pile cross-sectional area.
- (7) The hammer should be operating at the manufacturers recommended stroke when virtual refusal is measured.
- (8) Due to the dense to very dense sand and gravel strata at the site, difficult driving conditions should be anticipated. These

conditions could adversely affect the structural integrity of the piles and also result in variable penetration into subsurface materials. Consequently, predrilling may be required to advance piles through the sand and gravel overburden materials.

- (9) A representative of the soil engineer should observe the pile driving operations.

Spread Footing Alternate: The structure may be founded on spread footings placed on the dense to very dense sand and gravel strata. The following design and construction details should be observed for spread footing foundation system.

- (1) Footings placed on undisturbed sand and gravel strata may be designed for a maximum allowable soil bearing pressure of 6,000 psf.
- (2) Spread footings placed on granular soils should have a minimum footing dimension of not less than 36 inches.
- (3) Footings should be provided with adequate scour protection above their bearing elevation.
- (4) The lateral resistance of spread footing foundations placed on the undisturbed sand and gravel strata at the site will be a combination of the passive earth pressure against the side of the footing and the sliding resistance of the footing on the foundation materials. Sliding friction at the bottom of the footings can be taken as 0.4 times the vertical dead load. Passive pressure against the sides of the footings can be

calculated using an equivalent fluid pressure of 200 psf per foot of depth.

- (5) Based on experience, we estimate that total settlement for footings designed and constructed as discussed in this section will be approximately 3/4 inch.
- (6) The proposed footing elevations appear to be near or slightly above ground water level. Therefore, it may be necessary to dewater some footing excavations during construction. Dewatering should not be conducted by pumping from inside the footing excavations. This may decrease the supporting capacity of the soils.
- (7) A representative of the soil engineer should observe all footing excavations prior to concrete placement in order to evaluate the supporting capacity of foundation materials.


#### ABUTMENT AND WINGWALL BACKFILL

Backfill within 6 feet of the abutments and wingwalls should be Class 1 structural backfill in accordance with Colorado Standard Specifications for Road and Bridge Construction and should be compacted to a density of not less than 95% as determined in accordance with ASTM D698. Design lateral loads on wingwalls and abutments should be based on equivalent fluid pressure of 40 psf per foot.

#### LIMITATIONS

This report has been prepared in accordance with generally accepted soil and foundation engineering practices in this area for

use by the client for design purposes. The conclusions and recommendations submitted in this report are based upon the data obtained from the exploratory holes drilled at the locations indicated on the exploratory hole plan. The nature and extent of variations between the exploratory holes may not become evident until excavation is performed. If during construction, soil, rock and ground water conditions appear to be different from those described herein, this office should be advised at once so that re-evaluation of the recommendations may be made. We recommend on-site observation of excavations and foundation bearing strata by a soil engineer.



RJS:fs

CHEN AND ASSOCIATES, INC.

By Richard J. Suedkamp  
Richard J. Suedkamp, P.E.

Reviewed By David M. Jubenville  
David M. Jubenville, P.E.

## CONCLUSIONS

- (1) The proposed structure should be founded on piers drilled into bedrock and designed for maximum end bearing pressure of 40,000 psf, a skin friction of 4,000 psf and a minimum dead load pressure of 15,000 psf, with design and construction details as outlined.
- (2) Alternate foundation systems consisting of steel H-piles and designed for a maximum stress of 12,000 psi with tip reinforcement or spread footings placed on the lower sand and gravel strata and designed for a maximum bearing pressure of 6,000 psf may be used.
- (3) Trash fill varying in depth from 8 to 16 feet was encountered across the site south of Ralston Creek. This landfill material is generating sufficient quantities of combustible methane gas to be hazardous.



Fill, man-made, sandy clay.



Trash fill, man-made, clay, metal, plastic, wood, paper organic materials.



Organic silt, slightly sandy, slightly clayey, stiff, moist to v moist, black.



Clay (CL), sandy, medium to stiff, moist to very moist, red to brown, occasionally gravel.



Gravel, silty to sandy, poorly graded, medium dense to very dens wet, brown, scattered cobbles.



Weathered Claystone, sandy, firm to medium hard, moist, rust to



Claystone, sandy, very hard, moist, gray.



Undisturbed drive sample. The symbol 15/12 indicates that 15 blc a 140 pound hammer falling 30 inches were required to drive the 12 inches.



Standard Split Spoon Sample.




Indicates P.V.C. pipe installed to depth shown.




Indicates depth to free water.



Depth at which hole caved.



LOCATION OF EXPLORATORY H  
Fig. 1



LOGS OF EXPLORATORY HOLES  
 FIG. 2

■ Fill, man-made, sandy clay.

☒ Trash fill, man-made, clay, metal, plastic, wood, paper organic materials.

■ Organic silt, slightly sandy, slightly clayey, stiff, moist to very moist, black.

☐ Clay (CL), sandy, medium to stiff, moist to very moist, red to brown, occasionally gravel.

■ Gravel, silty to sandy, poorly graded, medium dense to very dense, wet, brown, scattered cobbles.

☐ Weathered Claystone, sandy, firm to medium hard, moist, rust to brown.

■ Claystone, sandy, very hard, moist, gray.

☐ Undisturbed drive sample. The symbol 15/12 indicates that 15 blows of a 140 pound hammer falling 30 inches were required to drive the sampler 12 inches.

■ Standard Split Spoon Sample.

■ Indicates P.V.C. pipe installed to depth shown.



4 Indicates depth to free water.

→ Depth at which hole caved.

#### NOTES:

1. Test holes were drilled on January 11 and 18, 1982 with a 6-inch diameter continuous flight hollow stem and 4-inch diameter continuous flight power auger.
2. Location of test holes are approximate and were determined by pacing from existing Croke Channel.
3. Elevations of test hole were determined by interpolation between contours on the plan provided.
4. The locations and elevations of test holes should be considered accurate only to the degree implied by the method used.
5. The stratification lines shown on the test hole logs represent the approximate boundary between soil types and the transition may be gradual.
6. Water level readings have been made in the drill holes at times and under conditions stated on the boring logs. These data have been reviewed and interpretations made in the text of this report. However, it must be noted that fluctuations in the level of the groundwater may occur due to variations in rain fall, temperature, and other factors at the time measurements were made.
7. WC = Water Content (%);  
DD = Dry Density (pcf);  
-200 = Percent Passing No. 200 Sieve;  
LL = Liquid Limit (%);  
PI = Plasticity Index (%);  
NP = Non Plastic;  
UC = Unconfined Compressive Strength (psf).

## chen and associates, inc.



**CHEN AND ASSOCIATES**

## TABLE I



## SUMMARY OF LABORATORY TEST RESULTS

Job No. 23,548

Page 1 of 1

[illegible]

**chen and associates, inc.**



## APPENDIX I

### FIELD GC (GAS CHROMATOGRAPH) DATA



ERCE

Stanford Place 3, Suite 415  
4582 South Ulster St Pkwy  
Denver, CO 80237  
Attention: Mr. Dave Runyon

Mr. Runyon:

Here are the analytical results for the project done on site at 69th and Indiana in Arvada, Colorado. There were 6 water samples collected, and subsamples were taken from all of these and analyzed.

The instrumentation was calibrated for the SW-846 Method 8020 suite of analytes and unleaded gasoline by Method 8015. Of these, the benzene, toluene, ethylbenzene, and xylene subset (BTEX), and the total volatile hydrocarbons (TVH) are reported.

The PQL for the BTEX analytes is 5 ug/L and for the total volatile hydrocarbons it is 2 mg/L.

The sample analysis for boring #8 was lost due to generator failure. Notation in the analysis log book showed sample run (BH08 WS01) to be clean.

If there are any questions concerning the data or the analysis, please feel free to call.

Cordially,

A handwritten signature in cursive script that reads "Adam P. Macdonald".

Adam P. Macdonald  
Geochemist  
GEO Environmental  
(303) 279-4655

Client: ERCE  
Chromatographer: Adam P. Macdonald  
Analysis Date: December 26, 1991  
Analysis: SW-846 Method 8015/8020  
Location: 69th & Indiana Arvada, CO  
Sample Number: BH01 WS01

| Analyte                     | Concentration |
|-----------------------------|---------------|
| Benzene                     | <5 ug/L       |
| Toluene                     | <5 ug/L       |
| Ethylbenzene                | <5 ug/L       |
| Total Xylenes               | <5 ug/L       |
| Total Volatile Hydrocarbons | <2 mg/L       |

Client: ERCE  
Chromatographer: Adam P. Macdonald  
Analysis Date: December 26, 1991  
Analysis: SW-846 Method 8015/8020  
Location: 69th & Indiana Arvada, CO  
Sample Number: BH02 WS01

| Analyte                     | Concentration |
|-----------------------------|---------------|
| Benzene                     | <5 ug/L       |
| Toluene                     | <5 ug/L       |
| Ethylbenzene                | <5 ug/L       |
| Total Xylenes               | <5 ug/L       |
| Total Volatile Hydrocarbons | <2 mg/L       |

Client: ERCE  
Chromatographer: Adam P. Macdonald  
Analysis Date: December 26, 1991  
Analysis: SW-846 Method 8015/8020  
Location: 69th & Indiana Arvada, CO  
Sample Number: BH03 WS01

| Analyte                     | Concentration |
|-----------------------------|---------------|
| Benzene                     | <5 ug/L       |
| Toluene                     | <5 ug/L       |
| Ethylbenzene                | <5 ug/L       |
| Total Xylenes               | <5 ug/L       |
| Total Volatile Hydrocarbons | <2 mg/L       |



Analytical**Technologies, Inc.** 225 Commerce Drive Fort Collins, Colorado 80524 (303) 490-1511

January 3, 1992

Mr. Dave Runyon  
ERCE  
Stanford Place 3, Suite 415  
4582 South Ulster Street Parkway  
Denver, CO 80237

RE: ATI Workorder: 91-12-195  
Client Project Name: Cottonwood ESA

Dear Mr. Runyon:

One water sample was received from ERCE on December 27, 1991. The sample was scheduled for Total Extractable Petroleum Hydrocarbons analysis. Results for this analysis are contained in the following report.

Thank you for your confidence in Analytical Technologies, Inc. Should you have any questions, please call.

Sincerely yours,

*Steven Fry*

Steven Fry, Ph.D.  
Project Manager

SF/jw

Enclosures



Analytical Technologies, Inc.

**QUALITY ASSURANCE  
DATA REVIEW**

The data contained in the following report has been reviewed and approved by the appropriate supervisory personnel listed below:

Eddy Hammerquist  
Eddy Hammerquist, Fuels Supervisor

**CERTIFICATION**

Analytical Technologies, Inc. certifies that the analyses reported herein are true, complete and correct within the limits of the method employed.

**TOTAL EXTRACTABLE PETROLEUM HYDROCARBONS**  
**Modified Method 8015**

Lab Name: Analytical Technologies, Inc.

Date Collected: 12/27/91

Client Name: ERCE

Date Extracted: 12/31/91

Client Project ID: Cottonwood ESA

Date Analyzed: 12/31/91

ATI Workorder Number: 91-12-195

Sample Matrix: Water

| Client Sample ID  | Lab Sample ID | Dilution Factor | Conc. TEPH (mg/L) |
|-------------------|---------------|-----------------|-------------------|
| Reagent Blank 006 | 91-12-195-RB  | 1               | < 1               |
|                   | 91-12-195-01  | 1               | 2                 |

Note: Sample 006 contains high molecular weight components which could not be quantified by TPH-D analytical conditions.

**TOTAL EXTRACTABLE PETROLEUM HYDROCARBONS  
MATRIX SPIKE RESULTS  
Modified Method 8015**

Lab Name: Analytical Technologies, Inc.

Client Sample ID:

008

Client Name: ERCE

Lab Sample ID: 91-12-195-01

Date Analyzed: 12/31/91

Sample Matrix: Water

GC Column: DB-5

| Compound | Spike Added (mg/L) | Sample Concentration (mg/L) | MS Concentration (mg/L) | MS Percent Recovery |
|----------|--------------------|-----------------------------|-------------------------|---------------------|
| TEPH     | 10                 | 2                           | 10                      | 80                  |

| Compound | Spike Added (mg/L) | MSD Concentration (mg/L) | MSD Percent Recovery | Matrix Spike RPD |
|----------|--------------------|--------------------------|----------------------|------------------|
| TEPH     | 10                 | 9.8                      | 78                   | 2                |



## **APPENDIX G**

### **DATA VALIDATION SUMMARY OF LABORATORY RESULTS**

Date: 01\15\92  
Client: D. Runyon (Ogden)  
Reviewer: T. Perrin

### Data Validation Summary

#### Samples and Analyses

| Client Sample ID | Lab Sample ID | Analysis   | Matrix |
|------------------|---------------|------------|--------|
| 001              | 91-12-190-01  | Volatiles  | SOIL   |
| 004              | 91-12-190-03  | Volatiles  | WATER  |
| 002              | 91-12-190-02A | PCBs       | SOIL   |
| 002              | 91-12-190-02  | Total Lead | SOIL   |
| 005              | 91-12-190-04  | Total Lead | WATER  |

#### Volatile Organics:

1.

##### Overall Assessment:

Only result summaries were provided so compound identification could not be confirmed from raw instrument results nor could the calculations be verified. No data for instrument tuning or calibration was provided. Data is acceptable with qualifications as noted below.

2.

##### Holding times:

Per W. Glasgow the sample for volatile water analysis was not preserved with acid. The holding time for volatile analysis of an unpreserved water sample is 7 days. The sample was analyzed at 14 days after collection, therefore analytes were qualified "UJ" in sample 004. Since there are no guidelines for soils the soil sample was not qualified.

3. Surrogate Recoveries:  
Surrogate compounds were added to the samples as a measure of purging efficiency. Surrogate recoveries were acceptable for both reagent blanks and sample 004. Recovery for surrogate toluene-d8 was low and bromofluorobenzene high for soil sample 001. All detects were qualified as estimated "J" and all quantitation limits as estimated "UJ" in sample 001 for this QC exceedance. In the case narrative the lab attributed the non-compliant surrogate recoveries to a matrix effect because on reanalysis the surrogate performance did not improve.
4. Reagent Blank:  
A reagent blank was analyzed to evaluate possible laboratory-introduced contamination. No target analytes were reported in the reagent blanks. A TIC result page was not provided for the reagent blanks. Whether this is an omission by the lab or whether no TICs were detected in the reagent blanks is unknown. One tentatively identified compound (TIC) was reported in each sample. Trichlorofluoromethane (freon) is a common laboratory contaminant and therefore may not be a true sample constituent in analysis 001.
5. Matrix Spike/Matrix Spike Duplicate:  
An associated matrix spike/matrix spike duplicate was performed on a water sample although not on the Ogden water sample. % Recoveries and RPDs were acceptable.  
PCBs:
  1. Overall Assessment:  
No PCBs were reported in the sample. Only result summaries were provided so compound identification could not be confirmed from raw instrument results nor could the calculations be verified. No qualification of data was required.
  2. Holding times:  
Holding times were acceptable.
  3. Surrogate Recoveries:  
A surrogate compound was added to the sample before extraction as a measure of the extraction efficiency. The surrogate recoveries at 86 and 98% are considered acceptable for the reagent blank and sample 002 respectively.

4. Reagent Blank:  
A reagent blank was analyzed to evaluate possible laboratory-introduced contamination. No target analytes were reported in the method blank.
5. Matrix Spike/Matrix Spike Duplicate:  
A matrix spike/matrix spike duplicate was performed on a soil sample although not on the Ogden soil sample. The MS/MSD was analyzed 11 days before sample 002 was extracted so is not really indicative of extraction conditions for sample 002. % Recoveries and RPDs were acceptable. No qualifications were required.

Total Lead:

1. Overall Assessment:  
Raw data was not provided for review; therefore, sample results and QC data were reviewed based on information presented in the respective summary forms. Sample results were acceptable without qualifications.
2. Holding Times:  
The soil and water sample were analyzed within the water holding time of six months. The water sample was preserved with  $\text{HNO}_3$ .
3. Blanks:  
Blank data presented on the Total Lead analysis data sheet was acceptable.
4. Matrix Spike:  
An acceptable Matrix Spike percent recovery (%R) of 108% and 100% were recorded on the Total Lead Matrix Spike sheet for the soil and water samples respectively.

## Method 8240

Client Sample ID:

001



Lab Name: Analytical Technologies Inc.

Lab Sample ID: 91-12-190-01

Client Name: ERCE

Date Collected: 12/26/91

Client Project ID: Cottonwood ESA

Date Analyzed: 01/09/92

Sample Matrix: Soil

Dilution Factor: 1

| COMPOUND NAME              | Concentration (ug/kg) | Res Qual     | Qual Code | Val Code |
|----------------------------|-----------------------|--------------|-----------|----------|
| Chloromethane              | < 10                  | UT           | S         | VV       |
| Bromomethane               | < 10                  |              |           |          |
| Vinyl chloride             | < 10                  |              |           |          |
| Chloroethane               | < 10                  |              |           |          |
| Methylene chloride         | 120                   |              |           |          |
| Acetone                    | 68                    |              |           |          |
| Carbon disulfide           | < 5                   |              |           |          |
| 1,1-Dichloroethene         | 2 J                   |              |           |          |
| 1,1-Dichloroethane         | < 5                   |              |           |          |
| 1,2-Dichloroethene (Total) | 4 J                   |              |           |          |
| Chloroform                 | 3 J                   |              |           |          |
| 1,2-Dichloroethane         | < 5                   |              |           |          |
| 2-Butanone                 | < 10                  |              |           |          |
| 1,1,1-Trichloroethane      | 12                    |              |           |          |
| Carbon tetrachloride       | < 5                   |              |           |          |
| Vinyl Acetate              | < 10                  |              |           |          |
| Bromodichloromethane       | < 5                   |              |           |          |
| 1,2-Dichloropropane        | < 5                   |              |           |          |
| cis-1,3-Dichloropropene    | < 5                   |              |           |          |
| Trichloroethene            | 4 J                   |              |           |          |
| Dibromochloromethane       | < 5                   |              |           |          |
| 1,1,2-Trichloroethane      | < 5                   |              |           |          |
| Benzene                    | 4 J                   |              |           |          |
| trans-1,3-Dichloropropene  | < 5                   |              |           |          |
| Bromoform                  | < 5                   |              |           |          |
| 2-Hexanone                 | < 10                  |              |           |          |
| 4-Methyl-2-pentanone       | < 10                  |              |           |          |
| Tetrachloroethene          | 23                    |              |           |          |
| 1,1,2,2-Tetrachloroethane  | < 5                   |              |           |          |
| Toluene                    | 24                    |              |           |          |
| Chlorobenzene              | 4 J                   |              |           |          |
| Ethylbenzene               | 7                     |              |           |          |
| Styrene                    | < 5                   |              |           |          |
| Total Xylenes              | 43                    |              |           |          |
| Surrogate Recoveries:      | % Rec                 | % Rec Limits |           |          |
| 1,2-Dichloroethane-d4      | 93                    | 70-121       |           |          |
| Toluene-d8                 | 72 *                  | 81-117       |           |          |
| Bromofluorobenzene         | 122 *                 | 74-121       |           |          |

\* Outside control limits.

J = compound detected below practical quantitation limit.

OGDEN VALIDATED

VOLATILE ORGANICS DATA SHEET  
Tentatively Identified Compounds

Client Sample ID:



001

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Date Analyzed: 01/09/92

Client Project ID: Cottonwood ESA

Dilution Factor: 1

Lab Sample ID: 91-12-190-01

Matrix: Soil

Concentration units: ug/kg

| COMPOUND NAME          | RT | Concentration | Q |
|------------------------|----|---------------|---|
| Trichlorofluoromethane |    | 120 J         |   |

|      |      |      |
|------|------|------|
| Rev  | Qual | Val  |
| Qual | Code | Code |
| NJ   |      | W    |

J = estimated value

**OGDEN VALIDATED**

## VOLATILE ORGANICS DATA SHEET

## Method 8240

Client Sample ID:

004



Lab Name: Analytical Technologies Inc.

Lab Sample ID: 91-12-190-03

Client Name: ERCE

Date Collected: 12/26/91

Client Project ID: Cottonwood ESA

Date Analyzed: 01/09/92

Sample Matrix: Water

Dilution Factor: 1

| COMPOUND NAME              | Concentration (ug/L) | Raw<br>Qual  | Qual<br>Code | Val<br>Code |
|----------------------------|----------------------|--------------|--------------|-------------|
| Chloromethane              | < 10                 | UJ           | H            | VV          |
| Bromomethane               | < 10                 |              |              |             |
| Vinyl chloride             | < 10                 |              |              |             |
| Chloroethane               | < 10                 |              |              |             |
| Methylene chloride         | < 5                  |              |              |             |
| Acetone                    | < 10                 |              |              |             |
| Carbon disulfide           | < 5                  |              |              |             |
| 1,1-Dichloroethene         | < 5                  |              |              |             |
| 1,1-Dichloroethane         | < 5                  |              |              |             |
| 1,2-Dichloroethene (Total) | < 5                  |              |              |             |
| Chloroform                 | < 5                  |              |              |             |
| 1,2-Dichloroethane         | < 5                  |              |              |             |
| 2-Butanone                 | < 10                 |              |              |             |
| 1,1,1-Trichloroethane      | < 5                  |              |              |             |
| Carbon tetrachloride       | < 5                  |              |              |             |
| Vinyl Acetate              | < 10                 |              |              |             |
| Bromodichloromethane       | < 5                  |              |              |             |
| 1,2-Dichloropropane        | < 5                  |              |              |             |
| cis-1,3-Dichloropropene    | < 5                  |              |              |             |
| Trichloroethene            | < 5                  |              |              |             |
| Dibromochloromethane       | < 5                  |              |              |             |
| 1,1,2-Trichloroethane      | < 5                  |              |              |             |
| Benzene                    | < 5                  |              |              |             |
| trans-1,3-Dichloropropene  | < 5                  |              |              |             |
| Bromoform                  | < 5                  |              |              |             |
| 2-Hexanone                 | < 10                 |              |              |             |
| 4-Methyl-2-pentanone       | < 10                 |              |              |             |
| Tetrachloroethene          | < 5                  |              |              |             |
| 1,1,2,2-Tetrachloroethane  | < 5                  |              |              |             |
| Toluene                    | < 5                  |              |              |             |
| Chlorobenzene              | < 5                  |              |              |             |
| Ethylbenzene               | < 5                  |              |              |             |
| Styrene                    | < 5                  |              |              |             |
| Total Xylenes              | < 5                  |              |              |             |
| Surrogate Recoveries:      | % Rec                | % Rec Limits |              |             |
| 1,2-Dichloroethane-d4      | 87                   | 76-116       |              |             |
| Toluene-d8                 | 102                  | 88-110       |              |             |
| Bromofluorobenzene         | 101                  | 86-115       |              |             |

OGDEN VALIDATED

## Tentatively Identified Compounds

Client Sample ID

004

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Date Analyzed: 01/09/92

Client Project ID: Cottonwood ESA

Dilution Factor: 1 1

Lab Sample ID: 91-12-190-03

Matrix: Water

Concentration units: ng/L

| COMPOUND NAME        | RT | Concentration | Q |
|----------------------|----|---------------|---|
| Methyl-t-butyl ether |    | 10 J          |   |

|      |      |      |
|------|------|------|
| Rev  | Qual | Val  |
| Qual | Code | Code |
| NJ   |      | VV   |

J = estimated value

**OGDEN VALIDATED**

**PCB ANALYSIS DATA SHEET**  
Method 8080

Lab Name: Analytical Technologies Inc.

Client Name: ERCE

Client Project ID: Cottonwood ESA

Lab Sample ID: 91-12-190-02A

Sample Matrix: Soil

Sample Weight: 30 g

GPC Cleanup: N

Client Sample ID:

002

Date Collected: 12/26/91

Date Extracted: 12/30/91

Date Analyzed: 01/03/92

Extract Volume: 10 mL

Dilution Factor: 1

| Compound | Conc (mg/kg) | Rev<br>Qual | Qual<br>Code | Vol<br>Code |
|----------|--------------|-------------|--------------|-------------|
| PCB 1016 | < 0.03       | U           |              | VV          |
| PCB 1221 | < 0.03       |             |              |             |
| PCB 1232 | < 0.03       |             |              |             |
| PCB 1242 | < 0.03       |             |              |             |
| PCB 1248 | < 0.03       |             |              |             |
| PCB 1254 | < 0.03       |             |              |             |
| PCB 1260 | < 0.03       |             |              |             |

**SURROGATE RECOVERY**

| Compound             | % Recovery |
|----------------------|------------|
| Tetrachloro-m-xylene | 98         |

**OGDEN VALIDATED**

**TOTAL LEAD ANALYSIS DATA SHEET**

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Prep Date: 01/02/92

Client Project ID: Cottonwood ESA

Date Analyzed: 01/02/92

Workorder Number: 91-12-190

Sample Matrix: Water

| Client ID.    | ATI ID.      | Lead Conc.<br>(mg/L) |
|---------------|--------------|----------------------|
| Reagent Blank | 91-12-190-RB | < 0.003              |
| 005           | 91-12-190-04 | 0.065                |

|             |              |             |
|-------------|--------------|-------------|
| Res<br>Qual | Qual<br>Code | Val<br>Code |
|             |              | VV          |

**OGDEN VALIDATED**

**TOTAL LEAD ANALYSIS DATA SHEET**

Laboratory Name: Analytical Technologies, Inc.

Date Collected: 12/26/91

Client Name: ERCE

Prep Date: 01/02/92

Client Project ID: Cottonwood ESA

Date Analyzed: 01/03/92

Workorder Number: 91-12-190

Sample Matrix: Soil

| Client ID.    | ATI ID.      | Lead Conc.<br>(mg/kg) | Raw<br>Anal | Qual<br>Code | Val<br>Code |
|---------------|--------------|-----------------------|-------------|--------------|-------------|
| Reagent Blank | 91-12-190-RB | < 5                   |             |              |             |
| 002           | 91-12-190-02 | 56                    |             |              | VV          |

**OGDEN VALIDATED**

### Qualifier Codes for Organics

- |   |    |
|---|----|
| 1) Holding times were exceeded:   | H  |
| 2) Tuning (BFB or DFTPP) was non-compliant:   | M  |
| 3) Calibration:   |    |
| a) RRF was <0.05:   | R  |
| b) %RSD or %D was outside of QC limits:   | C  |
| 4) Blanks:  |    |
| a) Presumed contamination from method blank:  | B  |
| b) Presumed contamination from trip blank:  | T  |
| c) Presumed contamination from field blank:   | F  |
| 5) Surrogate recovery was outside of QC limits:   | S  |
| 6) MS/MSD recovery was poor or RPD high:  | Q  |
| 7) Field duplicates showed poor agreement:  | E  |
| 8) IS Performance was unsatisfactory:   | I  |
| 9) Compound ID:   |    |
| a) False positive (reported compound was not present):  | +  |
| b) False Negative (compound was present but not reported):  | -  |
| 10) Reported result or other information was incorrect:   | \$ |
| 11) TIC identity or reported retention time has been changed:   | ?  |
| 12) Original analyses, dilutions, reanalyses or duplicate data that should not be used because another more technically sound analysis is available:  | D  |
| 13) Instrument performance for pesticides was poor:   | P  |
| 14) Unusual problems with the data that have been described in the Data Summary in a specific section. For example, *11 indicates that an unusual problem has been described in section 11 of the Data Summary: | *# |

### Reviewer Codes

- U The material was analyzed for but was not detected. The associated numerical value is the sample quantitation limit.
- J The analyte was positively identified in the sample, but the associated numerical value may not be an accurate representation of the amount actually present in the environmental sample. Values are of limited use.
- R The data are unusable (presence or absence cannot be determined). Resampling and/or reanalysis is necessary for verification.
- N Presumptive evidence of the presence of the material.
- NJ Presumptive evidence of the presence of the material at an estimated quantity.
- UJ The material was analyzed for but was not detected. The sample quantitation limit is an estimated quantity.

Validation Codes

| Validation Code | Definition        | Usability  |
|-----------------|-------------------|--|
| VV              | Validated Valid   | Usable data  |
| VI              | Validated Invalid | Unusable for any purpose.                              |
| UN              | Unvalidated       | All data which has not been validated e.g. trip blanks |

## **APPENDIX H**

### **CHEN AND ASSOCIATES CONSULTING GEOTECHNICAL ENGINEERS**

**"Soil & Foundation Investigation Proposed Bridge Across Ralston  
Creek Cottonwood Subdivision"**




**chen and associates**  
CONSULTING GEOTECHNICAL ENGINEERS  
96 SOUTH ZUNI STREET • DENVER, COLORADO 80223 • 303/744-7105

SOIL & FOUNDATION INVESTIGATION  
PROPOSED BRIDGE ACROSS RALSTON CREEK  
COTTONWOOD SUBDIVISION  
JEFFERSON COUNTY, COLORADO

Prepared for:

KKENA  
7456 W. 5th Avenue  
Denver CO 80226

Attn: Mr. Gary Thomas



Job No. 23,548

January 27, 1982

## TABLE OF CONTENTS

|  |    |
|--|----|
| CONCLUSIONS                                  | 1  |
| PURPOSE AND SCOPE OF STUDY                   | 2  |
| PROPOSED CONSTRUCTION                        | 2  |
| SITE CONDITIONS                              | 2  |
| SUBSURFACE CONDITIONS                        | 3  |
| EXISTING LANDFILL                            | 4  |
| FOUNDATION RECOMMENDATIONS                   | 6  |
| FOUNDATION ALTERNATES                        | 9  |
| ABUTMENT AND WINGWALL BACKFILL               | 11 |
| LIMITATIONS                                  | 11 |
| FIG. 1 - LOCATION OF EXPLORATORY HOLES       |    |
| FIG. 2 - LOGS OF EXPLORATORY HOLES           |    |
| FIG. 3 - LEGEND & NOTES                      |    |
| FIG. 4 - SWELL-CONSOLIDATION TEST RESULTS    |    |
| FIG. 5 - GRADATION TEST RESULTS              |    |
| TABLE I - SUMMARY OF LABORATORY TEST RESULTS |    |

#### PURPOSE AND SCOPE OF STUDY

This report presents the results of a soil and foundation investigation for a bridge across Ralston Creek in Cottonwood Subdivision, Jefferson County, Colorado. The project site is shown on Fig. 1.

This report has been prepared to summarize the data obtained and to present our conclusions and recommendations based on the conditions encountered. Design parameters and a discussion of geotechnical engineering considerations related to construction of the proposed facility are included.

#### PROPOSED CONSTRUCTION

An 80 foot long single-span structure is proposed for the site. The structure will be approximately 44 feet wide and include two 15 foot lanes and two 5 foot sidewalks with parapets. The type of construction had not been finalized at the time of our investigation. For purposes of this report, the foundation loads were assumed to range between 100 and 300 kips per abutment.

If loadings or conditions are significantly different from those described above, we should be notified to re-evaluate the recommendations contained in this report.

#### SITE CONDITIONS

The bridge site is located in the Cottonwood Subdivision on Kilmer Street. The structure will provide access across Ralston Creek. At the time of our investigation, the creek was approximately 4 feet wide

with flowing water about 6 inches deep. The north bank is nearly vertical with an overall depth of approximately 12 feet. The south bank is on a 1:1 slope with an intermediate bench.

The site was vacant at the time of our investigation. The vegetation consists of native grasses, weeds and deciduous trees along Ralston Creek.

Croke Canal is approximately 300 feet west of the proposed ditch site and runs perpendicular to Ralston Creek. The flow in the canal is approximately 15 feet wide with the water level at approximately elevation 60. A gate controls the flow from the canal into the creek. At the time of our investigation, the gate was closed. It appears that water seeps from the canal into the creek.

#### SUBSURFACE CONDITIONS

To evaluate the subsurface conditions at the bridge site, 3 test holes were drilled at the approximate locations shown on Fig. 1. Six additional test holes were drilled in the subdivision south of Ralston Creek to determine the extent and depth of trash fill.

In general, the subsoils at the site were highly variable. They consisted of 20 to 25 feet of trash fill, organic silt, clay, sand and gravel overlying bedrock. Trash fill varied in depth from 8 to 16 feet across the entire area south of Ralston Creek. This is an old landfill which consists of approximately 3 feet of sandy clay overlying various metal, plastic, wood, paper, glass and organic material. The exact lateral and vertical extent of the fill was not determined as a result of this investigation.

A 2.5 to 3 foot layer of organic silt was encountered in Test Holes 1, 7 and 9 below the trash fill. The clay is sandy and medium stiff and the sand is clayey and medium dense. The gravel and sand layer varied in thickness from 7 to 13 feet. This material is poorly graded and dense to very dense with scattered cobbles.

Claystone bedrock underlies the overburden soils. The claystone consists of a 1.5 to 2.5 foot weathered mantel overlying sandy and hard to very hard claystone. Field penetration tests and unconfined compression tests indicate that the bedrock is capable of supporting moderate foundation loads without undergoing significant settlements. Results of laboratory tests are shown on Figs 4 and 5 and summarized on Table I.

Free water was encountered at depths of 10.5 to 14 feet below the ground surface at the time of drilling and when measured 4 to 8 days after drilling, see Figs. 2 and 3. } Ground w. intersect landfill

#### EXISTING LANDFILL


Landfill debris consisting of mixtures of wood, paper, glass, plastic and metal was encountered in all of the test holes drilled south of Ralston Creek. This area and two areas to the south have been identified by the Jefferson County Health Department as known landfills. The approximate locations of these fills, results of bar hole punch gas surveys and landfill histories, are presented in a report prepared by the department.<sup>1</sup>

---

1. Jefferson County Health Department, Methane Site Investigation, 1980.

Combustible gas measurements were taken during our investigation to determine if combustible gases were present in the landfill. The measurements were obtained with an MSA Model 53 gas scope. This instrument allows the measurement of the percent by volume of combustible gas in air and the percent lower explosive limit (LEL). The measurements obtained indicated 85% to 100% of the LEL and 3% to 28% combustible gases. The readings are summarized below:

| <u>Hole No.</u> | <u>% LEL</u> | <u>% Gas</u> |
|-----------------|--------------|--------------|
| 4               | 100          | 10           |
| 5               | 85           | 3            |
| 6               | 100          | 28           |
| 9               | 100          | 13           |

Based on these readings, it appears that combustible gas is being generated within this landfill in quantities sufficient to be considered a hazard. The combustible range of methane gas is between 5% and 15% by volume in air. Concentrations above this range are too rich to burn. However, gas migration or exposure to the atmosphere will result in dilution of the gas and result in a flammable condition.

*both for  
excavation  
and  
digging*

Care should be taken when excavating within or adjacent to the landfill mass. Venting of excavations will be required. Any structures built over the landfill will require special methane gas controls. There are 2 basic approaches to controlling the migration of methane into structures. These include barriers separating the proposed structure from the landfill and ventilation systems. Access roads, parking areas, underground utilities and other facilities constructed on landfill materials will be subjected to large differential movements and a corrosive environment. The owner should

be aware of the high risk of distress associated with construction on landfills.

#### FOUNDATION RECOMMENDATIONS

Based on the subsurface conditions encountered at the site and the proposed construction, we recommend that the bridge be supported on drilled piers founded in the underlying unweathered bedrock. The following design and construction details should be observed for a drilled pier foundation system:

- (1) Piers should be designed for a maximum end bearing pressure of 40,000 psf and a skin friction of 4,000 psf for the portion of the pier in unweathered bedrock. Piers should be designed for a minimum dead load pressure of 15,000 psf based on end area only. Uplift on the piers can be resisted by utilizing 50% of the skin friction value plus the weight of the pier.
- (2) Piers should penetrate at least three pier diameters into the competent bedrock. A minimum penetration of 5 feet into the bedrock is recommended.
- (3) Piers should be designed to resist lateral loads assuming a modulus of horizontal subgrade reaction in the clay of 40 tcf, a constant of horizontal subgrade reaction in the granular soils of 60 tcf and a modulus of horizontal subgrade reaction of 200 tcf in the bedrock. Resistance to lateral loads should be neglected in the trash fill and all materials above estimated scour depth.
- (4) The minimum spacing requirements between caissons on the site should be 3 diameters from center to center. At this spacing, no

reduction in axial or horizontal soil modulus values is required. Piers grouped less than 3 diameters center to center should be studied on an individual basis to determine the appropriate reduction in both lateral and axial capacity.

- (5) A minimum pier diameter of 24 inches is recommended to facilitate proper cleaning and observation of the pier hole.
- (6) Concrete utilized in the piers should be a fluid mix with sufficient slump so that concrete will fill the void between reinforcing steel and the pier hole.
- (7) Rock penetration in all pier holes should be roughened artificially to assist the development of peripheral shear between the pier and the bedrock. The roughening should be installed with a grooving tool in a pattern approved by the soil engineer.

The specifications should allow the soil engineer to eliminate the requirements for pier roughening if it appears the roughening procedure is not beneficial. This could occur if the pier hole is sufficiently roughened by the drilling process or if the presence of water results in a degradation of the pier hole during the roughening procedure.

- (8) Based on the results of our field exploration, laboratory testing and experience with similiar, properly constructed caisson foundations, we estimate that pier settlement will be low. Generally, we estimate that settlement for a 24 to 36 inch diameter pier will be approximately 3/4 to 1 inch when designed with the criteria presented herein. The settlement of closely

spaced piers will be larger and should be studied on an individual basis.

- (9) Pier holes should be properly cleaned prior to the placement of concrete.
- (10) The presence of water and the nature of overburden strata encountered at the site indicates that the use of casing will be required to reduce water infiltration into the pier holes. If water cannot be removed prior to placement of concrete, the tremie method should be used after the hole has been well cleaned. In no case should concrete be placed in more than 3 inches of water.
- (11) Gravel and cobbles were encountered during drilling of our test holes. These conditions will complicate the drilling process and may reduce the effectiveness or prevent seating of the casing in the upper bedrock surface. The drilling contractor should be made aware of this information and should be prepared for these conditions during the pier installation.
- (12) Adequate construction equipment should be used to drill the piers to the required penetration and seat the casing into the bedrock materials. If shallow refusal is encountered in the bedrock our office should be notified to evaluate the conditions and establish that true refusal has been met with adequate equipment.
- (13) A representative of the soil engineer should observe the pier drilling operations.

## FOUNDATION ALTERNATES

Based on the subsurface conditions encountered, the proposed bridge may be supported on high-capacity driven piles or spread footings.

Driven Pile Alternate: The following design and construction details should be closely followed for a driven pile foundation system.

- (1) The maximum allowable pile capacity should not exceed a service stress of 12,000 psi.
- (2) The pile type should consist of heavy steel H-pile with tip reinforcement.
- (3) The piles should penetrate a minimum of 3 feet into unweathered bedrock.
- (4) The piles should be designed to resist lateral loads using a modulus of subgrade reaction of 40 tcf, a constant of horizontal subgrade reaction in the clay of 60 tcf and a modulus of horizontal subgrade reaction of 200 tcf in the bedrock.  
Resistance to lateral loads should be neglected in the trash fill material and all material above the estimated scour depths.
- (5) All piers should be advanced to virtual refusal. Virtual refusal is defined as 20 blows per inch with an approved pile hammer.
- (6) The rated energy output of the hammer should be between 1800 and 2,000 foot-pounds per square inch of pile cross-sectional area.
- (7) The hammer should be operating at the manufacturers recommended stroke when virtual refusal is measured.
- (8) Due to the dense to very dense sand and gravel strata at the site, difficult driving conditions should be anticipated. These

conditions could adversely affect the structural integrity of the piles and also result in variable penetration into subsurface materials. Consequently, predrilling may be required to advance piles through the sand and gravel overburden materials.

- (9) A representative of the soil engineer should observe the pile driving operations.

Spread Footing Alternate: The structure may be founded on spread footings placed on the dense to very dense sand and gravel strata. The following design and construction details should be observed for spread footing foundation system.

- (1) Footings placed on undisturbed sand and gravel strata may be designed for a maximum allowable soil bearing pressure of 6,000 psf.
- (2) Spread footings placed on granular soils should have a minimum footing dimension of not less than 36 inches.
- (3) Footings should be provided with adequate scour protection above their bearing elevation.
- (4) The lateral resistance of spread footing foundations placed on the undisturbed sand and gravel strata at the site will be a combination of the passive earth pressure against the side of the footing and the sliding resistance of the footing on the foundation materials. Sliding friction at the bottom of the footings can be taken as 0.4 times the vertical dead load. Passive pressure against the sides of the footings can be

calculated using an equivalent fluid pressure of 200 psf per foot of depth.

- (5) Based on experience, we estimate that total settlement for footings designed and constructed as discussed in this section will be approximately 3/4 inch.
- (6) The proposed footing elevations appear to be near or slightly above ground water level. Therefore, it may be necessary to dewater some footing excavations during construction. Dewatering should not be conducted by pumping from inside the footing excavations. This may decrease the supporting capacity of the soils.
- (7) A representative of the soil engineer should observe all footing excavations prior to concrete placement in order to evaluate the supporting capacity of foundation materials.


#### ABUTMENT AND WINGWALL BACKFILL

Backfill within 6 feet of the abutments and wingwalls should be Class 1 structural backfill in accordance with Colorado Standard Specifications for Road and Bridge Construction and should be compacted to a density of not less than 95% as determined in accordance with ASTM D698. Design lateral loads on wingwalls and abutments should be based on equivalent fluid pressure of 40 psf per foot.

#### LIMITATIONS

This report has been prepared in accordance with generally accepted soil and foundation engineering practices in this area for

use by the client for design purposes. The conclusions and recommendations submitted in this report are based upon the data obtained from the exploratory holes drilled at the locations indicated on the exploratory hole plan. The nature and extent of variations between the exploratory holes may not become evident until excavation is performed. If during construction, soil, rock and ground water conditions appear to be different from those described herein, this office should be advised at once so that re-evaluation of the recommendations may be made. We recommend on-site observation of excavations and foundation bearing strata by a soil engineer.



RJS:fs

CHEN AND ASSOCIATES, INC.

By Richard J. Suedkamp  
Richard J. Suedkamp, P.E.

Reviewed By David M. Jubenville  
David M. Jubenville, P.E.

## CONCLUSIONS

- (1) The proposed structure should be founded on piers drilled into bedrock and designed for maximum end bearing pressure of 40,000 psf, a skin friction of 4,000 psf and a minimum dead load pressure of 15,000 psf, with design and construction details as outlined.
- (2) Alternate foundation systems consisting of steel H-piles and designed for a maximum stress of 12,000 psi with tip reinforcement or spread footings placed on the lower sand and gravel strata and designed for a maximum bearing pressure of 6,000 psf may be used.
- (3) Trash fill varying in depth from 8 to 16 feet was encountered across the site south of Ralston Creek. This landfill material is generating sufficient quantities of combustible methane gas to be hazardous.

LEGEND:



Fill, man-made, sandy clay.



Trash fill, man-made, clay, metal, plastic, wood, paper organic materials.



Organic silt, slightly sandy, slightly clayey, stiff, moist to very moist, black.



Clay (CL), sandy, medium to stiff, moist to very moist, red to brown, occasionally gravel.



Gravel, silty to sandy, poorly graded, medium dense to very dense, wet, brown, scattered cobbles.



Weathered Claystone, sandy, firm to medium hard, moist, rust to brown.



Claystone, sandy, very hard, moist, gray.



Undisturbed drive sample. The symbol 15/12 indicates that 15 blows a 140 pound hammer falling 30 inches were required to drive the sampler 12 inches.



Standard Split Spoon Sample.




Indicates P.V.C. pipe installed to depth shown.















Indicates depth to free water.



Depth at which hole caved.







-  Fill, man-made, sandy clay.
-  Trash fill, man-made, clay, metal, plastic, wood, paper organic materials.
-  Organic silt, slightly sandy, slightly clayey, stiff, moist to very moist, black.
-  Clay (CL), sandy, medium to stiff, moist to very moist, red to brown, occasional gravel.
-  Gravel, silty to sandy, poorly graded, medium dense to very dense, wet, brown, scattered cobbles.
-  Weathered Claystone, sandy, firm to medium hard, moist, rust to brown.
-  Claystone, sandy, very hard, moist, gray.
-  Undisturbed drive sample. The symbol 15/12 indicates that 15 blows of a 140 pound hammer falling 30 inches were required to drive the sampler 12 inches.
-  Standard Split Spoon Sample.
-  Indicates P.V.C. pipe installed to depth shown.
-  Indicates depth to free water.
-  Depth at which hole caved.

#### NOTES:

1. Test holes were drilled on January 14 and 18, 1982 with a 6-inch diameter continuous flight hollow stem and 4-inch diameter continuous flight power auger.
2. Location of test holes are approximate and were determined by pacing from existing Croke Channel.
3. Elevations of test hole were determined by interpolation between contours on the plan provided.
4. The locations and elevations of test holes should be considered accurate only to the degree implied by the method used.
5. The stratification lines shown on the test hole logs represent the approximate boundary between soil types and the transition may be gradual.
6. Water level readings have been made in the drill holes at times and under conditions stated on the boring logs. These data have been reviewed and interpretations made in the text of this report. However, it must be noted that fluctuations in the level of the groundwater may occur due to variations in rain fall, temperature, and other factors at the time measurements were made.
7. WC = Water Content (%);  
DD = Dry Density (pcf);  
-200 = Percent Passing No. 200 Sieve;  
LL = Liquid Limit (%);  
PI = Plasticity Index (%);  
NP = Non Plastic;  
UC = Unconfined Compressive Strength (psf).

LEGEND & NOTES  
Fig. 3

## chen and associates, inc.




**CHEN AND ASSOCIATES**

**TABLE I**  
**SUMMARY OF LABORATORY TEST RESULTS**


Job No. 23,548  
Page 1 of 1

[illegible]

# chen and associates, inc.



SAMPLE OF Silty sand and gravel FROM Hole 1 at depth 15'



SAMPLE OF Clayey sand and gravel FROM Hole 2 at depth 14'

## **APPENDIX I**

### **FIELD GC (GAS CHROMATOGRAPH) DATA**



ERCE

Stanford Place 3, Suite 415  
4582 South Ulster St Pkwy  
Denver, CO 80237  
Attention: Mr. Dave Runyon

Mr. Runyon:

Here are the analytical results for the project done on site at 69th and Indiana in Arvada, Colorado. There were 6 water samples collected, and subsamples were taken from all of these and analyzed.

The instrumentation was calibrated for the SW-846 Method 8020 suite of analytes and unleaded gasoline by Method 8015. Of these, the benzene, toluene, ethylbenzene, and xylene subset (BTEX), and the total volatile hydrocarbons (TVH) are reported.

The PQL for the BTEX analytes is 5 ug/L and for the total volatile hydrocarbons it is 2 mg/L.

The sample analysis for boring #8 was lost due to generator failure. Notation in the analysis log book showed sample run (BH08 WS01) to be clean.

If there are any questions concerning the data or the analysis, please feel free to call.

Cordially,

A handwritten signature in cursive script that reads "Adam P. Macdonald".

Adam P. Macdonald  
Geochemist  
GEO Environmental  
(303) 279-4655

Client: ERCE  
Chromatographer: Adam P. Macdonald  
Analysis Date: December 26, 1991  
Analysis: SW-846 Method 8015/8020  
Location: 69th & Indiana Arvada, CO  
Sample Number: BH01 WS01

| Analyte                     | Concentration |
|-----------------------------|---------------|
| Benzene                     | <5 ug/L       |
| Toluene                     | <5 ug/L       |
| Ethylbenzene                | <5 ug/L       |
| Total Xylenes               | <5 ug/L       |
| Total Volatile Hydrocarbons | <2 mg/L       |

Client: ERCE  
Chromatographer: Adam P. Macdonald  
Analysis Date: December 26, 1991  
Analysis: SW-846 Method 8015/8020  
Location: 69th & Indiana Arvada, CO  
Sample Number: BH02 WS01

| Analyte                     | Concentration |      |
|-----------------------------|---------------|------|
| Benzene                     | <5            | ug/L |
| Toluene                     | <5            | ug/L |
| Ethylbenzene                | <5            | ug/L |
| Total Xylenes               | <5            | ug/L |
| Total Volatile Hydrocarbons | <2            | mg/L |

Client: ERCE  
Chromatographer: Adam P. Macdonald  
Analysis Date: December 26, 1991  
Analysis: SW-846 Method 8015/8020  
Location: 69th & Indiana Arvada, CO  
Sample Number: BH03 WS01

| Analyte                     | Concentration |
|-----------------------------|---------------|
| Benzene                     | <5 ug/L       |
| Toluene                     | <5 ug/L       |
| Ethylbenzene                | <5 ug/L       |
| Total Xylenes               | <5 ug/L       |
| Total Volatile Hydrocarbons | <2 mg/L       |


Client: ERCE  
Chromatographer: Adam P. Macdonald  
Analysis Date: December 26, 1991  
Analysis: SW-846 Method 8015/8020  
Location: 69th & Indiana Arvada, CO  
Sample Number: RALSTON CRK WS01

| Analyte                     | Concentration |
|-----------------------------|---------------|
| Benzene                     | <5 ug/L       |
| Toluene                     | <5 ug/L       |
| Ethylbenzene                | <5 ug/L       |
| Total Xylenes               | <5 ug/L       |
| Total Volatile Hydrocarbons | <2 mg/L       |

Client: ERCE  
Chromatographer: Adam P. Macdonald  
Analysis Date: December 26, 1991  
Analysis: SW-846 Method 8015/8020  
Location: 69th & Indiana Arvada, CO  
Sample Number: BH06 WS01


| Analyte                     | Concentration |
|-----------------------------|---------------|
| Benzene                     | <5 ug/L       |
| Toluene                     | <5 ug/L       |
| Ethylbenzene                | <5 ug/L       |
| Total Xylenes               | <5 ug/L       |
| Total Volatile Hydrocarbons | <2 mg/L       |

Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 1 PID  
 Conditions : 250NG BTEX CALIB STD  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225A1.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 07:06:29




| Component       | Number | Retention | Area    | External | Internal  | Units |
|-----------------|--------|-----------|---------|----------|-----------|-------|
| Benzene         | 1      | 16.425    | 1566.06 | 206.06   | 76.4270   | NG    |
| F3-Toluene surr | 2      | 17.100    | 500.43  | 404.42   | 150.0000  | NG    |
| Toluene         | 3      | 18.041    | 1360.70 | 179.04   | 66.4053   | NG    |
| Ethylbenzene    | 5      | 20.083    | 372.12  | 186.06   | 271.8159  | NG    |
| m-Xylene        | 6      | 20.275    | 806.92  | 216.91   | 316.8863  | NG    |
| p-Xylene        | 7      | 20.916    | 1161.59 | 223.38   | 326.3371  | NG    |
| BFB - surr      | 8      | 21.833    | 213.23  | 102.68   | 150.0000  | NG    |
| 7               |        |           | 5981.06 | 1518.56  | 1357.8717 |       |

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 2 FID  
 Conditions : 250NG BTEX CALIB STD  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225B1.CHR  
 Temperature : 8020.TEM  
 Components : 8020TPGH.CPT  
 Date : 12/26/1991  
 Time : 07:06:29




| Component      | Number | Retention | Area    | External | Internal | Units |
|----------------|--------|-----------|---------|----------|----------|-------|
| TOTL PRGBL H-C | 1      | 16.450    | 9788.09 | N/A      | N/A      |       |
| 1              |        |           | 9788.09 | N/A      | N/A      |       |

Control File : 8020.CUN  
 Operator : GED ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 1 PID  
 Conditions : 5 ML DI H2O BLANK (250NG SURR'S)  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225A2.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 09:26:18




| Component       | Number | Retention | Area   | External | Internal | Units |
|-----------------|--------|-----------|--------|----------|----------|-------|
| Benzene         | 1      | 16.391    | 26.05  | 3.43     | 0.8872   | NG    |
| F3-Toluene surr | 2      | 17.041    | 750.60 | 579.54   | 150.0000 | NG    |
| Toluene         | 3      | 17.941    | 57.50  | 7.57     | 1.9582   | NG    |
| m-Xylene        | 6      | 20.066    | 78.28  | 21.04    | 24.7398  | NG    |
| o-Xylene        | 7      | 20.691    | 69.00  | 13.27    | 15.6013  | NG    |
| BFB - surr      | 8      | 21.575    | 335.93 | 127.58   | 150.0000 | NG    |

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 1 PID  
 Conditions : BH01 WS01 5ML PURGE COLLECTED @ 1057 @ 12'  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225A3.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 11:11:45




| Component       | Number | Retention | Area    | External | Internal | Units |
|-----------------|--------|-----------|---------|----------|----------|-------|
| Benzene         | 1      | 16.391    | 38.15   | 5.02     | 1.3140   | NG    |
| E3-Toluene surr | 2      | 17.025    | 741.30  | 573.04   | 150.0000 | NG    |
| Toluene         | 3      | 17.941    | 34.55   | 4.55     | 1.1900   | NG    |
| m-Xylene        | 6      | 20.100    | 43.50   | 11.69    | 12.0738  | NG    |
| BFB - surr      | 8      | 21.625    | 423.13  | 145.28   | 150.0000 | NG    |
|                 | 5      |           | 1280.63 | 739.58   | 314.5778 |       |

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 1 PID  
 Conditions : RALSTON CRK WS01 5ML PURGE COLLT'D @1325@SURF.  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225A4.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 13:33:35




| Component       | Number | Retention | Area    | External | Internal | Units |
|-----------------|--------|-----------|---------|----------|----------|-------|
| F3-Toluene surr | 2      | 17.008    | 754.44  | 582.24   | 150.0000 | NG    |
| Toluene         | 3      | 17.908    | 32.62   | 4.29     | 1.1059   | NG    |
| m-Xylene        | 6      | 20.091    | 39.45   | 10.60    | 10.4128  | NG    |
| l - surr        | 8      | 21.600    | 460.04  | 152.77   | 150.0000 | NG    |
|                 | 4      |           | 1286.55 | 749.90   | 311.5188 |       |

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 1 PID  
 Conditions : BH03 WS01 5ML PURGE COLLECTED @ 1352 @ 18'  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225A5.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 14:21:11




| Component       | Number | Retention | Area    | External | Internal | Units |
|-----------------|--------|-----------|---------|----------|----------|-------|
| F3-Toluene surr | 2      | 17.075    | 732.33  | 566.76   | 150.0000 | NG    |
| Toluene         | 3      | 17.991    | 27.98   | 3.68     | 0.9742   | NG    |
| Surrogate       | 8      | 21.708    | 402.92  | 141.17   | 150.0000 | NG    |
|                 | 3      |           | 1163.23 | 711.61   | 300.9742 |       |

Control file : 8020.CON  
 Operator : GED ENVIRONMENTAL  
 Description : INSTRUMENT 5 CH 1 PID  
 Conditions : BH06 WS01 5ML PURGE COLLECTED @ 1453 @ 18'  
               : ERCE 69TH & INDIANA ARVADA, CO  
               : SW-846 METHOD 8015/8020  
 File : 1225A6.CHR  
 Temperature : 8020.TEM  
 Components : 8020A.CPT  
 Date : 12/26/1991  
 Time : 15:19:45




| Component       | Number | Retention | Area    | External | Internal | Units |
|-----------------|--------|-----------|---------|----------|----------|-------|
| Benzene         | 1      | 16.333    | 49.60   | 6.53     | 1.6474   | NG    |
| F3-Toluene surr | 2      | 16.958    | 771.58  | 594.23   | 150.0000 | NG    |
| I - surr        | 8      | 21.566    | 439.30  | 148.56   | 150.0000 | NG    |
|                 | 3      |           | 1260.48 | 749.32   | 301.6474 |       |

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 6 CH 1 PID  
 Conditions : 250NG BTEX CALIB STD  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225C1.CHR  
 Temperature : 8020.TEM  
 Components : 8020CD23.CPT  
 Date : 12/26/1991  
 Time : 07:07:01




| Component     | Number | Retention | Area    | External | Internal | Units |
|---------------|--------|-----------|---------|----------|----------|-------|
| Benzene       | 1      | 16.308    | 1413.79 | 251.12   | 74.7528  | NG    |
| Fluorobenzene | 2      | 17.025    | 541.97  | 503.90   | 150.0000 | NG    |
| Toluene       | 3      | 17.841    | 58.60   | N/A      | N/A      | NG    |
| Toluene       | 3      | 18.025    | 1231.83 | 250.59   | 74.5956  | NG    |
| Ethylbenzene  | 5      | 20.091    | 758.58  | 249.01   | 190.3119 | NG    |
| m/p-Xylene    | 6      | 20.283    | 1102.80 | 251.80   | 192.4420 | NG    |
| o-Xylene      | 7      | 20.916    | 1284.35 | 251.87   | 192.4984 | NG    |
| BFB - surr    | 8      | 21.825    | 509.49  | 196.27   | 150.0000 | NG    |

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 6 CH 2 FID  
 Conditions : 250NG BTEX CALIB STD  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225D1.CHR  
 Temperature : 8020.TEM  
 Components : 8020TPGH.CPT  
 Date : 12/26/1991  
 Time : 07:07:01




| Component      | Number | Retention | Area    | External | Internal | Units |
|----------------|--------|-----------|---------|----------|----------|-------|
| TOTL PRGBL H-C | 1      | 16.375    | 6655.88 | N/A      | N/A      |       |
| 1              |        |           | 6655.88 | N/A      | N/A      |       |

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 6 CH 1 PID  
 Conditions : 5000NG BTEX CALIB STD (250NG SURR'S)  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225C3.CHR  
 Temperature : 8020.TEM  
 Components : 8020CD23.CPT  
 Date : 12/26/1991  
 Time : 10:50:50




| Component          | Number | Retention | Area     | External | Internal  | Units |
|--------------------|--------|-----------|----------|----------|-----------|-------|
| Toluene            | 1      | 16.083    | 17514.46 | 5001.31  | 1943.2584 | NG    |
| Fluorobenzene surr | 2      | 16.816    | 403.14   | 386.05   | 150.0000  | NG    |
| Toluene            | 3      | 17.766    | 15964.05 | 5001.31  | 1943.2552 | NG    |
| Ethylbenzene       | 5      | 19.758    | 7608.69  | 4999.09  | 3967.3364 | NG    |
| m/p-Xylene         | 6      | 19.958    | 8484.13  | 5002.66  | 3970.1669 | NG    |
| o-Xylene           | 7      | 20.591    | 12297.65 | 4998.99  | 3967.2535 | NG    |
| BFB - surr         | 8      | 21.225    | 91.21    | 51.07    | 150.0000  | NG    |
| BFB - surr         | 8      | 21.458    | 488.58   | 189.01   | 150.0000  | NG    |

Control file : 8020.CON  
 Operator : GEO ENVIRONMENTAL  
 Description : INSTRUMENT 6 CH 1 PID  
 Conditions : 5ML DI H2O BLANK (250NG SURR'S)  
               : ERCE 69TH & INDIANA ARVADA, CO  
               : SW-846 METHOD 8015/8020  
 File : 1225C4.CHR  
 Temperature : 8020.TEM  
 Components : 8020CD23.CPT  
 Date : 12/26/1991  
 Time : 11:29:45



| Component      | Number | Retention | Area    | External | Internal | Units |
|----------------|--------|-----------|---------|----------|----------|-------|
| Benzene        | 1      | 16.366    | 83.15   | N/A      | N/A      | NG    |
| o-Toluene surr | 2      | 17.166    | 814.00  | 734.82   | 150.0000 | NG    |
| Toluene        | 3      | 18.133    | 92.30   | N/A      | N/A      | NG    |
| m/p-Xylene     | 6      | 20.358    | 68.40   | N/A      | N/A      | NG    |
| o-Xylene       | 7      | 20.983    | 35.00   | N/A      | N/A      | NG    |
| BFB - surr     | 8      | 21.908    | 785.03  | 291.92   | 150.0000 | NG    |
|                |        |           | 1877.88 | 67.79    | 296.0000 |       |

Control file : 8020.CON  
 Operator : GED ENVIRONMENTAL  
 Description : INSTRUMENT 6 CH 1 PID  
 Conditions : RH02 WS01 5ML PURGE COLLECTED @ 1330 @ 15'  
 : ERCE 69TH & INDIANA ARVADA, CO  
 : SW-846 METHOD 8015/8020  
 File : 1225C6.CHR  
 Temperature : 8020.TEM  
 Components : 8020C.CPT  
 Date : 12/26/1991  
 Time : 14:43:34



| Component           | Number | Retention | Area   | External | Internal | Units |
|---------------------|--------|-----------|--------|----------|----------|-------|
| 1,2-Dichlorobenzene | 1      | 16.391    | 61.62  | N/A      | N/A      | NG    |
| 1,4-Dichlorobenzene | 2      | 17.033    | 994.28 | 887.86   | 150.0000 | NG    |
| Toluene             | 3      | 18.000    | 78.47  | N/A      | N/A      | NG    |
| m/p-Xylene          | 6      | 20.258    | 112.90 | N/A      | N/A      | NG    |
| o-Xylene            | 7      | 20.883    | 29.75  | N/A      | N/A      | NG    |
| BFB - surr          | 8      | 21.783    | 749.35 | 279.53   | 150.0000 | NG    |